Gateway Documentation - Deposits Service

Oracle FLEXCUBE Universal Banking

Release FCUBS_12.0.3.0.0

[April] [2014]

Table Of Contents

1. BACKGROUND **1**

2. FCUBSLDService **2**

2.1. QueryLDPaymentSim **2**

2.1.1. LD-QueryLDPaymentSimReq-IO-MSG.xsd *2*

2.1.2. LD-QueryLDPaymentSimRes-Full-MSG.xsd *11*

2.2. QueryLDSIMContract **153**

2.2.1. LD-QueryLDSIMContractReq-IO-MSG.xsd *153*

2.2.2. LD-QueryLDSIMContractRes-Full-MSG.xsd *303*

2.3. QueryProduct **489**

2.3.1. LD-QueryProduct-Req-IO-MSG.xsd *489*

2.3.2. LD-QueryProduct-Res-Full-MSG.xsd *495*

2.4. ReopenLDBrnPrm **592**

2.4.1. LD-ReopenLDBrnPrm-Req-Full-MSG.xsd *592*

2.4.2. LD-ReopenLDBrnPrm-Req-IO-MSG.xsd *603*

2.4.3. LD-ReopenLDBrnPrm-Res-Full-MSG.xsd *610*

2.4.4. LD-ReopenLDBrnPrm-Res-PK-MSG.xsd *622*

2.5. AuthFeeAccrualLDContract **631**

2.5.1. LD-AuthoriseFeeAccrual-Req-Full-MSG.xsd *631*

2.5.2. LD-AuthoriseFeeAccrual-Res-Full-MSG.xsd *678*

2.6. AuthorizeBrnPrm **727**

2.6.1. LD-AuthorizeBrnPrm-Req-Full-MSG.xsd *727*

2.6.2. LD-AuthorizeBrnPrm-Req-IO-MSG.xsd *738*

2.6.3. LD-AuthorizeBrnPrm-Res-Full-MSG.xsd *744*

2.6.4. LD-AuthorizeBrnPrm-Res-PK-MSG.xsd *757*

2.7. AuthorizeLDBrnPrm **766**

2.7.1. LD-AuthorizeLDBrnPrm-Req-Full-MSG.xsd *766*

2.7.2. LD-AuthorizeLDBrnPrm-Req-IO-MSG.xsd *777*

2.7.3. LD-AuthorizeLDBrnPrm-Res-Full-MSG.xsd *784*

2.7.4. LD-AuthorizeLDBrnPrm-Res-PK-MSG.xsd *796*

2.8. AuthorizeProduct **805**

2.8.1. LD-AuthorizeProduct-Req-Full-MSG.xsd *805*

2.8.2. LD-AuthorizeProduct-Req-IO-MSG.xsd *900*

2.8.3. LD-AuthorizeProduct-Res-Full-MSG.xsd *906*

2.8.4. LD-AuthorizeProduct-Res-PK-MSG.xsd *1003*

2.9. CloseLDBrnPrm **1012**

2.9.1. LD-CloseLDBrnPrm-Req-Full-MSG.xsd *1012*

2.9.2. LD-CloseLDBrnPrm-Req-IO-MSG.xsd *1023*

2.9.3. LD-CloseLDBrnPrm-Res-Full-MSG.xsd *1030*

2.9.4. LD-CloseLDBrnPrm-Res-PK-MSG.xsd *1042*

2.10. CreateBrnPrm **1051**

2.10.1. LD-CreateBrnPrm-Req-Full-MSG.xsd *1051*

2.10.2. LD-CreateBrnPrm-Req-IO-MSG.xsd *1062*

2.10.3. LD-CreateBrnPrm-Res-Full-MSG.xsd *1071*

2.10.4. LD-CreateBrnPrm-Res-PK-MSG.xsd *1084*

2.11. CreateFeeAccrualLDContract **1095**

2.11.1. LD-CreateFeeAccrual-Req-Full-MSG.xsd *1095*

2.11.2. LD-CreateFeeAccrual-Req-MSG.xsd *1142*

2.11.3. LD-CreateFeeAccrual-Res-Full-MSG.xsd *1151*

2.11.4. LD-CreateFeeAccrual-Res-MSG.xsd *1200*

2.12. CreateLDBrnPrm **1212**

2.12.1. LD-CreateLDBrnPrm-Req-Full-MSG.xsd *1212*

2.12.2. LD-CreateLDBrnPrm-Req-IO-MSG.xsd *1223*

2.12.3. LD-CreateLDBrnPrm-Res-Full-MSG.xsd *1232*

2.12.4. LD-CreateLDBrnPrm-Res-PK-MSG.xsd *1244*

2.13. CreateLDPaymentSim **1255**
2.13.1. LD-CreateLDPaymentSim-Req-Full-MSG.xsd *1255*
2.13.2. LD-CreateLDPaymentSim-Res-PK-MSG.xsd *1396*
2.13.3. LD-CreateLDPaymentSimReq-IO-MSG.xsd *1407*
2.13.4. LD-CreateLDPaymentSimRes-Full-MSG.xsd *1416*
2.14. CreateProduct **1558**
2.14.1. LD-CreateProduct-Req-Full-MSG.xsd *1558*
2.14.2. LD-CreateProduct-Req-IO-MSG.xsd *1653*
2.14.3. LD-CreateProduct-Res-Full-MSG.xsd *1736*
2.14.4. LD-CreateProduct-Res-PK-MSG.xsd *1833*
2.15. DeleteBrnPrm **1918**
2.15.1. LD-DeleteBrnPrm-Req-Full-MSG.xsd *1918*
2.15.2. LD-DeleteBrnPrm-Req-IO-MSG.xsd *1929*
2.15.3. LD-DeleteBrnPrm-Res-Full-MSG.xsd *1935*
2.15.4. LD-DeleteBrnPrm-Res-PK-MSG.xsd *1948*
2.16. DeleteFeeAccrualLDContract **1957**
2.16.1. LD-DeleteFeeAccrual-Req-Full-MSG.xsd *1957*
2.16.2. LD-DeleteFeeAccrual-Req-MSG.xsd *2004*
2.16.3. LD-DeleteFeeAccrual-Res-Full-MSG.xsd *2013*
2.16.4. LD-DeleteFeeAccrual-Res-MSG.xsd *2062*
2.17. DeleteLDBrnPrm **2074**
2.17.1. LD-DeleteLDBrnPrm-Req-Full-MSG.xsd *2074*
2.17.2. LD-DeleteLDBrnPrm-Req-IO-MSG.xsd *2085*
2.17.3. LD-DeleteLDBrnPrm-Res-Full-MSG.xsd *2091*
2.17.4. LD-DeleteLDBrnPrm-Res-PK-MSG.xsd *2103*
2.18. ReverseLDPayment **2112**
2.18.1. LDPayment-Reverse-Res-Full-MSG.xsd *2112*
2.18.2. LDPayment-Reverse-Res-IOPK-MSG.xsd *2255*
2.18.3. LDPayment-Reverse-Req-Full-MSG.xsd *2266*
2.18.4. LDPayment-Reverse-Req-IO-MSG.xsd *2407*
2.19. AuthProvisionLDContract **2416**
2.19.1. LDProvision-Authorise-Req-Full-MSG.xsd *2416*
2.19.2. LDProvision-Authorise-Res-Full-MSG.xsd *2425*
2.20. CreateProvisionLDContract **2436**
2.20.1. LDProvision-Create-Req-Full-MSG.xsd *2436*
2.20.2. LDProvision-Create-Req-MSG.xsd *2445*
2.20.3. LDProvision-Create-Res-Full-MSG.xsd *2454*
2.20.4. LDProvision-Create-Res-MSG.xsd *2465*
2.21. ModifyProvisionLDContract **2479**
2.21.1. LDProvision-Modify-Req-Full-MSG.xsd *2479*
2.21.2. LDProvision-Modify-Req-MSG.xsd *2488*
2.21.3. LDProvision-Modify-Res-Full-MSG.xsd *2497*
2.21.4. LDProvision-Modify-Res-MSG.xsd *2508*
2.22. DeleteLDPaymentSim **2522**
2.22.1. LD-DeleteLDPaymentSim-Req-Full-MSG.xsd *2522*
2.22.2. LD-DeleteLDPaymentSim-Res-PK-MSG.xsd *2663*
2.22.3. LD-DeleteLDPaymentSimReq-IO-MSG.xsd *2674*
2.22.4. LD-DeleteLDPaymentSimRes-Full-MSG.xsd *2683*
2.23. DeleteLDSIMContract **2825**
2.23.1. LD-DeleteLDSIMContract-Req-Full-MSG.xsd *2825*
2.23.2. LD-DeleteLDSIMContract-Res-PK-MSG.xsd *3010*
2.23.3. LD-DeleteLDSIMContractReq-IO-MSG.xsd *3162*
2.23.4. LD-DeleteLDSIMContractRes-Full-MSG.xsd *3312*
2.24. DeleteProduct **3498**
2.24.1. LD-DeleteProduct-Req-Full-MSG.xsd *3498*
2.24.2. LD-DeleteProduct-Req-IO-MSG.xsd *3593*
2.24.3. LD-DeleteProduct-Res-Full-MSG.xsd *3599*
2.24.4. LD-DeleteProduct-Res-PK-MSG.xsd *3696*

2.25. LDActivateSimulate **3705**
2.25.1. LD-LDActivateSimulate-Req-Full-MSG.xsd *3705*
2.25.2. LD-LDActivateSimulate-Res-PK-MSG.xsd *3890*
2.25.3. LD-LDActivateSimulateReq-IO-MSG.xsd *4042*
2.25.4. LD-LDActivateSimulateRes-Full-MSG.xsd *4192*
2.26. LDInactivateSimulate **4378**
2.26.1. LD-LDInactivateSimulate-Req-Full-MSG.xsd *4378*
2.26.2. LD-LDInactivateSimulate-Res-PK-MSG.xsd *4563*
2.26.3. LD-LDInactivateSimulateReq-IO-MSG.xsd *4715*
2.26.4. LD-LDInactivateSimulateRes-Full-MSG.xsd *4865*
2.27. LDVamiCreateSim **5051**
2.27.1. LD-LDVamiCreateSim-Req-Full-MSG.xsd *5051*
2.27.2. LD-LDVamiCreateSim-Res-PK-MSG.xsd *5190*
2.27.3. LD-LDVamiCreateSimReq-IO-MSG.xsd *5318*
2.27.4. LD-LDVamiCreateSimRes-Full-MSG.xsd *5444*
2.28. LDVamiDeleteSim **5585**
2.28.1. LD-LDVamiDeleteSim-Req-Full-MSG.xsd *5585*
2.28.2. LD-LDVamiDeleteSim-Res-PK-MSG.xsd *5724*
2.28.3. LD-LDVamiDeleteSimReq-IO-MSG.xsd *5852*
2.28.4. LD-LDVamiDeleteSimRes-Full-MSG.xsd *5978*
2.29. LDVamiQuerySim **6119**
2.29.1. LD-LDVamiQuerySimReq-IO-MSG.xsd *6119*
2.29.2. LD-LDVamiQuerySimRes-Full-MSG.xsd *6269*
2.30. ModifyBrnPrm **6455**
2.30.1. LD-ModifyBrnPrm-Req-Full-MSG.xsd *6455*
2.30.2. LD-ModifyBrnPrm-Req-IO-MSG.xsd *6466*
2.30.3. LD-ModifyBrnPrm-Res-Full-MSG.xsd *6475*
2.30.4. LD-ModifyBrnPrm-Res-PK-MSG.xsd *6488*
2.31. ModifyFeeAccrualLDContract **6499**
2.31.1. LD-ModifyFeeAccrual-Req-Full-MSG.xsd *6499*
2.31.2. LD-ModifyFeeAccrual-Req-MSG.xsd *6546*
2.31.3. LD-ModifyFeeAccrual-Res-Full-MSG.xsd *6555*
2.31.4. LD-ModifyFeeAccrual-Res-MSG.xsd *6604*
2.32. ModifyLDBrnPrm **6616**
2.32.1. LD-ModifyLDBrnPrm-Req-Full-MSG.xsd *6616*
2.32.2. LD-ModifyLDBrnPrm-Req-IO-MSG.xsd *6627*
2.32.3. LD-ModifyLDBrnPrm-Res-Full-MSG.xsd *6636*
2.32.4. LD-ModifyLDBrnPrm-Res-PK-MSG.xsd *6648*
2.33. ModifyProduct **6659**
2.33.1. LD-ModifyProduct-Req-Full-MSG.xsd *6659*
2.33.2. LD-ModifyProduct-Req-IO-MSG.xsd *6754*
2.33.3. LD-ModifyProduct-Res-Full-MSG.xsd *6832*
2.33.4. LD-ModifyProduct-Res-PK-MSG.xsd *6929*
2.34. QueryBrnPrm **7009**
2.34.1. LD-QueryBrnPrm-Req-IO-MSG.xsd *7009*
2.34.2. LD-QueryBrnPrm-Res-Full-MSG.xsd *7015*
2.35. QueryFeeAccrualLDContract **7028**
2.35.1. LD-QueryFeeAccrual-Req-MSG.xsd *7028*
2.35.2. LD-QueryFeeAccrual-Res-Full-MSG.xsd *7037*
2.36. QueryLDBrnPrm **7086**
2.36.1. LD-QueryLDBrnPrm-Req-IO-MSG.xsd *7086*
2.36.2. LD-QueryLDBrnPrm-Res-Full-MSG.xsd *7092*
2.37. QueryProvisionLDContract **7105**
2.37.1. LDProvision-Query-Req-MSG.xsd *7105*
2.37.2. LDProvision-Query-Res-Full-MSG.xsd *7114*
2.38. ReassignLDContract **7125**
2.38.1. LDReassign-Create-Req-Full-MSG.xsd *7125*

2.38.2. LDReassign-Create-Req-MSG.xsd *7132*
2.38.3. LDReassign-Create-Res-Full-MSG.xsd *7139*
2.38.4. LDReassign-Create-Res-MSG.xsd *7148*
2.39. ReverseFeeAccrualLDContract **7158**
2.39.1. LD-ReverseFeeAccrual-Req-Full-MSG.xsd *7158*
2.39.2. LD-ReverseFeeAccrual-Req-MSG.xsd *7205*
2.39.3. LD-ReverseFeeAccrual-Res-Full-MSG.xsd *7214*
2.39.4. LD-ReverseFeeAccrual-Res-MSG.xsd *7263*
2.40. AuthorizeLDContract **7275**
2.40.1. LDContract-Auth-Req-Full-MSG.xsd *7275*
2.40.2. LDContract-Auth-Req-MSG.xsd *7290*
2.40.3. LDContract-Auth-Res-Full-MSG.xsd *7298*
2.40.4. LDContract-Auth-Res-PK-MSG.xsd *7314*
2.41. DeleteLDContract **7324**
2.41.1. LDContract-Delete-Req-Full-MSG.xsd *7324*
2.41.2. LDContract-Delete-Req-IO-MSG.xsd *7509*
2.41.3. LDContract-Delete-Res-Full-MSG.xsd *7659*
2.41.4. LDContract-Delete-Res-IOPK-MSG.xsd *7845*
2.42. ModifyLDContract **7997**
2.42.1. LDContract-Master-Modify-Full-MSG.xsd *7997*
2.42.2. LDContract-Modify-Req-IO-MSG.xsd *8182*
2.42.3. LDContract-Modify-Res-Full-MSG.xsd *8332*
2.42.4. LDContract-Modify-Res-IOPK-MSG.xsd *8518*
2.43. CreateLDContract **8670**
2.43.1. LDContract-Master-Req-Full-MSG.xsd *8670*
2.43.2. LDContract-Master-Req-IO-MSG.xsd *8855*
2.43.3. LDContract-Master-Res-Full-MSG.xsd *9005*
2.43.4. LDContract-Master-Res-PK-MSG.xsd *9191*
2.44. QueryLDContract **9343**
2.44.1. LDContract-Query-Req-IO-MSG.xsd *9343*
2.44.2. LDContract-Query-Res-Full-MSG.xsd *9493*
2.45. ReverseLDContract **9679**
2.45.1. LDContract-Reverse-Req-Full-MSG.xsd *9679*
2.45.2. LDContract-Reverse-Req-IO-MSG.xsd *9864*
2.45.3. LDContract-Reverse-Res-Full-MSG.xsd *10014*
2.45.4. LDContract-Reverse-Res-IOPK-MSG.xsd *10200*
2.46. RolloverLDContract **10352**
2.46.1. LDContract-Rollover-Req-Full-MSG.xsd *10352*
2.46.2. LDContract-Rollover-Req-IO-MSG.xsd *10537*
2.46.3. LDContract-Rollover-Res-Full-MSG.xsd *10687*
2.46.4. LDContract-Rollover-Res-IOPK-MSG.xsd *10873*
2.47. LDVamiAuthorize **11025**
2.47.1. LDContractVAMI-Auth-Req-Full-MSG.xsd *11025*
2.47.2. LDContractVAMI-Auth-Res-Full-MSG.xsd *11164*
2.48. LDDeleteVami **11305**
2.48.1. LDContractVAMI-Delete-Req-Full-MSG.xsd *11305*
2.48.2. LDContractVAMI-Delete-Req-IO-MSG.xsd *11444*
2.48.3. LDContractVAMI-Delete-Res-Full-MSG.xsd *11570*
2.48.4. LDContractVAMI-Delete-Res-IOPK-MSG.xsd *11711*
2.49. LDVamiContract **11839**
2.49.1. LDContractVAMI-Req-Full-MSG.xsd *11839*
2.49.2. LDContractVAMI-Req-IO-MSG.xsd *11978*
2.49.3. LDContractVAMI-Res-Full-MSG.xsd *12104*
2.49.4. LDContractVAMI-Res-IOPK-MSG.xsd *12245*
2.50. AuthLDPayment **12373**
2.50.1. LDPayment-Auth-Req-Full-MSG.xsd *12373*
2.50.2. LDPayment-Auth-Res-MSG.xsd *12386*

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSLDService of CD-Module

2.FCUBSLDService

Deposits ServiceDeposits Service

2.1.QueryLDPaymentSim

Query of Payment simulation

2.1.1.LD-QueryLDPaymentSimReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *FCCREF*
    - *XREF*
    - *TOTPAID*
    - *VALDT*
    - *LIMITDT*
    - *Payment-Breakup*
      - *COMP*
      - *AMTDUE*
      - *OVERDUE*
      - *AMTPAID*
      - *INTPREPAY*
      - *TAXPAID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Includes Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Includes External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid.
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Payment-Breakup

Attribute	**Description**	
Name	Payment-Breakup	
Datatype		
Description	Includes Payment Break up Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

AMTDUE

Attribute	**Description**	
Name	AMTDUE	
Datatype	Number	
Description	Indicates Amount Due.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

OVERDUE

Attribute	**Description**	
Name	OVERDUE	
Datatype	Number	
Description	Indicates Over Due.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTPREPAY

Attribute	Description
Name	INTPREPAY
Datatype	Number
Description	Indicates the Interest Prepaid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

2.1.2.LD-QueryLDPaymentSimRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *XREF*
    - *FCCREF*
    - *CPTY*
    - *STATUS*
    - *OSBAL*
    - *CCY*
    - *OLDMATDT*
    - *NEWMATDT*
    - *EFFFROM*
    - *PREPMTBASIS*
    - *PREPMTEFFFROM*
    - *VALDT*
    - *TOTPAID*
    - *LIMITDT*
    - *DISCRATE*
    - *TOTPREPAID*
    - *LIMITAMT*
    - *LIQDFACEVAL*

PREPMTPENRATE
PREPMTPENAMT
PREPMTADJAMT1
PREPMTADJAMT2
PAYMNTREM
LCYEQVTTOTPAID
LCYEQVTTOTPREPAID
LCYEQVTLIMITAMT
LCYEQVTLIQDFACEVALUE
OSBALREP
SYNDNO
SUBSYSTEMSTAT
CURRPMNT
TOTPAMNT
Payment-Breakup
- *FCCREF*
- *COMP*
- *AMTDUE*
- *AMTPAID*

Schedule-Details
- *FCCREF*
- *SCOMP*
- *DUEDT*
- *AMTDUE*
- *AMTSETTL*

Contract-Event-Log
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *REVR_MAKERID*
- *REVR_CHECKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*
- *COSTCOD1*

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*
    - *TAXCCY*
    - *VALDT*
    - *COMPDT*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*

- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*

MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

OSBAL

Attribute	**Description**	
Name	OSBAL	
Datatype	Number	
Description	Indicates Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

OLDMATDT

Attribute	**Description**
Name	OLDMATDT
Datatype	Date
Description	Indicates Old Maturity Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEWMATDT

Attribute	**Description**	
Name	NEWMATDT	
Datatype	Date	
Description	Indicates New Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EFFFROM

Attribute	**Description**	
Name	EFFFROM	
Datatype	String	
Description	Indicates Effective From	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	2

TOP

PREPMTBASIS

Attribute	**Description**	
Name	PREPMTBASIS	
Datatype	String	
Description	Indicates Recomputation Basis	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PREPMTEFFFROM

Attribute	**Description**	
Name	PREPMTEFFFROM	
Datatype	String	
Description	Indicates Prepayment Effective From	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCRATE

Attribute	Description
Name	DISCRATE
Datatype	Number
Description	Indicates Disc. Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TOTPREPAID

Attribute	Description
Name	TOTPREPAID
Datatype	Number
Description	Indicates Amount Prepaid

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDFACEVAL

Attribute	Description
Name	LIQDFACEVAL
Datatype	Number
Description	Indicates Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

PREPMTPENRATE

Attribute	Description
Name	PREPMTPENRATE
Datatype	Number
Description	Indicates Prepayment Penalty Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTPENAMT

Attribute	Description
Name	PREPMTPENAMT
Datatype	Number
Description	Indicates Penalty Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT1

Attribute	Description
Name	PREPMTADJAMT1
Datatype	Number
Description	Indicates Adjust Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT2

Attribute	Description
Name	PREPMTADJAMT2
Datatype	Number
Description	Indicates Addl. Adj. Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCYEQVTTOTPAID

Attribute	Description
Name	LCYEQVTTOTPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Total Paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LCYEQVTTOTPREPAID

Attribute	**Description**	
Name	LCYEQVTTOTPREPAID	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Amount Prepaid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LCYEQVTLIMITAMT

Attribute	**Description**	
Name	LCYEQVTLIMITAMT	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Limit Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

LCYEQVTLIQDFACEVALUE

Attribute	**Description**	
Name	LCYEQVTLIQDFACEVALUE	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Liquidated Nominal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

OSBALREP

Attribute	**Description**
Name	OSBALREP
Datatype	Number
Description	Indicates O/S Bal- Rep

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SYNDNO

Attribute	Description
Name	SYNDNO
Datatype	Number
Description	Indicates Syndication Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates SubSystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CURRPMNT

Attribute	Description
Name	CURRPMNT
Datatype	Number
Description	Indicates Current Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TOTPAMNT

Attribute	Description
Name	TOTPAMNT
Datatype	Number
Description	Indicates Total Payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	Includes Payment Break Up details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates Amount Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedules details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DUEDT

Attribute	Description
Name	DUEDT

Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Payment Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	Description	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	Description	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	Description	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	Description	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance Rate details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date

Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Field details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Inlcudes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Inlcudes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Inlcudes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.QueryLDSIMContract

Query of deposit Contract simulation

2.2.1.LD-QueryLDSIMContractReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*

LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP

UREF

PCREF

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*

XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6

RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1

INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3

REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER

- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*

- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*
  - *AMT*

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description

Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date

Description	Indicate Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3LBL3

Attribute	**Description**	
Name	FUNDMIS3LBL3	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4LBL4

Attribute	**Description**	
Name	FUNDMIS4LBL4	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS5LBL5

Attribute	**Description**	
Name	FUNDMIS5LBL5	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS6LBL6

Attribute	**Description**
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	**Description**	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	**Description**
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description	Indicates the Effective date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLMATDT

Attribute	**Description**	
Name	ROLLMATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ROLLNOTDAYS

Attribute	**Description**	
Name	ROLLNOTDAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ROLLICCFFROM

Attribute	**Description**	
Name	ROLLICCFFROM	
Datatype	String	
Description	Indicates ICCF Rollover Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

ROLLBY

Attribute	**Description**
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.2.2.LD-QueryLDSIMContractRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

- CCYDESC
- Contract-Rollover
  - ROLLAMT
  - ROLLMATDT
  - ROLLNOTDAYS
  - UPDATEUTIL
  - LIQDODSCHD
  - DRAWDOWNNO
  - ROLLBY
  - ROLLINTST
  - ROLLMECH
  - ROLLMETHD
  - ROLLTYPE
  - ROLLAMTTYP
  - ROLLMATTYPE
  - ROLLICCFFROM
  - SCHDBASIS
  - TRESPLAMT
  - APPROLLTAX
  - NEWCOMPALL
  - ROLLMATDAYS
  - APPCHG
  - REFRATE
  - Rvrintrates
    - INTCOMP
    - DEFFROM
    - RATETYPE
    - INTBASIS
  - INTBAS
    - INTCOMP
    - ROLLOIFROM
    - RATETYPE
    - RATEUSCD
    - INTRATE
    - INTBASIS
    - RATECD
    - SPREAD
    - MARGIN
    - AMT
    - ROLSTENOR
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description

Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String
Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLMETHD

Attribute	Description	
Name	ROLLMETHD	
Datatype	String	
Description	Indicates Rollover Method	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates rollover type Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REFRATE

Attribute	Description	
Name	REFRATE	
Datatype	Number	
Description	Indicates Refinance Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	11

TOP

Rvrintrates

Attribute	Description	
Name	Rvrintrates	
Datatype		
Description	Includes Rollover Interest Rates details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DEFFROM

Attribute	Description	
Name	DEFFROM	
Datatype	String	
Description	Indicates Basis Product : P Contract : C User Rate : U	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 5 totalDigits: 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxInclusive: 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.QueryProduct

Query of Loans and Deposit Product

2.3.1.LD-QueryProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Query-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.3.2.LD-QueryProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-IO*
      - *PRDCD*
    - *Product-Details-Full*
      - *PRDCD*
      - *PRDDESC*
      - *PRDTYP*
      - *PROD_TYPE_DESC*
      - *PRDSLG*
      - *PRDGRP*
      - *DESC*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *RTCODEPRFERD*
      - *PMNTMTHD*
      - *PRDSCHTYP*
      - *DFLTCLSTR*
      - *ACCRFREQ*

ACCRSTRTMNTH
ACCRSTRTDT
COLCTDRNGAMNDT
MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ

TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*

- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*
- *MORATRMPERD*

Liquidation-Order

- *CMPNT*
- *LIQORDR*

Grace-Levels

- *LVLNO*
- *NOOFUNITS*
- *UNIT*

Ccy-Days-Details

- *CCY*
- *EXCRATFXNGDAYS*
- *INTRATFXNGDAYS*

Trs-Components-Details

- *COMPNT*

Status-Master-Details

- *STATUS*
- *TRANSACTIONCD*
- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *COMPLETEACCRUALS*
- *TRNSFRCAPITLIZDINCM*
- *AUTOFRWD*
- *AUTOREVERSE*
- *DERVTNRUL*
- *RBKPROVSN*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*
  - *GLDESC*
  - *TRNSFERGL*
  - *DWNWRDTRANSFERFRMGL*
  - *DWNWRDTRANSFERTOGL*
- *Acc-Status-Gl-Details*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Tax-Scheme

- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *RUL*
  - *AMNTTAG*
  - *BASISAMNTTAG*
  - *COMPTATIONEVNT*
  - *TYP*
  - *Ccy-Tax-Details*
    - *CCY*
    - *MAXTAXINTPERD*
    - *PERDUNIT*
    - *MININTTAXAMT*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*
  - *STPAPPLICTION*
  - *RESETTENOR*
  - *BRWLENDIND*
  - *LVLNO*
  - *PREPMTMETD*
  - *PROPREQD*
  - *MARGNBASIS*
  - *MARGNAPPLN*
  - *RATECALCTYP*
  - *ACQREQD*
  - *CHNGDRGAMNDMNT*
  - *SHWNINCNTRTMAINSCR*
  - *BLKAMTFLG*
  - *DEPORATECD*
  - *DISCACCRAPP*
  - *UNIT*
  - *NOUNIT*
  - *EVNT*
  - *COMPNENT*
  - *COMPNENTDESC*
  - *RUL*
  - *COLTYP*
  - *EVNTDESC*

- RULEDESC
- Interest-Ccy-Preferences
  - CCY
  - DEFRAT
  - MINRATE
  - MAXRAT
  - DFLTSPRD
  - MINSPRD
  - MAXSPRD
  - INTBASIS
  - DENOMBASIS
  - BAS366
  - NOOFINTPRD
  - PRPMTRT
- Product-Accrual-Fee
  - Accrual-Fee-Details
    - LIQINT
    - LIQPRNCHNG
    - DISCACCRAPP
    - ACCRREQD
    - BASISAMT
    - ENDDTINP
    - RULFEE
    - FEETYP
    - ACCRFREQ
    - FREQVAL
    - COMP
    - STPASSN
    - COMPNENTDESC
- Product-Charges
  - Charge-Details
    - CHGTYP
    - THRDPTYTY
    - DRCRTYPE
    - NTCNSINDI
    - NETCONSPLSMINS
    - SWIFTQLF
    - SETTCCY
    - DFTWAIV
    - ALWRULAMND
    - AMNDAFTRASSOC
    - ALWAMTAMND
    - AMNDAFTRAPPL
    - STPASOCIATN

ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD
EVENTDESC
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
DESC
GENTIME
SUPRS
PRIOR

CHGREQD

Role-To-Head-Mapping

CLASCD

CLASDESC

Mapping-Details

ACCTRL

ROLDESC

ACCTHD

GLDESC

Prod-Cust-Restrictions

CATGLIS

CLASCD

Cust-Categories

CATGDSAW

DESCRIPTION

Customers

CSTID

CUSTNAME

ALWD

Branch-Ccy-Restrictions

CCYLST

BRNLST

CLASCD

CLASDESC

Branch-List

BRNDISALOW

BRNNAME

Ccy-List

BGTDLCCY

CCYNAME

Product-Fields

Field-Details

FLDNUM

FLDNAME

Product-Discount-Accrual

CLASCD

CLASDESC

CLSDFLT

Disc-Accr-Details

DISCACCRREQD

ACCRFREQ

PREPAYTBDTREAT

ACQTYP

Ccy-Preferences

CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Query-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Query Full details

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDTYP

Attribute	Description	
Name	PRDTYP	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROD_TYPE_DESC

Attribute	Description	
Name	PROD_TYPE_DESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description	Indicates Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,M

TOP

PMNTMTHD

Attribute	**Description**	
Name	PMNTMTHD	
Datatype	String	
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,D,T,

TOP

PRDSCHTYP

Attribute	**Description**
Name	PRDSCHTYP
Datatype	String

Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number

Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String
Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String

Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description

Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREPMNTPNLTY

Attribute	**Description**	
Name	PREPMNTPNLTY	
Datatype	String	
Description	Indicates Prepayment Penalty Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RECMPUTESCHDLS

Attribute	**Description**	
Name	RECMPUTESCHDLS	
Datatype	String	
Description	Indicates Recompute Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FWDDATNGALLWD

Attribute	**Description**
Name	FWDDATNGALLWD
Datatype	String

Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description

Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXNOOFLNS

Attribute	Description
Name	MAXNOOFLNS
Datatype	Number

Description	Indicates Maximum Number of Loans
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates Statement Generation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DMNDBASIS

Attribute	**Description**	
Name	DMNDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,B,

TOP

AUTOACC

Attribute	**Description**	
Name	AUTOACC	
Datatype	String	
Description	Indicates Auto Account Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCCLSS

Attribute	**Description**	
Name	ACCCLSS	
Datatype	String	
Description	Indicates Account Class	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

USRDEFSCHD

Attribute	**Description**
Name	USRDEFSCHD
Datatype	String

Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number
Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN
Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String
Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number

Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Product Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

APLYTAX

Attribute	**Description**	
Name	APLYTAX	
Datatype	String	
Description	Indicates Apply Tax Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RLOVRWITHINT

Attribute	**Description**	
Name	RLOVRWITHINT	
Datatype	String	
Description	Indicates Rollover With Interest Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDCTTAXONRLOVR

Attribute	**Description**	
Name	DEDCTTAXONRLOVR	
Datatype	String	
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMANRLOVR

Attribute	**Description**
Name	AUTOMANRLOVR
Datatype	String

Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String

Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TRANSACTIONCD

Attribute	Description	
Name	TRANSACTIONCD	
Datatype	String	
Description	Indicates Transaction code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STATUSSEQ

Attribute	Description	
Name	STATUSSEQ	
Datatype	Number	
Description	Indicates status Sequence	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STPACCRUALS

Attribute	Description	
Name	STPACCRUALS	
Datatype	String	
Description	Indicates Stop Accruals Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC

Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCROL

Attribute	**Description**	
Name	ACCROL	
Datatype	String	
Description	Indicates Account Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	**Description**	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCHD

Attribute	**Description**	
Name	ACCHD	
Datatype	String	
Description	Indicates Account Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	**Description**	
Name	GLDESC	
Datatype	String	
Description	Indicates GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String

Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Ccy-Tax-Details

Attribute	**Description**	
Name	Ccy-Tax-Details	
Datatype		
Description	Includes Currency Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MAXTAXINTPERD

Attribute	**Description**	
Name	MAXTAXINTPERD	
Datatype	Number	
Description	Indicates Maximum Interest Period for Tax	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PERDUNIT

Attribute	**Description**	
Name	PERDUNIT	
Datatype	String	
Description	Indicates Period Unit Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String

Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String

Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description

Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String

Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description

Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number

Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQPRNCHNG

Attribute	Description
Name	LIQPRNCHNG
Datatype	String
Description	Indicates Increase In Principal Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BASISAMT

Attribute	**Description**	
Name	BASISAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,E

TOP

ENDDTINP

Attribute	**Description**
Name	ENDDTINP
Datatype	String

Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges

Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

NTCNSINDI

Attribute	**Description**	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	**Description**	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	**Description**	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	**Description**
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	**Description**	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	**Description**	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSOC

Attribute	**Description**	
Name	AMNDAFTRASSOC	
Datatype	String	
Description	Indicates Amend After Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWAMTAMND

Attribute	**Description**
Name	ALWAMTAMND
Datatype	String

Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description

Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description

Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String

Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description

Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String

Description	Indicates the message type.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGREQD

Attribute	**Description**	
Name	CHGREQD	
Datatype	String	
Description	Indicates charges required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Role-To-Head-Mapping

Attribute	**Description**	
Name	Role-To-Head-Mapping	
Datatype		
Description	Includes Role To Head Mapping details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates Role Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String

Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes Product Customer Restriction details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description

Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields

Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description

Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRFREQ

Attribute	**Description**	
Name	ACCRFREQ	
Datatype	String	
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	**Description**	
Name	PREPAYTBDTREAT	
Datatype	String	
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,R,

TOP

ACQTYP

Attribute	**Description**	
Name	ACQTYP	
Datatype	String	
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description

Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.ReopenLDBrnPrm

Reopen Branch Parameter for LD / MM

2.4.1.LD-ReopenLDBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.4.2.LD-ReopenLDBrnPrm-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Ld-Branch-Params-IO
BRNCD
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.4.3.LD-ReopenLDBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.4.LD-ReopenLDBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.AuthFeeAccrualLDContract

Authorization of FeeAccrual Loans and Deposit Contract

2.5.1.LD-AuthoriseFeeAccrual-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*

COMP
FEEAMT
REFAMT
VALDT
ACCBRN
ACC
BASAMT
CALCSTDT
CALCENDDT
FEETYP
CONSDISCNT
ACCREQD
FEECCY
REFCCY
COMPCCY
COMPESN
AMT
AMTCCY
FEEAUDIT
ESN
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT
REVR_MAKERID
REVR_MAKERSTAMP
REVR_CHECKERID
REVR_CHECKERSTAMP
STLDETAILS_IS_MAIN
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4

BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP

PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Advices

MSGTYPE
PARTYID
MEDIUM
SUPPRESS

PRIORITY

CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Fee Accrual has been successfully Authorised

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Authorization details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MATDATE

Attribute	**Description**	
Name	MATDATE	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	**Description**	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREF

Attribute	**Description**	
Name	USRREF	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREF

Attribute	**Description**	
Name	CUSTREF	
Datatype	String	
Description	Indicates Custom Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	Description	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	Description	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	Description

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

2.5.2.LD-AuthoriseFeeAccrual-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*
      - *COMP*
      - *FEEAMT*
      - *REFAMT*

- *VALDT*
- *ACCBRN*
- *ACC*
- *BASAMT*
- *CALCSTDT*
- *CALCENDDT*
- *FEETYP*
- *CONSDISCNT*
- *ACCREQD*
- *FEECCY*
- *REFCCY*
- *COMPCCY*
- *COMPESN*
- *AMT*
- *AMTCCY*

FEEAUDIT

- *ESN*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *CONTSTAT*
- *AUTHSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*

STLDETAILS_IS_MAIN

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*

BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2

PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the Fee Accrual that has been successfully Authorised

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Authorization details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MATDATE

Attribute	Description
Name	MATDATE
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREF

Attribute	Description
Name	CUSTREF
Datatype	String
Description	Indicates Custom Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.6.AuthorizeBrnPrm

Authorization of Loans and Deposit Branch Parameters

2.6.1.LD-AuthorizeBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	Include Loans and Deposits Branch Params Full type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Inidctae branch name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BTN_UDF

Attribute	**Description**	
Name	BTN_UDF	
Datatype	String	
Description	Indicates Button For UDF Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicate the maker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the maker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the checker stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates transaction status Open : O Closed :C
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.6.2.LD-AuthorizeBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-IO*
    - *BRNCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	This Indicates LD Branch Parameters Input Only Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

2.6.3.LD-AuthorizeBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	This Includes Authorize LD Branch Parameters Full Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates Button For UDF Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicate the maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the maker stamp
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the checker

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the checker stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates transaction status Open : O Closed :C	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.4.LD-AuthorizeBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	This Includes Authorize LDBranch Parameters Primary Key details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	This Includes Authorize LDBranch Parameters Input Only details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.7.AuthorizeLDBrnPrm

Authorize Branch Parameter for LD / MM

2.7.1.LD-AuthorizeLDBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.7.2.LD-AuthorizeLDBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-IO*
    - *BRNCD*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.7.3.LD-AuthorizeLDBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Maker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Ld-Branch-Params-PK*
    - *BRNCD*
  - *Ld-Branch-Params-IO*
    - *BRNCD*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.AuthorizeProduct

Authorisation of Loans and Deposit Product

2.8.1.LD-AuthorizeProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*

ACCRSTRTMNTH
ACCRSTRTDT
COLCTDRNGAMNDT
MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ

TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*

- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*
- *MORATRMPERD*

Liquidation-Order

- *CMPNT*
- *LIQORDR*

Grace-Levels

- *LVLNO*
- *NOOFUNITS*
- *UNIT*

Ccy-Days-Details

- *CCY*
- *EXCRATFXNGDAYS*
- *INTRATFXNGDAYS*

Trs-Components-Details

- *COMPNT*

Status-Master-Details

- *STATUS*
- *TRANSACTIONCD*
- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *COMPLETEACCRUALS*
- *TRNSFRCAPITLIZDINCM*
- *AUTOFRWD*
- *AUTOREVERSE*
- *DERVTNRUL*
- *RBKPROVSN*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*
  - *GLDESC*
  - *TRNSFERGL*
  - *DWNWRDTRANSFERFRMGL*
  - *DWNWRDTRANSFERTOGL*
- *Acc-Status-Gl-Details*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Tax-Scheme

- SCHME
- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
  - Ccy-Tax-Details
    - CCY
    - MAXTAXINTPERD
    - PERDUNIT
    - MININTTAXAMT
- Product-Interest
  - Interest-Components
    - BASISAMNTTYP
    - BASISAMNTCATG
    - RATCDUSGE
    - RATTYP
    - RATCD
    - SETTLMNTCCY
    - STPAPPLICTION
    - RESETTENOR
    - BRWLENDIND
    - LVLNO
    - PREPMTMETD
    - PROPREQD
    - MARGNBASIS
    - MARGNAPPLN
    - RATECALCTYP
    - ACQREQD
    - CHNGDRGAMNDMNT
    - SHWNINCNTRTMAINSCR
    - BLKAMTFLG
    - DEPORATECD
    - DISCACCRAPP
    - UNIT
    - NOUNIT
    - EVNT
    - COMPNENT
    - COMPNENTDESC
    - RUL
    - COLTYP
    - EVNTDESC

- RULEDESC
- Interest-Ccy-Preferences
  - CCY
  - DEFRAT
  - MINRATE
  - MAXRAT
  - DFLTSPRD
  - MINSPRD
  - MAXSPRD
  - INTBASIS
  - DENOMBASIS
  - BAS366
  - NOOFINTPRD
  - PRPMTRT
- Product-Accrual-Fee
  - Accrual-Fee-Details
    - LIQINT
    - LIQPRNCHNG
    - DISCACCRAPP
    - ACCRREQD
    - BASISAMT
    - ENDDTINP
    - RULFEE
    - FEETYP
    - ACCRFREQ
    - FREQVAL
    - COMP
    - STPASSN
    - COMPNENTDESC
- Product-Charges
  - Charge-Details
    - CHGTYP
    - THRDPTYTY
    - DRCRTYPE
    - NTCNSINDI
    - NETCONSPLSMINS
    - SWIFTQLF
    - SETTCCY
    - DFTWAIV
    - ALWRULAMND
    - AMNDAFTRASSOC
    - ALWAMTAMND
    - AMNDAFTRAPPL
    - STPASOCIATN

- ADVCHG
- CAPTLIZE
- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences

CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Authorization details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description	
Name	PROD_TYPE_DESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	Attribute: minOccurs Description: 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	Attribute: minOccurs Description: 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 255

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: enumeration Description: B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String

Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String
Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description

Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String
Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXNOOFLNS

Attribute	Description
Name	MAXNOOFLNS
Datatype	Number
Description	Indicates Maximum Number of Loans
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates Statement Generation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DMNDBASIS

Attribute	Description
Name	DMNDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B,

TOP

AUTOACC

Attribute	Description
Name	AUTOACC
Datatype	String
Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number

Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String

Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String

Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN
Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String

Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Product Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEDCTTAXONRLOVR

Attribute	Description
Name	DEDCTTAXONRLOVR
Datatype	String
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMANRLOVR

Attribute	Description
Name	AUTOMANRLOVR
Datatype	String
Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STRTDAY

Attribute	**Description**
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	**Description**
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	**Description**
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	**Description**
Name	MORATRMPERDUNIT
Datatype	String

Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	

Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Status-Advices-Details

Attribute	**Description**	
Name	Status-Advices-Details	
Datatype		
Description	Includes Status Advices detail	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MESSAGECD

Attribute	**Description**	
Name	MESSAGECD	
Datatype	String	
Description	Indicates Message of Status Advices	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Product-Status-Gl-Details

Attribute	**Description**	
Name	Product-Status-Gl-Details	
Datatype		
Description	Includes Product Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCNTROLE

Attribute	**Description**	
Name	ACCNTROLE	
Datatype	String	
Description	Indicates Accounting Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String

Description	Indicates Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description

Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PERDUNIT

Attribute	**Description**	
Name	PERDUNIT	
Datatype	String	
Description	Indicates Period Unit Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

MININTTAXAMT

Attribute	**Description**	
Name	MININTTAXAMT	
Datatype	Number	
Description	Indicates Minimum Interest Amount for Tax	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Product-Interest

Attribute	**Description**	
Name	Product-Interest	
Datatype		
Description	Includes Product Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Interest-Components

Attribute	**Description**	
Name	Interest-Components	
Datatype		
Description	Includes Interest Components details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description

Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description

Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

EVNTDESC

Attribute	**Description**	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Interest-Ccy-Preferences

Attribute	**Description**	
Name	Interest-Ccy-Preferences	
Datatype		
Description	Includes Interest Currency preferences details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQPRNCHNG

Attribute	**Description**	
Name	LIQPRNCHNG	
Datatype	String	
Description	Indicates Increase In Principal Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BASISAMT

Attribute	**Description**
Name	BASISAMT
Datatype	String

Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description

Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description

Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRCRTYPE

Attribute	**Description**	
Name	DRCRTYPE	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

NTCNSINDI

Attribute	**Description**	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	**Description**	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	**Description**
Name	SWIFTQLF

Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRLIQ

Attribute	Description	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD

Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description

Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes Product Customer Restriction details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details

Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET

Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	**Description**	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.8.2.LD-AuthorizeProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Authorization-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.8.3.LD-AuthorizeProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*
    - *ACCRSTRTMNTH*
    - *ACCRSTRTDT*
    - *COLCTDRNGAMNDT*

MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO

TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*
- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*

- *MORATRMPERD*
- *Liquidation-Order*
  - *CMPNT*
  - *LIQORDR*
- *Grace-Levels*
  - *LVLNO*
  - *NOOFUNITS*
  - *UNIT*
- *Ccy-Days-Details*
  - *CCY*
  - *EXCRATFXNGDAYS*
  - *INTRATFXNGDAYS*
- *Trs-Components-Details*
  - *COMPNT*
- *Status-Master-Details*
  - *STATUS*
  - *TRANSACTIONCD*
  - *STATUSSEQ*
  - *STPACCRUALS*
  - *REVERSEACCRUALS*
  - *COMPLETEACCRUALS*
  - *TRNSFRCAPITLIZDINCM*
  - *AUTOFRWD*
  - *AUTOREVERSE*
  - *DERVTNRUL*
  - *RBKPROVSN*
  - *Status-Advices-Details*
    - *MESSAGECD*
  - *Product-Status-Gl-Details*
    - *ACCNTROLE*
    - *UPWARDTRANFERFRMGL*
    - *GLDESC*
    - *TRNSFERGL*
    - *DWNWRDTRANSFERFRMGL*
    - *DWNWRDTRANSFERTOGL*
  - *Acc-Status-Gl-Details*
    - *ACCROL*
    - *ROLDESC*
    - *ACCHD*
    - *GLDESC*
- *Tax-Scheme*
  - *SCHME*
  - *SCHEMEDESC*
  - *Tax-Details*

RUL
AMNTTAG
BASISAMNTTAG
COMPTATIONEVNT
TYP
Ccy-Tax-Details
CCY
MAXTAXINTPERD
PERDUNIT
MININTTAXAMT
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY

DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
Product-Accrual-Fee
Accrual-Fee-Details
LIQINT
LIQPRNCHNG
DISCACCRAPP
ACCRREQD
BASISAMT
ENDDTINP
RULFEE
FEETYP
ACCRFREQ
FREQVAL
COMP
STPASSN
COMPNENTDESC
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY
DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB

PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD
EVENTDESC
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
DESC
GENTIME
SUPRS
PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD

- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
    - DESCRIPTION
  - Customers
    - CSTID
    - CUSTNAME
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - CLASDESC
  - Branch-List
    - BRNDISALOW
    - BRNNAME
  - Ccy-List
    - BGTDLCCY
    - CCYNAME
- Product-Fields
  - Field-Details
    - FLDNUM
    - FLDNAME
- Product-Discount-Accrual
  - CLASCD
  - CLASDESC
  - CLSDFLT
  - Disc-Accr-Details
    - DISCACCRREQD
    - ACCRFREQ
    - PREPAYTBDTREAT
    - ACQTYP
  - Ccy-Preferences
    - CCYCODE
    - CCYNAME
    - DENOMDCNTMET

DENOMMETHOD

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISCLS

MISCD

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Authorization-Full details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP

Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description
Name	PROD_TYPE_DESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String

Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String

Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description

Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number

Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String

Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description

Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String

Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXNOOFLNS

Attribute	Description
Name	MAXNOOFLNS
Datatype	Number
Description	Indicates Maximum Number of Loans
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	**Description**	
Name	SGENREQD	
Datatype	String	
Description	Indicates Statement Generation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTCREQD

Attribute	**Description**	
Name	NOTCREQD	
Datatype	String	
Description	Indicates Whether Notice is Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DMNDBASIS

Attribute	**Description**	
Name	DMNDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,B,

TOP

AUTOACC

Attribute	**Description**
Name	AUTOACC
Datatype	String

Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number
Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN

Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String
Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTNRATTYP

Attribute	**Description**	
Name	REVALTNRATTYP	
Datatype	String	
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates Checker ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Product Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Auth Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDCTTAXONRLOVR

Attribute	Description	
Name	DEDCTTAXONRLOVR	
Datatype	String	
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMANRLOVR

Attribute	Description	
Name	AUTOMANRLOVR	
Datatype	String	
Description	Indicates Rollover Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

RLOVRMECHNSM

Attribute	Description	
Name	RLOVRMECHNSM	
Datatype	String	
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description

Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number

Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUSSEQ

Attribute	Description

Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String

Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN

Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	Description

Name	ACCHD
Datatype	String
Description	Indicates Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,M,Y,</td></tr></table>

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,D,N,O</td></tr></table>

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,P</td></tr></table>

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String

Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR

Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**	
Name	MARGNAPPLN	
Datatype	String	
Description	Indicates Margin Application Periodic : P Automatic : A None : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,A,N

TOP

RATECALCTYP

Attribute	**Description**	
Name	RATECALCTYP	
Datatype	String	
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COMPNENT

Attribute	Description	
Name	COMPNENT	
Datatype	String	
Description	Indicates Component	
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RUL

Attribute	Description	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description

Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description

Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String

Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQPRNCHNG

Attribute	Description
Name	LIQPRNCHNG
Datatype	String
Description	Indicates Increase In Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTAPPLIDESC

Attribute	**Description**	
Name	EVNTAPPLIDESC	
Datatype	String	
Description	Indicates Event Application Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULDESC

Attribute	Description	
Name	RULDESC	
Datatype	String	
Description	Indicates rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Includes Product Events details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes Product Customer Restriction details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CLSDFLT

Attribute	**Description**	
Name	CLSDFLT	
Datatype	String	
Description	Indicates Class Default	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description

Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.4.LD-AuthorizeProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Indicates Loans and Deposit Product Authorization-PK details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Authorization-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.9.CloseLDBrnPrm

Close Branch Parameter for LD / MM

2.9.1.LD-CloseLDBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,L

TOP

SGENMANLIQ

Attribute	Description	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	Description	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	Description	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.9.2.LD-CloseLDBrnPrm-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Ld-Branch-Params-IO*
  - *BRNCD*
  - *MAKER*
  - *MAKERSTAMP*
  - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.9.3.LD-CloseLDBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Maker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.4.LD-CloseLDBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.CreateBrnPrm

Creation of Loans and Deposit Branch Parameters

2.10.1.LD-CreateBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	This Includes LD Branch Paramters Full Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS

Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF

Datatype	String
Description	Indicates Button For UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicate the maker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the maker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String

Description	Indicates the checker stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates transaction status Open : O Closed :C
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.10.2.LD-CreateBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-IO*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	This Includes Create LD Branch Parameters Input Only Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCTILL

Attribute	Description	
Name	PROCTILL	
Datatype	String	
Description	Indicate Process Till S System Date N Next Working Day -1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,N

TOP

ACCRLVL

Attribute	Description	
Name	ACCRLVL	
Datatype	String	
Description	Indicate Accrual Level P Product C Contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

TAXCOMPBASIS

Attribute	Description	
Name	TAXCOMPBASIS	
Datatype	String	
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ

Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates UDF
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes UDF details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.10.3.LD-CreateBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	This Includes Create LDBranch Parameters Full Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BTN_UDF

Attribute	**Description**	
Name	BTN_UDF	
Datatype	String	
Description	Indicates Button For UDF Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description	Indicate Use User Reference No in Messages Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Indicate the maker	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the maker stamp	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates the checker

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the checker stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates transaction status Open : O Closed :C	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.4.LD-CreateBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
      - *PROCTILL*
      - *ACCRLVL*
      - *TAXCOMPBASIS*
      - *SGENMANLIQ*
      - *APYCALC*
      - *BTN_UDF*
      - *USRREFINMSGS*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	This Includes LDCreate Branch Parameters Primary Key Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	This Includes LDCreate Branch Parameters Input Only details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,N

TOP

ACCRLVL

Attribute	**Description**	
Name	ACCRLVL	
Datatype	String	
Description	Indicate Accrual Level P Product C Contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

TAXCOMPBASIS

Attribute	**Description**	
Name	TAXCOMPBASIS	
Datatype	String	
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**
Name	APYCALC

Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates UDF
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes UDF details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.CreateFeeAccrualLDContract

Creation of FeeAccrual Loans and Deposit Contract

2.11.1.LD-CreateFeeAccrual-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*

COMP
FEEAMT
REFAMT
VALDT
ACCBRN
ACC
BASAMT
CALCSTDT
CALCENDDT
FEETYP
CONSDISCNT
ACCREQD
FEECCY
REFCCY
COMPCCY
COMPESN
AMT
AMTCCY
FEEAUDIT
ESN
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT
REVR_MAKERID
REVR_MAKERSTAMP
REVR_CHECKERID
REVR_CHECKERSTAMP
STLDETAILS_IS_MAIN
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4

BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP

PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Advices

MSGTYPE
PARTYID
MEDIUM
SUPPRESS

PRIORITY

CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Fee Accrual that has been successfully Created

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Creation details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MATDATE

Attribute	Description	
Name	MATDATE	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREF

Attribute	Description	
Name	USRREF	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREF

Attribute	Description	
Name	CUSTREF	
Datatype	String	
Description	Indicates Custom Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	**Description**
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

2.11.2.LD-CreateFeeAccrual-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *XREF*
    - *Contract-Accr-Fee*
      - *FCCREF*
      - *COMPCCY*
      - *FEEAMT*
      - *REFAMT*
      - *VALDT*
      - *CALCSTDT*
      - *CALCENDDT*
      - *FEETYP*
      - *ACCREQD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual that has been successfully Created

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Creation-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	Description	
Name	Contract-Accr-Fee	
Datatype		
Description	Include Loans and Deposits Contract fee type details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	Description	
Name	COMPCCY	
Datatype	String	
Description	Indicate Component Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number
Description	Indicate Fee Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicate Refund Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.11.3.LD-CreateFeeAccrual-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*
      - *COMP*
      - *FEEAMT*
      - *REFAMT*

- *VALDT*
- *ACCBRN*
- *ACC*
- *BASAMT*
- *CALCSTDT*
- *CALCENDDT*
- *FEETYP*
- *CONSDISCNT*
- *ACCREQD*
- *FEECCY*
- *REFCCY*
- *COMPCCY*
- *COMPESN*
- *AMT*
- *AMTCCY*

FEEAUDIT

- *ESN*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *CONTSTAT*
- *AUTHSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*

STLDETAILS_IS_MAIN

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*

BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2

PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the Fee Accrual that has been successfully Created

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Creation details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MATDATE

Attribute	Description
Name	MATDATE
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREF

Attribute	Description
Name	CUSTREF
Datatype	String
Description	Indicates Custom Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	Description	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST4

Attribute	Description	
Name	INT_REIM_INST4	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST5

Attribute	Description	
Name	INT_REIM_INST5	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST6

Attribute	Description	
Name	INT_REIM_INST6	
Datatype	String	
Description	Country to which the Intermediary remitter institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.11.4.LD-CreateFeeAccrual-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-PK*
      - *FCCREF*
      - *USRREF*
    - *Contract-IO*
      - *FCCREF*
      - *XREF*
      - *Contract-Accr-Fee*
        - *FCCREF*
        - *COMPCCY*
        - *FEEAMT*
        - *REFAMT*
        - *VALDT*
        - *CALCSTDT*
        - *CALCENDDT*
        - *FEETYP*
        - *ACCREQD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual that has been successfully Created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-PK

Attribute	Description
Name	Contract-PK
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Creation-Primary key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicate User Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Contract-IO

Attribute	Description
Name	Contract-IO
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Creation-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	Description
Name	Contract-Accr-Fee
Datatype	
Description	Include Loans and Deposits Contract fee type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicate Component Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number
Description	Indicate Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicate Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.CreateLDBrnPrm

Create Branch Parameter for LD / MM

2.12.1.LD-CreateLDBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.12.2.LD-CreateLDBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-IO*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *USRREFINMSGS*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCTILL

Attribute	**Description**	
Name	PROCTILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,N

TOP

ACCRLVL

Attribute	**Description**	
Name	ACCRLVL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

TAXCOMPBASIS

Attribute	**Description**	
Name	TAXCOMPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.12.3.LD-CreateLDBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Maker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.4.LD-CreateLDBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
      - *PROCTILL*
      - *ACCRLVL*
      - *TAXCOMPBASIS*
      - *SGENMANLIQ*
      - *APYCALC*
      - *USRREFINMSGS*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.CreateLDPaymentSim

Input of deposit payment simulation

2.13.1.LD-CreateLDPaymentSim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *XREF*
    - *FCCREF*
    - *CPTY*
    - *STATUS*
    - *OSBAL*
    - *CCY*
    - *OLDMATDT*
    - *NEWMATDT*
    - *EFFFROM*
    - *PREPMTBASIS*
    - *PREPMTEFFFROM*
    - *VALDT*
    - *TOTPAID*
    - *LIMITDT*
    - *DISCRATE*

TOTPREPAID
LIMITAMT
LIQDFACEVAL
PREPMTPENRATE
PREPMTPENAMT
PREPMTADJAMT1
PREPMTADJAMT2
PAYMNTREM
LCYEQVTTOTPAID
LCYEQVTTOTPREPAID
LCYEQVTLIMITAMT
LCYEQVTLIQDFACEVALUE
OSBALREP
SYNDNO
SUBSYSTEMSTAT
CURRPMNT
TOTPAMNT
Payment-Breakup
  FCCREF
  COMP
  AMTDUE
  AMTPAID
Schedule-Details
  FCCREF
  SCOMP
  DUEDT
  AMTDUE
  AMTSETTL
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  REVR_MAKERID
  REVR_CHECKERID
  REVR_MAKERSTAMP
  REVR_CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
  REVR_AUTHSTAT
  REVR_CONTSTAT
Settlement-Addl-Details
  ACCBRN
  ACC_CCY

ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT

INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3

TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend

CONTREF
RTYPE
RCODE
SPD

Refinance-Rate

UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR

- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*
    - *TAXCCY*
    - *VALDT*
    - *COMPDT*
- *Contract_Schedules*

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

MSGTYPE

PARTYID

MEDIUM

SUPPRESS

PRIORITY

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

OSBAL

Attribute	Description
Name	OSBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OLDMATDT

Attribute	Description
Name	OLDMATDT
Datatype	Date
Description	Indicates Old Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWMATDT

Attribute	Description

Name	NEWMATDT
Datatype	Date
Description	Indicates New Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFFROM

Attribute	Description
Name	EFFFROM
Datatype	String
Description	Indicates Effective From
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

PREPMTBASIS

Attribute	Description
Name	PREPMTBASIS
Datatype	String
Description	Indicates Recomputation Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PREPMTEFFFROM

Attribute	Description
Name	PREPMTEFFFROM
Datatype	String
Description	Indicates Prepayment Effective From
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCRATE

Attribute	Description
Name	DISCRATE
Datatype	Number
Description	Indicates Disc. Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

TOTPREPAID

Attribute	Description
Name	TOTPREPAID
Datatype	Number
Description	Indicates Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDFACEVAL

Attribute	Description
Name	LIQDFACEVAL
Datatype	Number
Description	Indicates Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

PREPMTPENRATE

Attribute	Description
Name	PREPMTPENRATE
Datatype	Number
Description	Indicates Prepayment Penalty Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTPENAMT

Attribute	Description
Name	PREPMTPENAMT
Datatype	Number
Description	Indicates Penalty Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT1

Attribute	Description	
Name	PREPMTADJAMT1	
Datatype	Number	
Description	Indicates Adjust Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREPMTADJAMT2

Attribute	Description	
Name	PREPMTADJAMT2	
Datatype	Number	
Description	Indicates Addl. Adj. Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PAYMNTREM

Attribute	Description	
Name	PAYMNTREM	
Datatype	String	
Description	Indicates Payment Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYEQVTTOTPAID

Attribute	Description	
Name	LCYEQVTTOTPAID	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Total Paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LCYEQVTTOTPREPAID

Attribute	Description
Name	LCYEQVTTOTPREPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LCYEQVTLIMITAMT

Attribute	Description
Name	LCYEQVTLIMITAMT
Datatype	Number
Description	Indicates Local Currency Equivalent of Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

LCYEQVTLIQDFACEVALUE

Attribute	Description
Name	LCYEQVTLIQDFACEVALUE
Datatype	Number
Description	Indicates Local Currency Equivalent of Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

OSBALREP

Attribute	Description
Name	OSBALREP
Datatype	Number
Description	Indicates O/S Bal- Rep
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SYNDNO

Attribute	Description
Name	SYNDNO
Datatype	Number
Description	Indicates Syndication Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates SubSystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CURRPMNT

Attribute	Description
Name	CURRPMNT
Datatype	Number
Description	Indicates Current Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TOTPAMNT

Attribute	Description
Name	TOTPAMNT
Datatype	Number
Description	Indicates Total Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	Includes Payment Break Up details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTPAID

Attribute	Description

Name	AMTPAID
Datatype	Number
Description	Indicates Amount Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedules details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_MAKERID

Attribute	Description	
Name	REVR_MAKERID	
Datatype	String	
Description	Indicates the Maker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERID

Attribute	Description	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Payment Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REVR_CONTSTAT

Attribute	**Description**	
Name	REVR_CONTSTAT	
Datatype	String	
Description	Indicates the Contract status of reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**
Name	TAG_CCY
Datatype	String
Description	Indicates Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	**Description**	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	**Description**
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM4

Attribute	Description	
Name	RCVR_CUSNM4	
Datatype	String	
Description	Indicates the Receiver Name 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description	
Name	SNDR_ACC	
Datatype	String	
Description	Indicates the Sender Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

RCVR_ACC

Attribute	Description	
Name	RCVR_ACC	
Datatype	String	
Description	Indicates the Receiver Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance Rate details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date

Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Field details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

RETENOR

Attribute	**Description**	
Name	RETENOR	
Datatype	Number	
Description	Indicates the Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	5

TOP

BORLENIND

Attribute	**Description**	
Name	BORLENIND	
Datatype	String	
Description	Indicates the Borrow \ Lend Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M

TOP

RTCALCTYP

Attribute	**Description**	
Name	RTCALCTYP	
Datatype	String	
Description	Indicates the Interest Rate Calculation type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	**Description**	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

DENOBASIS

Attribute	Description	
Name	DENOBASIS	
Datatype	String	
Description	Indicates the Denominator basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description	Indicates the BASIS_366	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOINTPRD

Attribute	Description	
Name	NOINTPRD	
Datatype	Number	
Description	Indicates the No of Interest Period.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	Description	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax Main details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Inlcudes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	Description	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

STDT

Attribute	Description	
Name	STDT	
Datatype	Date	
Description	Indicates the Start Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Inlcudes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Inlcudes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

2.13.2.LD-CreateLDPaymentSim-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Summary-PK*
      - *XREF*
      - *FCCREF*
    - *Payment-Summary-IO*
      - *FCCREF*
      - *XREF*
      - *TOTPAID*
      - *VALDT*
      - *LIMITDT*
      - *Payment-Breakup*
        - *COMP*
        - *AMTDUE*
        - *OVERDUE*
        - *AMTPAID*
        - *INTPREPAY*
        - *TAXPAID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Summary-PK

Attribute	Description
Name	Payment-Summary-PK
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Payment-Summary-IO

Attribute	Description
Name	Payment-Summary-IO
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid.
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	

Description	Includes Payment Break up Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

OVERDUE

Attribute	Description
Name	OVERDUE
Datatype	Number
Description	Indicates Over Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

INTPREPAY

Attribute	Description
Name	INTPREPAY
Datatype	Number
Description	Indicates the Interest Prepaid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.3.LD-CreateLDPaymentSimReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary-IO*
    - *FCCREF*
    - *XREF*
    - *TOTPAID*
    - *VALDT*
    - *LIMITDT*
    - *Payment-Breakup*
      - *COMP*
      - *AMTDUE*
      - *OVERDUE*
      - *AMTPAID*
      - *INTPREPAY*
      - *TAXPAID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary-IO

Attribute	Description
Name	Payment-Summary-IO
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Includes Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Includes External Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TOTPAID

Attribute	Description	
Name	TOTPAID	
Datatype	Number	
Description	Indicates Total Paid.	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIMITDT

Attribute	Description	
Name	LIMITDT	
Datatype	Date	
Description	Indicates Limit Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	

Description	Includes Payment Break up Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

OVERDUE

Attribute	Description
Name	OVERDUE
Datatype	Number
Description	Indicates Over Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

INTPREPAY

Attribute	Description
Name	INTPREPAY
Datatype	Number
Description	Indicates the Interest Prepaid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

2.13.4.LD-CreateLDPaymentSimRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *XREF*
    - *FCCREF*
    - *CPTY*
    - *STATUS*
    - *OSBAL*
    - *CCY*
    - *OLDMATDT*
    - *NEWMATDT*
    - *EFFFROM*
    - *PREPMTBASIS*
    - *PREPMTEFFFROM*
    - *VALDT*
    - *TOTPAID*
    - *LIMITDT*
    - *DISCRATE*
    - *TOTPREPAID*
    - *LIMITAMT*
    - *LIQDFACEVAL*

PREPMTPENRATE
PREPMTPENAMT
PREPMTADJAMT1
PREPMTADJAMT2
PAYMNTREM
LCYEQVTTOTPAID
LCYEQVTTOTPREPAID
LCYEQVTLIMITAMT
LCYEQVTLIQDFACEVALUE
OSBALREP
SYNDNO
SUBSYSTEMSTAT
CURRPMNT
TOTPAMNT
Payment-Breakup
  FCCREF
  COMP
  AMTDUE
  AMTPAID
Schedule-Details
  FCCREF
  SCOMP
  DUEDT
  AMTDUE
  AMTSETTL
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  REVR_MAKERID
  REVR_CHECKERID
  REVR_MAKERSTAMP
  REVR_CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
  REVR_AUTHSTAT
  REVR_CONTSTAT
Settlement-Addl-Details
  ACCBRN
  ACC_CCY
  ACC
  AMTTAG
  CUSTSPRD

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*
    - *TAXCCY*
    - *VALDT*
    - *COMPDT*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*

- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*

MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

OSBAL

Attribute	**Description**	
Name	OSBAL	
Datatype	Number	
Description	Indicates Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

OLDMATDT

Attribute	**Description**
Name	OLDMATDT
Datatype	Date
Description	Indicates Old Maturity Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEWMATDT

Attribute	**Description**	
Name	NEWMATDT	
Datatype	Date	
Description	Indicates New Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EFFFROM

Attribute	**Description**	
Name	EFFFROM	
Datatype	String	
Description	Indicates Effective From	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	2

TOP

PREPMTBASIS

Attribute	**Description**	
Name	PREPMTBASIS	
Datatype	String	
Description	Indicates Recomputation Basis	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PREPMTEFFFROM

Attribute	**Description**	
Name	PREPMTEFFFROM	
Datatype	String	
Description	Indicates Prepayment Effective From	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCRATE

Attribute	Description
Name	DISCRATE
Datatype	Number
Description	Indicates Disc. Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TOTPREPAID

Attribute	Description
Name	TOTPREPAID
Datatype	Number
Description	Indicates Amount Prepaid

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDFACEVAL

Attribute	Description
Name	LIQDFACEVAL
Datatype	Number
Description	Indicates Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

PREPMTPENRATE

Attribute	Description
Name	PREPMTPENRATE
Datatype	Number
Description	Indicates Prepayment Penalty Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTPENAMT

Attribute	Description
Name	PREPMTPENAMT
Datatype	Number
Description	Indicates Penalty Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREPMTADJAMT1

Attribute	**Description**	
Name	PREPMTADJAMT1	
Datatype	Number	
Description	Indicates Adjust Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREPMTADJAMT2

Attribute	**Description**	
Name	PREPMTADJAMT2	
Datatype	Number	
Description	Indicates Addl. Adj. Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PAYMNTREM

Attribute	**Description**	
Name	PAYMNTREM	
Datatype	String	
Description	Indicates Payment Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYEQVTTOTPAID

Attribute	**Description**
Name	LCYEQVTTOTPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Total Paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LCYEQVTTOTPREPAID

Attribute	**Description**	
Name	LCYEQVTTOTPREPAID	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Amount Prepaid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LCYEQVTLIMITAMT

Attribute	**Description**	
Name	LCYEQVTLIMITAMT	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Limit Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

LCYEQVTLIQDFACEVALUE

Attribute	**Description**	
Name	LCYEQVTLIQDFACEVALUE	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Liquidated Nominal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

OSBALREP

Attribute	**Description**
Name	OSBALREP
Datatype	Number
Description	Indicates O/S Bal- Rep

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SYNDNO

Attribute	Description
Name	SYNDNO
Datatype	Number
Description	Indicates Syndication Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates SubSystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CURRPMNT

Attribute	Description
Name	CURRPMNT
Datatype	Number
Description	Indicates Current Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TOTPAMNT

Attribute	Description
Name	TOTPAMNT
Datatype	Number
Description	Indicates Total Payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	Includes Payment Break Up details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates Amount Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedules details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DUEDT

Attribute	Description
Name	DUEDT

Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Payment Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM4

Attribute	Description	
Name	RCVR_CUSNM4	
Datatype	String	
Description	Indicates the Receiver Name 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description	
Name	SNDR_ACC	
Datatype	String	
Description	Indicates the Sender Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

RCVR_ACC

Attribute	Description	
Name	RCVR_ACC	
Datatype	String	
Description	Indicates the Receiver Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RCODE

Attribute	Description	
Name	RCODE	
Datatype	String	
Description	Indicates Rate Code	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPD

Attribute	Description	
Name	SPD	
Datatype	Number	
Description	Indicates Spread	
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Refinance-Rate

Attribute	Description	
Name	Refinance-Rate	
Datatype		
Description	Includes Refinance Rate details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	Description	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date

Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Field details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

RETENOR

Attribute	**Description**	
Name	RETENOR	
Datatype	Number	
Description	Indicates the Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	5

TOP

BORLENIND

Attribute	**Description**	
Name	BORLENIND	
Datatype	String	
Description	Indicates the Borrow \ Lend Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M

TOP

RTCALCTYP

Attribute	**Description**	
Name	RTCALCTYP	
Datatype	String	
Description	Indicates the Interest Rate Calculation type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	**Description**	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

DENOBASIS

Attribute	Description	
Name	DENOBASIS	
Datatype	String	
Description	Indicates the Denominator basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description	Indicates the BASIS_366	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOINTPRD

Attribute	Description	
Name	NOINTPRD	
Datatype	Number	
Description	Indicates the No of Interest Period.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	Description	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax Main details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Inlcudes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Inlcudes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Inlcudes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.CreateProduct

Input of Loans and Deposit Product

2.14.1.LD-CreateProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*

ACCRSTRTMNTH
ACCRSTRTDT
COLCTDRNGAMNDT
MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ

TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*

- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*
- *MORATRMPERD*

Liquidation-Order

- *CMPNT*
- *LIQORDR*

Grace-Levels

- *LVLNO*
- *NOOFUNITS*
- *UNIT*

Ccy-Days-Details

- *CCY*
- *EXCRATFXNGDAYS*
- *INTRATFXNGDAYS*

Trs-Components-Details

- *COMPNT*

Status-Master-Details

- *STATUS*
- *TRANSACTIONCD*
- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *COMPLETEACCRUALS*
- *TRNSFRCAPITLIZDINCM*
- *AUTOFRWD*
- *AUTOREVERSE*
- *DERVTNRUL*
- *RBKPROVSN*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*
  - *GLDESC*
  - *TRNSFERGL*
  - *DWNWRDTRANSFERFRMGL*
  - *DWNWRDTRANSFERTOGL*
- *Acc-Status-Gl-Details*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Tax-Scheme

- SCHME
- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
  - Ccy-Tax-Details
    - CCY
    - MAXTAXINTPERD
    - PERDUNIT
    - MININTTAXAMT
- Product-Interest
  - Interest-Components
    - BASISAMNTTYP
    - BASISAMNTCATG
    - RATCDUSGE
    - RATTYP
    - RATCD
    - SETTLMNTCCY
    - STPAPPLICTION
    - RESETTENOR
    - BRWLENDIND
    - LVLNO
    - PREPMTMETD
    - PROPREQD
    - MARGNBASIS
    - MARGNAPPLN
    - RATECALCTYP
    - ACQREQD
    - CHNGDRGAMNDMNT
    - SHWNINCNTRTMAINSCR
    - BLKAMTFLG
    - DEPORATECD
    - DISCACCRAPP
    - UNIT
    - NOUNIT
    - EVNT
    - COMPNENT
    - COMPNENTDESC
    - RUL
    - COLTYP
    - EVNTDESC

- RULEDESC
- Interest-Ccy-Preferences
  - CCY
  - DEFRAT
  - MINRATE
  - MAXRAT
  - DFLTSPRD
  - MINSPRD
  - MAXSPRD
  - INTBASIS
  - DENOMBASIS
  - BAS366
  - NOOFINTPRD
  - PRPMTRT
- Product-Accrual-Fee
  - Accrual-Fee-Details
    - LIQINT
    - LIQPRNCHNG
    - DISCACCRAPP
    - ACCRREQD
    - BASISAMT
    - ENDDTINP
    - RULFEE
    - FEETYP
    - ACCRFREQ
    - FREQVAL
    - COMP
    - STPASSN
    - COMPNENTDESC
- Product-Charges
  - Charge-Details
    - CHGTYP
    - THRDPTYTY
    - DRCRTYPE
    - NTCNSINDI
    - NETCONSPLSMINS
    - SWIFTQLF
    - SETTCCY
    - DFTWAIV
    - ALWRULAMND
    - AMNDAFTRASSOC
    - ALWAMTAMND
    - AMNDAFTRAPPL
    - STPASOCIATN

- *ADVCHG*
- *CAPTLIZE*
- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences

CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Creation-Full details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description	
Name	PROD_TYPE_DESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String

Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String
Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description

Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String
Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFY_DRWDNAMT

Attribute	**Description**	
Name	VRFY_DRWDNAMT	
Datatype	String	
Description	Indicates Verify Drawdown Amount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAXNOOFLNS

Attribute	**Description**	
Name	MAXNOOFLNS	
Datatype	Number	
Description	Indicates Maximum Number of Loans	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNPRD

Attribute	**Description**	
Name	LNPRD	
Datatype	String	
Description	Indicates Loan Product	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	**Description**	
Name	ALLWSCHEAMNDAFTRSGEN	
Datatype	String	
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates Statement Generation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DMNDBASIS

Attribute	Description
Name	DMNDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B,

TOP

AUTOACC

Attribute	Description
Name	AUTOACC
Datatype	String
Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number

Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String

Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String

Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN
Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String

Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Product Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEDCTTAXONRLOVR

Attribute	Description
Name	DEDCTTAXONRLOVR
Datatype	String
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMANRLOVR

Attribute	Description
Name	AUTOMANRLOVR
Datatype	String
Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String

Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	

Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Status-Advices-Details

Attribute	**Description**	
Name	Status-Advices-Details	
Datatype		
Description	Includes Status Advices detail	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MESSAGECD

Attribute	**Description**	
Name	MESSAGECD	
Datatype	String	
Description	Indicates Message of Status Advices	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Product-Status-Gl-Details

Attribute	**Description**	
Name	Product-Status-Gl-Details	
Datatype		
Description	Includes Product Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCNTROLE

Attribute	**Description**	
Name	ACCNTROLE	
Datatype	String	
Description	Indicates Accounting Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String

Description	Indicates Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description

Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PERDUNIT

Attribute	**Description**	
Name	PERDUNIT	
Datatype	String	
Description	Indicates Period Unit Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

MININTTAXAMT

Attribute	**Description**	
Name	MININTTAXAMT	
Datatype	Number	
Description	Indicates Minimum Interest Amount for Tax	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Product-Interest

Attribute	**Description**	
Name	Product-Interest	
Datatype		
Description	Includes Product Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Interest-Components

Attribute	**Description**	
Name	Interest-Components	
Datatype		
Description	Includes Interest Components details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

RATCD

Attribute	Description	
Name	RATCD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SETTLMNTCCY

Attribute	Description	
Name	SETTLMNTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STPAPPLICTION

Attribute	Description	
Name	STPAPPLICTION	
Datatype	String	
Description	Indicates Stop Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RESETTENOR

Attribute	Description	
Name	RESETTENOR	
Datatype	Number	
Description	Indicates Reset Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description

Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description

Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

EVNTDESC

Attribute	**Description**	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Interest-Ccy-Preferences

Attribute	**Description**	
Name	Interest-Ccy-Preferences	
Datatype		
Description	Includes Interest Currency preferences details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQPRNCHNG

Attribute	**Description**	
Name	LIQPRNCHNG	
Datatype	String	
Description	Indicates Increase In Principal Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BASISAMT

Attribute	**Description**
Name	BASISAMT
Datatype	String

Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description

Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description

Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRCRTYPE

Attribute	**Description**	
Name	DRCRTYPE	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

NTCNSINDI

Attribute	**Description**	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	**Description**	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	**Description**
Name	SWIFTQLF

Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD

Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description

Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes Product Customer Restriction details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details

Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET

Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	**Description**	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.14.2.LD-CreateProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*
    - *ACCRSTRTMNTH*
    - *ACCRSTRTDT*
    - *COLCTDRNGAMNDT*
    - *MINTNR*
    - *MAXTNR*

STDTNR
TNRUNIT
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL

IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
Rollover-Details
  RLOVRICCFFRM
  APLYTAX
  RLOVRWITHINT
  DEDCTTAXONRLOVR
  AUTOMANRLOVR
  RLOVRMECHNSM
Default-Schedules
  CMPNT
  REF
  FREQ
  FREQUNIT
  STRTDAY
  STRTMNTH
  STRTDT
  MORATRMPERDUNIT
  MORATRMPERD
Liquidation-Order
  CMPNT
  LIQORDR
Grace-Levels
  LVLNO
  NOOFUNITS
  UNIT
Ccy-Days-Details
  CCY
  EXCRATFXNGDAYS

- INTRATFXNGDAYS
- Trs-Components-Details
  - COMPNT
- Status-Master-Details
  - STATUS
  - TRANSACTIONCD
  - STPACCRUALS
  - REVERSEACCRUALS
  - COMPLETEACCRUALS
  - TRNSFRCAPITLIZDINCM
  - AUTOFRWD
  - AUTOREVERSE
  - DERVTNRUL
  - RBKPROVSN
  - Status-Advices-Details
    - MESSAGECD
  - Product-Status-Gl-Details
    - ACCNTROLE
    - UPWARDTRANFERFRMGL
    - TRNSFERGL
    - DWNWRDTRANSFERFRMGL
    - DWNWRDTRANSFERTOGL
  - Acc-Status-Gl-Details
    - ACCROL
    - ACCHD
- Tax-Scheme
  - SCHME
  - Tax-Details
    - RUL
    - BASISAMNTTAG
    - COMPTATIONEVNT
    - TYP
    - Ccy-Tax-Details
      - RULE
      - CCY
      - MAXTAXINTPERD
      - PERDUNIT
      - MININTTAXAMT
- Product-Interest
  - Interest-Components
    - BASISAMNTTYP
    - BASISAMNTCATG
    - RATCDUSGE
    - RATTYP

RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
RUL
COLTYP
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
Product-Accrual-Fee
Accrual-Fee-Details
LIQINT
LIQPRNCHNG
DISCACCRAPP
ACCRREQD
BASISAMT
ENDDTINP

- *RULFEE*
- *FEETYP*
- *ACCRFREQ*
- *FREQVAL*
- *COMP*
- *STPASSN*

Product-Charges

- *Charge-Details*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *DISCACCRAPLB*
  - *DISCNTBASIS*
  - *DFTRULE*
  - *COMPNT*

Product-Events

- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping
- *CLASCD*
- *Mapping-Details*
  - *ACCTRL*
  - *ACCTHD*
  - *STAT*

Prod-Cust-Restrictions
- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
- *Customers*
  - *CSTID*
  - *ALWD*

Branch-Ccy-Restrictions
- *CCYLST*
- *BRNLST*
- *CLASCD*
- *Branch-List*
  - *BRNDISALOW*
- *Ccy-List*
  - *BGTDLCCY*
  - *SOLDCCY*

Product-Fields
- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Discount-Accrual
- *CLASCD*
- *CLSDFLT*
- *Disc-Accr-Details*
  - *DISCACCRREQD*
  - *ACCRFREQ*
  - *PREPAYTBDTREAT*
  - *ACQTYP*
- *Ccy-Preferences*
  - *CCYCODE*
  - *DENOMDCNTMET*
  - *DENOMMETHOD*

Product-Mis-Details
- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*

CSTCD4

CSTCD5

Default-Mis-Codes

MISTYP

MISCLS

MISCD

KYID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Creation-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates Product Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description	Indicates Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT

Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String
Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAXNOOFLNS

Attribute	**Description**	
Name	MAXNOOFLNS	
Datatype	Number	
Description	Indicates Maximum Number of Loans	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNPRD

Attribute	**Description**	
Name	LNPRD	
Datatype	String	
Description	Indicates Loan Product	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	**Description**	
Name	ALLWSCHEAMNDAFTRSGEN	
Datatype	String	
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	**Description**	
Name	SGENREQD	
Datatype	String	
Description	Indicates Statement Generation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DMNDBASIS

Attribute	Description
Name	DMNDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B,

TOP

AUTOACC

Attribute	Description
Name	AUTOACC
Datatype	String
Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

USRDEFSCHD

Attribute	**Description**	
Name	USRDEFSCHD	
Datatype	String	
Description	Indicates User Defined Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LOANSTMTCYCL

Attribute	**Description**	
Name	LOANSTMTCYCL	
Datatype	String	
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	**Description**	
Name	STMNTDAY	
Datatype	Number	
Description	Indicates Loan Statement Day (of)	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANSTMTTYP

Attribute	**Description**
Name	LOANSTMTTYP
Datatype	String

Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provision Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS

Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN
Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String

Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String
Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDCTTAXONRLOVR

Attribute	**Description**	
Name	DEDCTTAXONRLOVR	
Datatype	String	
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMANRLOVR

Attribute	**Description**	
Name	AUTOMANRLOVR	
Datatype	String	
Description	Indicates Rollover Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

RLOVRMECHNSM

Attribute	**Description**	
Name	RLOVRMECHNSM	
Datatype	String	
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,C,L,

TOP

Default-Schedules

Attribute	**Description**

Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description	
Name	MORATRMPERDUNIT	
Datatype	String	
Description	Indicates Period Unit Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

MORATRMPERD

Attribute	Description	
Name	MORATRMPERD	
Datatype	Number	
Description	Indicates Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Liquidation-Order

Attribute	Description	
Name	Liquidation-Order	
Datatype		
Description	Includes Liquidation Order details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNT

Attribute	Description	
Name	CMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	

Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Status-Advices-Details

Attribute	**Description**	
Name	Status-Advices-Details	
Datatype		
Description	Includes Status Advices detail	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MESSAGECD

Attribute	**Description**	
Name	MESSAGECD	
Datatype	String	
Description	Indicates Message of Status Advices	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Product-Status-Gl-Details

Attribute	**Description**	
Name	Product-Status-Gl-Details	
Datatype		
Description	Includes Product Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCNTROLE

Attribute	**Description**	
Name	ACCNTROLE	
Datatype	String	
Description	Indicates Accounting Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	Indicates Account Head
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Tax-Details

Attribute	Description	
Name	Tax-Details	
Datatype		
Description	Includes Tax Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RUL

Attribute	Description	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	Description	
Name	COMPTATIONEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String

Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR

Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**	
Name	MARGNAPPLN	
Datatype	String	
Description	Indicates Margin Application Periodic : P Automatic : A None : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,A,N

TOP

RATECALCTYP

Attribute	**Description**	
Name	RATECALCTYP	
Datatype	String	
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNT

Attribute	**Description**	
Name	EVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COMPNENT

Attribute	**Description**	
Name	COMPNENT	
Datatype	String	
Description	Indicates Component	
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

COLTYP

Attribute	**Description**	
Name	COLTYP	
Datatype	String	
Description	Indicates Collection Type Advance: A Arrear : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DFLTSPRD

Attribute	**Description**	
Name	DFLTSPRD	
Datatype	Number	
Description	Indicates Default Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPRD

Attribute	**Description**	
Name	MINSPRD	
Datatype	Number	
Description	Indicates Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPRD

Attribute	**Description**	
Name	MAXSPRD	
Datatype	Number	
Description	Indicates Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	

Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQPRNCHNG

Attribute	Description
Name	LIQPRNCHNG
Datatype	String
Description	Indicates Increase In Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Includes Product Charge details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	Includes Product Events details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Accounting-Entries

Attribute	**Description**	
Name	Accounting-Entries	
Datatype		
Description	Accounting Entry Details for Events	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR

Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	**Description**	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description	Indicates the status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes Product Customer Restriction details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers

Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Branch-List

Attribute	Description	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	Description

Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String

Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String

Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	**Description**	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description

Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.14.3.LD-CreateProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*
    - *ACCRSTRTMNTH*
    - *ACCRSTRTDT*
    - *COLCTDRNGAMNDT*

MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO

TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*
- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*

- *MORATRMPERD*
- *Liquidation-Order*
  - *CMPNT*
  - *LIQORDR*
- *Grace-Levels*
  - *LVLNO*
  - *NOOFUNITS*
  - *UNIT*
- *Ccy-Days-Details*
  - *CCY*
  - *EXCRATFXNGDAYS*
  - *INTRATFXNGDAYS*
- *Trs-Components-Details*
  - *COMPNT*
- *Status-Master-Details*
  - *STATUS*
  - *TRANSACTIONCD*
  - *STATUSSEQ*
  - *STPACCRUALS*
  - *REVERSEACCRUALS*
  - *COMPLETEACCRUALS*
  - *TRNSFRCAPITLIZDINCM*
  - *AUTOFRWD*
  - *AUTOREVERSE*
  - *DERVTNRUL*
  - *RBKPROVSN*
  - *Status-Advices-Details*
    - *MESSAGECD*
  - *Product-Status-Gl-Details*
    - *ACCNTROLE*
    - *UPWARDTRANFERFRMGL*
    - *GLDESC*
    - *TRNSFERGL*
    - *DWNWRDTRANSFERFRMGL*
    - *DWNWRDTRANSFERTOGL*
  - *Acc-Status-Gl-Details*
    - *ACCROL*
    - *ROLDESC*
    - *ACCHD*
    - *GLDESC*
- *Tax-Scheme*
  - *SCHME*
  - *SCHEMEDESC*
  - *Tax-Details*

RUL
AMNTTAG
BASISAMNTTAG
COMPTATIONEVNT
TYP
Ccy-Tax-Details
CCY
MAXTAXINTPERD
PERDUNIT
MININTTAXAMT
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY

DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
Product-Accrual-Fee
Accrual-Fee-Details
LIQINT
LIQPRNCHNG
DISCACCRAPP
ACCRREQD
BASISAMT
ENDDTINP
RULFEE
FEETYP
ACCRFREQ
FREQVAL
COMP
STPASSN
COMPNENTDESC
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY
DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB

PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD
EVENTDESC
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
DESC
GENTIME
SUPRS
PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Discount-Accrual*
  - *CLASCD*
  - *CLASDESC*
  - *CLSDFLT*
  - *Disc-Accr-Details*
    - *DISCACCRREQD*
    - *ACCRFREQ*
    - *PREPAYTBDTREAT*
    - *ACQTYP*
  - *Ccy-Preferences*
    - *CCYCODE*
    - *CCYNAME*
    - *DENOMDCNTMET*

DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Creation-Full details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP

Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description
Name	PROD_TYPE_DESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates Product Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description	Indicates Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String

Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String

Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description

Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number

Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String

Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description

Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String

Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXNOOFLNS

Attribute	Description
Name	MAXNOOFLNS
Datatype	Number
Description	Indicates Maximum Number of Loans
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	**Description**	
Name	SGENREQD	
Datatype	String	
Description	Indicates Statement Generation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTCREQD

Attribute	**Description**	
Name	NOTCREQD	
Datatype	String	
Description	Indicates Whether Notice is Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DMNDBASIS

Attribute	**Description**	
Name	DMNDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,B,

TOP

AUTOACC

Attribute	**Description**
Name	AUTOACC
Datatype	String

Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number
Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN

Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String
Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTNRATTYP

Attribute	**Description**	
Name	REVALTNRATTYP	
Datatype	String	
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates Checker ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Product Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Auth Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDCTTAXONRLOVR

Attribute	Description	
Name	DEDCTTAXONRLOVR	
Datatype	String	
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMANRLOVR

Attribute	Description	
Name	AUTOMANRLOVR	
Datatype	String	
Description	Indicates Rollover Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

RLOVRMECHNSM

Attribute	Description	
Name	RLOVRMECHNSM	
Datatype	String	
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description

Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number

Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Status-Master-Details

Attribute	Description	
Name	Status-Master-Details	
Datatype		
Description	Includes Status control Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TRANSACTIONCD

Attribute	Description	
Name	TRANSACTIONCD	
Datatype	String	
Description	Indicates Transaction code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STATUSSEQ

Attribute	Description

Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String

Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN

Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

UPWARDTRANFERFRMGL

Attribute	Description	
Name	UPWARDTRANFERFRMGL	
Datatype	String	
Description	Indicates Upward From GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TRNSFERGL

Attribute	Description	
Name	TRNSFERGL	
Datatype	String	
Description	Indicates Accounting Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description	
Name	DWNWRDTRANSFERFRMGL	
Datatype	String	
Description	Indicates Downward Movement FROM GL Account Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description	
Name	DWNWRDTRANSFERTOGL	
Datatype	String	
Description	Indicates Downward Movement To GL Account Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Acc-Status-Gl-Details

Attribute	Description	
Name	Acc-Status-Gl-Details	
Datatype		
Description	Includes Account Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCROL

Attribute	Description	
Name	ACCROL	
Datatype	String	
Description	Indicates Account Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCHD

Attribute	Description

Name	ACCHD
Datatype	String
Description	Indicates Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description	
Name	COMPTATIONEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	Description	
Name	TYP	
Datatype	String	
Description	Indicates Tax Type WITHHOLDING : W Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Ccy-Tax-Details

Attribute	Description	
Name	Ccy-Tax-Details	
Datatype		
Description	Includes Currency Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,M,Y,</td></tr></table>

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,D,N,O</td></tr></table>

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,P</td></tr></table>

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String

Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR

Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**	
Name	MARGNAPPLN	
Datatype	String	
Description	Indicates Margin Application Periodic : P Automatic : A None : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,A,N

TOP

RATECALCTYP

Attribute	**Description**	
Name	RATECALCTYP	
Datatype	String	
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNT

Attribute	**Description**	
Name	EVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COMPNENT

Attribute	**Description**	
Name	COMPNENT	
Datatype	String	
Description	Indicates Component	
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description

Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description

Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String

Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQPRNCHNG

Attribute	Description
Name	LIQPRNCHNG
Datatype	String
Description	Indicates Increase In Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULDESC

Attribute	Description	
Name	RULDESC	
Datatype	String	
Description	Indicates rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Includes Product Events details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	**Description**	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes Product Customer Restriction details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description	Includes Branch Currency Restrictions details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CLSDFLT

Attribute	**Description**	
Name	CLSDFLT	
Datatype	String	
Description	Indicates Class Default	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description	
Name	DENOMDCNTMET	
Datatype	String	
Description	Indicates Numerator Method 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

DENOMMETHOD

Attribute	Description	
Name	DENOMMETHOD	
Datatype	String	
Description	Indicates Denominator Method The possible values are L, H, X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H,X,

TOP

Product-Mis-Details

Attribute	Description	
Name	Product-Mis-Details	
Datatype		
Description	Includes Product MIS details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description

Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.4.LD-CreateProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDGRP*
      - *DESC*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *RTCODEPRFERD*
      - *PMNTMTHD*
      - *PRDSCHTYP*
      - *DFLTCLSTR*
      - *ACCRFREQ*
      - *ACCRSTRTMNTH*
      - *ACCRSTRTDT*

COLCTDRNGAMNDT
MINTNR
MAXTNR
STDTNR
TNRUNIT
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY

TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*
- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*
- *MORATRMPERD*

Liquidation-Order
- *CMPNT*
- *LIQORDR*

Grace-Levels
- *LVLNO*
- *NOOFUNITS*
- *UNIT*

Ccy-Days-Details
- *CCY*
- *EXCRATFXNGDAYS*
- *INTRATFXNGDAYS*

Trs-Components-Details
- *COMPNT*

Status-Master-Details
- *STATUS*
- *TRANSACTIONCD*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *COMPLETEACCRUALS*
- *TRNSFRCAPITLIZDINCM*
- *AUTOFRWD*
- *AUTOREVERSE*
- *DERVTNRUL*
- *RBKPROVSN*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*
  - *TRNSFERGL*
  - *DWNWRDTRANSFERFRMGL*
  - *DWNWRDTRANSFERTOGL*
- *Acc-Status-Gl-Details*
  - *ACCROL*
  - *ACCHD*

Tax-Scheme
- *SCHME*
- *Tax-Details*
  - *RUL*
  - *BASISAMNTTAG*
  - *COMPTATIONEVNT*
  - *TYP*
  - *Ccy-Tax-Details*
    - *RULE*
    - *CCY*
    - *MAXTAXINTPERD*
    - *PERDUNIT*
    - *MININTTAXAMT*

Product-Interest
- *Interest-Components*
  - *BASISAMNTTYP*

BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
RUL
COLTYP
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
Product-Accrual-Fee
Accrual-Fee-Details
LIQINT
LIQPRNCHNG
DISCACCRAPP

ACCRREQD
BASISAMT
ENDDTINP
RULFEE
FEETYP
ACCRFREQ
FREQVAL
COMP
STPASSN
Product-Charges
Charge-Details
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
DISCACCRAPLB
DISCNTBASIS
DFTRULE
COMPNT
Product-Events
CLASCD
Event-Details
EVNTCD
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
GENTIME

SUPRS
PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
Mapping-Details
ACCTRL
ACCTHD
STAT
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Discount-Accrual
CLASCD
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP

POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Indicates Loans and Deposit Product Creation-PK details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Creation-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXTNR

Attribute	**Description**	
Name	MAXTNR	
Datatype	Number	
Description	Indicates Maximum Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STDTNR

Attribute	**Description**	
Name	STDTNR	
Datatype	Number	
Description	Indicates Default Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TNRUNIT

Attribute	**Description**	
Name	TNRUNIT	
Datatype	String	
Description	Indicates Tenor Unit Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

RKYCCY

Attribute	**Description**	
Name	RKYCCY	
Datatype	String	
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String
Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DYSFORAPYCALC

Attribute	**Description**	
Name	DYSFORAPYCALC	
Datatype	Number	
Description	Indicates Day Basis for Annual Percentage Yield	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ALLWPRTIALREDNONCMNT

Attribute	**Description**	
Name	ALLWPRTIALREDNONCMNT	
Datatype	String	
Description	Indicates Allow Partial Reduction Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFY_DRWDNAMT

Attribute	**Description**	
Name	VRFY_DRWDNAMT	
Datatype	String	
Description	Indicates Verify Drawdown Amount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAXNOOFLNS

Attribute	**Description**	
Name	MAXNOOFLNS	
Datatype	Number	
Description	Indicates Maximum Number of Loans	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates Statement Generation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DMNDBASIS

Attribute	Description	
Name	DMNDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,B,

TOP

AUTOACC

Attribute	Description	
Name	AUTOACC	
Datatype	String	
Description	Indicates Auto Account Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCCLSS

Attribute	Description	
Name	ACCCLSS	
Datatype	String	
Description	Indicates Account Class	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LOANSTMTCYCL

Attribute	Description	
Name	LOANSTMTCYCL	
Datatype	String	
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description	
Name	STMNTDAY	
Datatype	Number	
Description	Indicates Loan Statement Day (of)	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANSTMTTYP

Attribute	Description	
Name	LOANSTMTTYP	
Datatype	String	
Description	Indicates Loan Statement Type None : N Summary : S Detail : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD

Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provision Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONSDRBRNHOL

Attribute	**Description**	
Name	CONSDRBRNHOL	
Datatype	String	
Description	Indicates Consider Branch Holiday Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGNRHOLDYS

Attribute	**Description**	
Name	IGNRHOLDYS	
Datatype	String	
Description	Indicates Ignore Holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CSCDESCHDLS

Attribute	**Description**	
Name	CSCDESCHDLS	
Datatype	String	
Description	Indicates Cascade Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MVACRSMNTHS

Attribute	**Description**
Name	MVACRSMNTHS
Datatype	String

Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESCLS

Attribute	Description	
Name	PRDDESCLS	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CASCDEPRTCPTN

Attribute	Description	
Name	CASCDEPRTCPTN	
Datatype	String	
Description	Indicates Cascade Participation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOLDFLTBASIS

Attribute	Description	
Name	HOLDFLTBASIS	
Datatype	String	
Description	Indicates Holiday Default Basis Facility : F Product : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String

Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String
Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number

Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDCTTAXONRLOVR

Attribute	Description
Name	DEDCTTAXONRLOVR
Datatype	String
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMANRLOVR

Attribute	Description
Name	AUTOMANRLOVR
Datatype	String
Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String

Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	

Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVERSEACCRUALS

Attribute	**Description**	
Name	REVERSEACCRUALS	
Datatype	String	
Description	Indicates Reverse Accruals Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPLETEACCRUALS

Attribute	**Description**	
Name	COMPLETEACCRUALS	
Datatype	String	
Description	Indicates Complete Accruals Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	**Description**	
Name	TRNSFRCAPITLIZDINCM	
Datatype	String	
Description	Indicates Transfer Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOFRWD

Attribute	**Description**
Name	AUTOFRWD
Datatype	String

Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details

Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	Description

Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	Indicates Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RUL

Attribute	Description	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	Description	
Name	COMPTATIONEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	Description	
Name	TYP	
Datatype	String	
Description	Indicates Tax Type WITHHOLDING : W Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String

Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SETTLMNTCCY

Attribute	**Description**	
Name	SETTLMNTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STPAPPLICTION

Attribute	**Description**	
Name	STPAPPLICTION	
Datatype	String	
Description	Indicates Stop Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RESETTENOR

Attribute	**Description**	
Name	RESETTENOR	
Datatype	Number	
Description	Indicates Reset Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRWLENDIND

Attribute	**Description**
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String

Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LIQINT

Attribute	**Description**	
Name	LIQINT	
Datatype	String	
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQPRNCHNG

Attribute	**Description**	
Name	LIQPRNCHNG	
Datatype	String	
Description	Indicates Increase In Principal Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP

Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN

Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	**Description**	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**
Name	DISCNTBASIS
Datatype	String

Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,C</td></tr></table>

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD

Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description

Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes Product Customer Restriction details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLSDFLT

Attribute	**Description**	
Name	CLSDFLT	
Datatype	String	
Description	Indicates Class Default	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Disc-Accr-Details

Attribute	**Description**	
Name	Disc-Accr-Details	
Datatype		
Description	Includes Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,D,P,A,

TOP

Ccy-Preferences

Attribute	**Description**	
Name	Ccy-Preferences	
Datatype		
Description	Includes Currency Preferences details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCYCODE

Attribute	**Description**	
Name	CCYCODE	
Datatype	String	
Description	Indicates Currency Code	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DENOMDCNTMET

Attribute	**Description**	
Name	DENOMDCNTMET	
Datatype	String	
Description	Indicates Numerator Method 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

DENOMMETHOD

Attribute	**Description**	
Name	DENOMMETHOD	
Datatype	String	
Description	Indicates Denominator Method The possible values are L, H, X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2

Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.DeleteBrnPrm

Deletion of Loans and Deposit Branch Parameters

2.15.1.LD-DeleteBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	Include Loans and deposits branch parameters full details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates Button For UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicate the maker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the maker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the checker stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates transaction status Open : O Closed :C
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.15.2.LD-DeleteBrnPrm-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Ld-Branch-Params-IO
BRNCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	Include Loans and deposits Branch parameters delete IO type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

2.15.3.LD-DeleteBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*

FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	Include Loans and deposits branch parameters full details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates Button For UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicate the maker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the maker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the checker stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates transaction status Open : O Closed :C
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.15.4.LD-DeleteBrnPrm-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
Ld-Branch-Params-PK
BRNCD
Ld-Branch-Params-IO
BRNCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	Include Loans and deposits Branch parameters PK type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	Include Loans and deposits Branch parameters delete IO type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.16.DeleteFeeAccrualLDContract

Deletion of FeeAccrual Loans and Deposit Contract

2.16.1.LD-DeleteFeeAccrual-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*

COMP
FEEAMT
REFAMT
VALDT
ACCBRN
ACC
BASAMT
CALCSTDT
CALCENDDT
FEETYP
CONSDISCNT
ACCREQD
FEECCY
REFCCY
COMPCCY
COMPESN
AMT
AMTCCY
FEEAUDIT
ESN
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT
REVR_MAKERID
REVR_MAKERSTAMP
REVR_CHECKERID
REVR_CHECKERSTAMP
STLDETAILS_IS_MAIN
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4

BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP

PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS

PRIORITY

CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Fee Accrual Delete that has been successfully deleted

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Deletion details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MATDATE

Attribute	Description
Name	MATDATE
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREF

Attribute	Description
Name	CUSTREF
Datatype	String
Description	Indicates Custom Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description
Name	BASAMT
Datatype	String
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicates Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

2.16.2.LD-DeleteFeeAccrual-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *XREF*
    - *Contract-Accr-Fee*
      - *FCCREF*
      - *COMPCCY*
      - *FEEAMT*
      - *REFAMT*
      - *VALDT*
      - *CALCSTDT*
      - *CALCENDDT*
      - *FEETYP*
      - *ACCREQD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual delete that has been successfully deleted

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Deletion-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	**Description**	
Name	Contract-Accr-Fee	
Datatype		
Description	Include Loans and Deposits Contract fee type details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	**Description**	
Name	COMPCCY	
Datatype	String	
Description	Indicate Component Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number
Description	Indicate Fee Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicate Refund Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.16.3.LD-DeleteFeeAccrual-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*
      - *COMP*
      - *FEEAMT*
      - *REFAMT*

- *VALDT*
- *ACCBRN*
- *ACC*
- *BASAMT*
- *CALCSTDT*
- *CALCENDDT*
- *FEETYP*
- *CONSDISCNT*
- *ACCREQD*
- *FEECCY*
- *REFCCY*
- *COMPCCY*
- *COMPESN*
- *AMT*
- *AMTCCY*

FEEAUDIT

- *ESN*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *CONTSTAT*
- *AUTHSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*

STLDETAILS_IS_MAIN

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*

BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2

PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the Fee Accrual delete that has been successfully deleted

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Deletion details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MATDATE

Attribute	**Description**	
Name	MATDATE	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	**Description**	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREF

Attribute	**Description**	
Name	USRREF	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREF

Attribute	**Description**	
Name	CUSTREF	
Datatype	String	
Description	Indicates Custom Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST5

Attribute	Description

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.16.4.LD-DeleteFeeAccrual-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-PK*
      - *FCCREF*
      - *USRREF*
    - *Contract-IO*
      - *FCCREF*
      - *XREF*
      - *Contract-Accr-Fee*
        - *FCCREF*
        - *COMPCCY*
        - *FEEAMT*
        - *REFAMT*
        - *VALDT*
        - *CALCSTDT*
        - *CALCENDDT*
        - *FEETYP*
        - *ACCREQD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual delete that has been successfully deleted

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-PK

Attribute	Description
Name	Contract-PK
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Deletion-Primary key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicate User Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Contract-IO

Attribute	Description
Name	Contract-IO
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Deletion-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	Description
Name	Contract-Accr-Fee
Datatype	
Description	Include Loans and Deposits Contract fee type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicate Component Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number
Description	Indicate Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicate Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.DeleteLDBrnPrm

Delete Branch Parameter for LD / MM

2.17.1.LD-DeleteLDBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.17.2.LD-DeleteLDBrnPrm-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Ld-Branch-Params-IO
BRNCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

2.17.3.LD-DeleteLDBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.4.LD-DeleteLDBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.18.ReverseLDPayment

Reversal of Loans and Deposits Payment

2.18.1.LDPayment-Reverse-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *XREF*
    - *FCCREF*
    - *CPTY*
    - *STATUS*
    - *OSBAL*
    - *CCY*
    - *OLDMATDT*
    - *NEWMATDT*
    - *EFFFROM*
    - *PREPMTBASIS*
    - *PREPMTEFFFROM*
    - *VALDT*
    - *TOTPAID*
    - *LIMITDT*
    - *DISCRATE*

TOTPREPAID
LIMITAMT
LIQDFACEVAL
PREPMTPENRATE
PREPMTPENAMT
PREPMTADJAMT1
PREPMTADJAMT2
PAYMNTREM
LCYEQVTTOTPAID
LCYEQVTTOTPREPAID
LCYEQVTLIMITAMT
LCYEQVTLIQDFACEVALUE
OSBALREP
SYNDNO
SUBSYSTEMSTAT
CURRPMNT
TOTPAMNT
Payment-Breakup
  FCCREF
  COMP
  AMTDUE
  AMTPAID
Schedule-Details
  FCCREF
  SCOMP
  DUEDT
  AMTDUE
  AMTSETTL
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  REVR_MAKERID
  REVR_CHECKERID
  REVR_MAKERSTAMP
  REVR_CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
  REVR_AUTHSTAT
  REVR_CONTSTAT
Settlement-Addl-Details
  ACCBRN
  ACC_CCY

ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT

INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3

TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR

- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*
    - *TAXCCY*
    - *VALDT*
    - *COMPDT*
- *Contract_Schedules*

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

MSGTYPE

PARTYID

MEDIUM

SUPPRESS

PRIORITY

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	Includes Loans and Deposits Payment Reversal Summary details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

OSBAL

Attribute	Description
Name	OSBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OLDMATDT

Attribute	Description
Name	OLDMATDT
Datatype	Date
Description	Indicates Old Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWMATDT

Attribute	Description
Name	NEWMATDT
Datatype	Date
Description	Indicates New Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFFROM

Attribute	Description
Name	EFFFROM
Datatype	String
Description	Indicates Effective From
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

PREPMTBASIS

Attribute	Description
Name	PREPMTBASIS
Datatype	String
Description	Indicates Recomputation Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PREPMTEFFFROM

Attribute	Description
Name	PREPMTEFFFROM
Datatype	String
Description	Indicates Prepayment Effective From
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCRATE

Attribute	Description
Name	DISCRATE
Datatype	Number
Description	Indicates Disc. Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

TOTPREPAID

Attribute	Description

Name	TOTPREPAID
Datatype	Number
Description	Indicates Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDFACEVAL

Attribute	Description
Name	LIQDFACEVAL
Datatype	Number
Description	Indicates Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

PREPMTPENRATE

Attribute	Description
Name	PREPMTPENRATE
Datatype	Number
Description	Indicates Prepayment Penalty Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTPENAMT

Attribute	Description
Name	PREPMTPENAMT
Datatype	Number
Description	Indicates Penalty Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT1

Attribute	Description
Name	PREPMTADJAMT1
Datatype	Number
Description	Indicates Adjust Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT2

Attribute	Description
Name	PREPMTADJAMT2
Datatype	Number
Description	Indicates Addl. Adj. Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCYEQVTTOTPAID

Attribute	Description
Name	LCYEQVTTOTPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LCYEQVTTOTPREPAID

Attribute	Description
Name	LCYEQVTTOTPREPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LCYEQVTLIMITAMT

Attribute	Description
Name	LCYEQVTLIMITAMT
Datatype	Number
Description	Indicates Local Currency Equivalent of Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

LCYEQVTLIQDFACEVALUE

Attribute	Description
Name	LCYEQVTLIQDFACEVALUE
Datatype	Number
Description	Indicates Local Currency Equivalent of Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

OSBALREP

Attribute	Description
Name	OSBALREP
Datatype	Number
Description	Indicates O/S Bal- Rep
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SYNDNO

Attribute	Description
Name	SYNDNO
Datatype	Number
Description	Indicates Syndication Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates SubSystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CURRPMNT

Attribute	Description
Name	CURRPMNT
Datatype	Number
Description	Indicates Current Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TOTPAMNT

Attribute	Description
Name	TOTPAMNT
Datatype	Number
Description	Indicates Total Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	Includes Payment Break Up details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

AMTDUE

Attribute	Description

Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates Amount Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedules details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String

Description	Indicates Contract Payment Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Includes Settlement Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description

Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COSTCOD1

Attribute	Description	
Name	COSTCOD1	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COSTCOD2

Attribute	Description	
Name	COSTCOD2	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Mis-Amend

Attribute	**Description**	
Name	Mis-Amend	
Datatype		
Description	Includes MIS Amendment details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREF

Attribute	**Description**
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance Rate details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String

Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Field details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>5</td></tr></table>

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,L,M</td></tr></table>

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax Main details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Inlcudes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Inlcudes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description

Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Inlcudes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	**Description**

Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.18.2.LDPayment-Reverse-Res-IOPK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Summary-IO*
      - *FCCREF*
      - *XREF*
      - *TOTPAID*
      - *VALDT*
      - *LIMITDT*
      - *Payment-Breakup*
        - *COMP*
        - *AMTDUE*
        - *OVERDUE*
        - *AMTPAID*
        - *INTPREPAY*
        - *TAXPAID*
    - *Payment-Summary-PK*
      - *XREF*
      - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Summary-IO

Attribute	Description
Name	Payment-Summary-IO
Datatype	
Description	Inlcudes Loans and Deposits Payment Reversal Summary Input Only details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Includes Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Includes External Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALDT

Attribute	Description

Name	VALDT
Datatype	Date
Description	Indicates Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	Includes Payment Break up Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

OVERDUE

Attribute	Description
Name	OVERDUE
Datatype	Number
Description	Indicates Over Due.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTPREPAY

Attribute	Description
Name	INTPREPAY
Datatype	Number
Description	Indicates the Interest Prepaid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Payment-Summary-PK

Attribute	Description
Name	Payment-Summary-PK
Datatype	
Description	Inlcudes Loans and Deposits Payment Reversal Summary Primary Key details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Includes External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Includes Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.3.LDPayment-Reverse-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *XREF*
    - *FCCREF*
    - *CPTY*
    - *STATUS*
    - *OSBAL*
    - *CCY*
    - *OLDMATDT*
    - *NEWMATDT*
    - *EFFFROM*
    - *PREPMTBASIS*
    - *PREPMTEFFFROM*
    - *VALDT*
    - *TOTPAID*
    - *LIMITDT*
    - *DISCRATE*
    - *TOTPREPAID*
    - *LIMITAMT*
    - *LIQDFACEVAL*

PREPMTPENRATE
PREPMTPENAMT
PREPMTADJAMT1
PREPMTADJAMT2
PAYMNTREM
LCYEQVTTOTPAID
LCYEQVTTOTPREPAID
LCYEQVTLIMITAMT
LCYEQVTLIQDFACEVALUE
OSBALREP
SYNDNO
SUBSYSTEMSTAT
CURRPMNT
TOTPAMNT
Payment-Breakup
  FCCREF
  COMP
  AMTDUE
  AMTPAID
Schedule-Details
  FCCREF
  SCOMP
  DUEDT
  AMTDUE
  AMTSETTL
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  REVR_MAKERID
  REVR_CHECKERID
  REVR_MAKERSTAMP
  REVR_CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
  REVR_AUTHSTAT
  REVR_CONTSTAT
Settlement-Addl-Details
  ACCBRN
  ACC_CCY
  ACC
  AMTTAG
  CUSTSPRD

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*
    - *TAXCCY*
    - *VALDT*
    - *COMPDT*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*

- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*

MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Reversal of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	Includes Loans and Deposits Payment Reversal Summary details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

OSBAL

Attribute	Description
Name	OSBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

OLDMATDT

Attribute	Description
Name	OLDMATDT
Datatype	Date
Description	Indicates Old Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEWMATDT

Attribute	Description
Name	NEWMATDT

Datatype	Date
Description	Indicates New Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFFROM

Attribute	Description
Name	EFFFROM
Datatype	String
Description	Indicates Effective From
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

PREPMTBASIS

Attribute	Description
Name	PREPMTBASIS
Datatype	String
Description	Indicates Recomputation Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PREPMTEFFFROM

Attribute	Description
Name	PREPMTEFFFROM
Datatype	String
Description	Indicates Prepayment Effective From
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCRATE

Attribute	Description
Name	DISCRATE
Datatype	Number
Description	Indicates Disc. Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

TOTPREPAID

Attribute	Description
Name	TOTPREPAID
Datatype	Number
Description	Indicates Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDFACEVAL

Attribute	Description
Name	LIQDFACEVAL
Datatype	Number
Description	Indicates Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

PREPMTPENRATE

Attribute	Description
Name	PREPMTPENRATE
Datatype	Number
Description	Indicates Prepayment Penalty Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTPENAMT

Attribute	Description
Name	PREPMTPENAMT
Datatype	Number
Description	Indicates Penalty Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT1

Attribute	Description
Name	PREPMTADJAMT1
Datatype	Number
Description	Indicates Adjust Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT2

Attribute	Description
Name	PREPMTADJAMT2
Datatype	Number
Description	Indicates Addl. Adj. Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCYEQVTTOTPAID

Attribute	Description
Name	LCYEQVTTOTPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LCYEQVTTOTPREPAID

Attribute	Description
Name	LCYEQVTTOTPREPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LCYEQVTLIMITAMT

Attribute	Description
Name	LCYEQVTLIMITAMT
Datatype	Number
Description	Indicates Local Currency Equivalent of Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

LCYEQVTLIQDFACEVALUE

Attribute	Description
Name	LCYEQVTLIQDFACEVALUE
Datatype	Number
Description	Indicates Local Currency Equivalent of Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

OSBALREP

Attribute	Description
Name	OSBALREP
Datatype	Number
Description	Indicates O/S Bal- Rep
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SYNDNO

Attribute	Description
Name	SYNDNO
Datatype	Number
Description	Indicates Syndication Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates SubSystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CURRPMNT

Attribute	Description
Name	CURRPMNT
Datatype	Number
Description	Indicates Current Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TOTPAMNT

Attribute	Description
Name	TOTPAMNT
Datatype	Number
Description	Indicates Total Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	Includes Payment Break Up details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTPAID

Attribute	Description

Name	AMTPAID
Datatype	Number
Description	Indicates Amount Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedules details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_MAKERID

Attribute	Description	
Name	REVR_MAKERID	
Datatype	String	
Description	Indicates the Maker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERID

Attribute	Description	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Payment Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates the ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**
Name	TAG_CCY
Datatype	String
Description	Indicates Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance Rate details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date

Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Field details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

RETENOR

Attribute	**Description**	
Name	RETENOR	
Datatype	Number	
Description	Indicates the Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	5

TOP

BORLENIND

Attribute	**Description**	
Name	BORLENIND	
Datatype	String	
Description	Indicates the Borrow \ Lend Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M

TOP

RTCALCTYP

Attribute	**Description**	
Name	RTCALCTYP	
Datatype	String	
Description	Indicates the Interest Rate Calculation type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	**Description**	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

DENOBASIS

Attribute	Description	
Name	DENOBASIS	
Datatype	String	
Description	Indicates the Denominator basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description	Indicates the BASIS_366	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOINTPRD

Attribute	Description	
Name	NOINTPRD	
Datatype	Number	
Description	Indicates the No of Interest Period.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	Description	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	**Description**	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

Taxdetails-Main

Attribute	Description	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	Description	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Inlcudes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Inlcudes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Inlcudes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

2.18.4.LDPayment-Reverse-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *FCCREF*
    - *XREF*
    - *TOTPAID*
    - *VALDT*
    - *LIMITDT*
    - *Payment-Breakup*
      - *COMP*
      - *AMTDUE*
      - *OVERDUE*
      - *AMTPAID*
      - *INTPREPAY*
      - *TAXPAID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Reverse of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	Includes Loans and Deposits Payment Reversal Summary details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String

Description	Includes Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Includes External Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid.
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup

Datatype	
Description	Includes Payment Break up Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

OVERDUE

Attribute	Description
Name	OVERDUE
Datatype	Number
Description	Indicates Over Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

INTPREPAY

Attribute	Description
Name	INTPREPAY
Datatype	Number
Description	Indicates the Interest Prepaid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

2.19.AuthProvisionLDContract

Authorization of Provision Loans and Deposit Contract

2.19.1.LDProvision-Authorise-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *PROVISION*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for creation of LD Contract Provision

TOP

PROVISION

Attribute	Description
Name	PROVISION
Datatype	
Description	Includes Loans and Deposits Authorize Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates the Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	Description	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.19.2.LDProvision-Authorise-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *PROVISION-DETAILS*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the LD Contract Provision that has been successfully authorised

TOP

PROVISION-DETAILS

Attribute	Description
Name	PROVISION-DETAILS
Datatype	
Description	Includes Loans and Deposits Authorize Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SEQ

Attribute	Description
Name	SEQ
Datatype	Number
Description	Indicates the Sequence number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.CreateProvisionLDContract

Creation of Provision Loans and Deposit Contract

2.20.1.LDProvision-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *PROVISION*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for creation of LD Contract Provision.

TOP

PROVISION

Attribute	Description
Name	PROVISION
Datatype	
Description	Includes Loans and Deposits Create Contract Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates the Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	Description	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.20.2.LDProvision-Create-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CONTRACT_PROVISION-IO-IO*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for LD Contract Provision .

TOP

CONTRACT_PROVISION-IO-IO

Attribute	Description
Name	CONTRACT_PROVISION-IO-IO
Datatype	
Description	Includes Loans and Deposits Create Contract Provision Input Only details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates the Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	Description	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.20.3.LDProvision-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *PROVISION-DETAILS*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the LD Contract Provision that has been successfully Created

TOP

PROVISION-DETAILS

Attribute	Description
Name	PROVISION-DETAILS
Datatype	
Description	Includes Loans and Deposits Create Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SEQ

Attribute	Description
Name	SEQ
Datatype	Number
Description	Indicates the Sequence number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.4.LDProvision-Create-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *PROVISION-DETAILS*
      - *FCCREF*
      - *CCY*
      - *AMT*
      - *SEQ*
      - *STAT*
      - *CONTRACT-EVENT-LOG*
        - *MAKERID*
        - *MAKERSTAMP*
        - *CHECKERID*
        - *CHECKERSTAMP*
        - *CONTSTAT*
        - *AUTHSTAT*
    - *CONTRACT_PROVISION-IO*
      - *FCCREF*
      - *CCY*
      - *AMT*
      - *SEQ*

STAT
CONTRACT-EVENT-LOG
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Registered

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

PROVISION-DETAILS

Attribute	Description
Name	PROVISION-DETAILS
Datatype	
Description	Includes Loans and Deposits Create Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SEQ

Attribute	Description
Name	SEQ
Datatype	Number
Description	Indicates the Sequence number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String

Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTRACT_PROVISION-IO

Attribute	Description
Name	CONTRACT_PROVISION-IO
Datatype	
Description	Includes Loans and Deposits Create Contract Provision Input Only details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	**Description**	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	4

TOP

CONTRACT-EVENT-LOG

Attribute	**Description**	
Name	CONTRACT-EVENT-LOG	
Datatype		
Description	Includes the Contract Event Log Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.ModifyProvisionLDContract

Modification of Provision Loans and Deposit Contract

2.21.1.LDProvision-Modify-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *PROVISION*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for modification of LD Contract Provision

TOP

PROVISION

Attribute	Description
Name	PROVISION
Datatype	
Description	Includes Loans and Deposits Modify Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates the Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	Description	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.21.2.LDProvision-Modify-Req-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CONTRACT_PROVISION-IO-IO
FCCREF
CCY
AMT
SEQ
STAT
CONTRACT-EVENT-LOG
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for LD Contract Provision .

TOP

CONTRACT_PROVISION-IO-IO

Attribute	Description
Name	CONTRACT_PROVISION-IO-IO
Datatype	
Description	Includes Loans and Deposits Modify Contract Provision Input Only details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates the Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	Description	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.21.3.LDProvision-Modify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *PROVISION-DETAILS*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the LD Contract Provision that has been successfully modified

TOP

PROVISION-DETAILS

Attribute	Description
Name	PROVISION-DETAILS
Datatype	
Description	Includes Loans and Deposits Modify Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SEQ

Attribute	Description
Name	SEQ
Datatype	Number
Description	Indicates the Sequence number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	4

TOP

CONTRACT-EVENT-LOG

Attribute	Description	
Name	CONTRACT-EVENT-LOG	
Datatype		
Description	Includes the Contract Event Log Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.4.LDProvision-Modify-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *PROVISION-DETAILS*
      - *FCCREF*
      - *CCY*
      - *AMT*
      - *SEQ*
      - *STAT*
      - *CONTRACT-EVENT-LOG*
        - *MAKERID*
        - *MAKERSTAMP*
        - *CHECKERID*
        - *CHECKERSTAMP*
        - *CONTSTAT*
        - *AUTHSTAT*
    - *CONTRACT_PROVISION-IO*
      - *FCCREF*
      - *CCY*
      - *AMT*
      - *SEQ*

STAT
CONTRACT-EVENT-LOG
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	**Description**	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully modified

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

PROVISION-DETAILS

Attribute	Description
Name	PROVISION-DETAILS
Datatype	
Description	Includes Loans and Deposits Modify Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SEQ

Attribute	Description
Name	SEQ
Datatype	Number
Description	Indicates the Sequence number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String

Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTRACT_PROVISION-IO

Attribute	Description
Name	CONTRACT_PROVISION-IO
Datatype	
Description	Includes Loans and Deposits Modify Contract Provision Input Only details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	**Description**	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	4

TOP

CONTRACT-EVENT-LOG

Attribute	**Description**	
Name	CONTRACT-EVENT-LOG	
Datatype		
Description	Includes the Contract Event Log Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.DeleteLDPaymentSim

Deleteion of deposit payment simulation

2.22.1.LD-DeleteLDPaymentSim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *XREF*
    - *FCCREF*
    - *CPTY*
    - *STATUS*
    - *OSBAL*
    - *CCY*
    - *OLDMATDT*
    - *NEWMATDT*
    - *EFFFROM*
    - *PREPMTBASIS*
    - *PREPMTEFFFROM*
    - *VALDT*
    - *TOTPAID*
    - *LIMITDT*
    - *DISCRATE*

TOTPREPAID
LIMITAMT
LIQDFACEVAL
PREPMTPENRATE
PREPMTPENAMT
PREPMTADJAMT1
PREPMTADJAMT2
PAYMNTREM
LCYEQVTTOTPAID
LCYEQVTTOTPREPAID
LCYEQVTLIMITAMT
LCYEQVTLIQDFACEVALUE
OSBALREP
SYNDNO
SUBSYSTEMSTAT
CURRPMNT
TOTPAMNT
Payment-Breakup
  FCCREF
  COMP
  AMTDUE
  AMTPAID
Schedule-Details
  FCCREF
  SCOMP
  DUEDT
  AMTDUE
  AMTSETTL
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  REVR_MAKERID
  REVR_CHECKERID
  REVR_MAKERSTAMP
  REVR_CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
  REVR_AUTHSTAT
  REVR_CONTSTAT
Settlement-Addl-Details
  ACCBRN
  ACC_CCY

ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT

INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3

TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend

CONTREF
RTYPE
RCODE
SPD

Refinance-Rate

UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR

- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*
    - *TAXCCY*
    - *VALDT*
    - *COMPDT*
- *Contract_Schedules*

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

MSGTYPE

PARTYID

MEDIUM

SUPPRESS

PRIORITY

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

OSBAL

Attribute	Description
Name	OSBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OLDMATDT

Attribute	Description
Name	OLDMATDT
Datatype	Date
Description	Indicates Old Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWMATDT

Attribute	Description

Name	NEWMATDT
Datatype	Date
Description	Indicates New Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFFROM

Attribute	Description
Name	EFFFROM
Datatype	String
Description	Indicates Effective From
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

PREPMTBASIS

Attribute	Description
Name	PREPMTBASIS
Datatype	String
Description	Indicates Recomputation Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PREPMTEFFFROM

Attribute	Description
Name	PREPMTEFFFROM
Datatype	String
Description	Indicates Prepayment Effective From
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCRATE

Attribute	Description
Name	DISCRATE
Datatype	Number
Description	Indicates Disc. Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

TOTPREPAID

Attribute	Description
Name	TOTPREPAID
Datatype	Number
Description	Indicates Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDFACEVAL

Attribute	Description
Name	LIQDFACEVAL
Datatype	Number
Description	Indicates Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

PREPMTPENRATE

Attribute	Description
Name	PREPMTPENRATE
Datatype	Number
Description	Indicates Prepayment Penalty Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTPENAMT

Attribute	Description
Name	PREPMTPENAMT
Datatype	Number
Description	Indicates Penalty Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT1

Attribute	Description
Name	PREPMTADJAMT1
Datatype	Number
Description	Indicates Adjust Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTADJAMT2

Attribute	Description
Name	PREPMTADJAMT2
Datatype	Number
Description	Indicates Addl. Adj. Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCYEQVTTOTPAID

Attribute	Description
Name	LCYEQVTTOTPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LCYEQVTTOTPREPAID

Attribute	Description
Name	LCYEQVTTOTPREPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Amount Prepaid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LCYEQVTLIMITAMT

Attribute	Description
Name	LCYEQVTLIMITAMT
Datatype	Number
Description	Indicates Local Currency Equivalent of Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

LCYEQVTLIQDFACEVALUE

Attribute	Description
Name	LCYEQVTLIQDFACEVALUE
Datatype	Number
Description	Indicates Local Currency Equivalent of Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

OSBALREP

Attribute	Description
Name	OSBALREP
Datatype	Number
Description	Indicates O/S Bal- Rep
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SYNDNO

Attribute	Description
Name	SYNDNO
Datatype	Number
Description	Indicates Syndication Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates SubSystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CURRPMNT

Attribute	Description
Name	CURRPMNT
Datatype	Number
Description	Indicates Current Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TOTPAMNT

Attribute	Description
Name	TOTPAMNT
Datatype	Number
Description	Indicates Total Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	Includes Payment Break Up details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTPAID

Attribute	Description

Name	AMTPAID
Datatype	Number
Description	Indicates Amount Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedules details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_MAKERID

Attribute	Description	
Name	REVR_MAKERID	
Datatype	String	
Description	Indicates the Maker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERID

Attribute	Description	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Payment Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REVR_CONTSTAT

Attribute	**Description**	
Name	REVR_CONTSTAT	
Datatype	String	
Description	Indicates the Contract status of reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**
Name	TAG_CCY
Datatype	String
Description	Indicates Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM4

Attribute	Description	
Name	RCVR_CUSNM4	
Datatype	String	
Description	Indicates the Receiver Name 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description	
Name	SNDR_ACC	
Datatype	String	
Description	Indicates the Sender Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

RCVR_ACC

Attribute	Description	
Name	RCVR_ACC	
Datatype	String	
Description	Indicates the Receiver Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance Rate details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date

Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Field details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax Main details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Inlcudes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Inlcudes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	Description	
Name	AVLAMT	
Datatype	Number	
Description	Indicates the Available amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Inlcudes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

2.22.2.LD-DeleteLDPaymentSim-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Summary-PK*
      - *XREF*
      - *FCCREF*
    - *Payment-Summary-IO*
      - *FCCREF*
      - *XREF*
      - *TOTPAID*
      - *VALDT*
      - *LIMITDT*
      - *Payment-Breakup*
        - *COMP*
        - *AMTDUE*
        - *OVERDUE*
        - *AMTPAID*
        - *INTPREPAY*
        - *TAXPAID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Summary-PK

Attribute	Description
Name	Payment-Summary-PK
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Payment-Summary-IO

Attribute	Description
Name	Payment-Summary-IO
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid.
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	

Description	Includes Payment Break up Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

OVERDUE

Attribute	Description
Name	OVERDUE
Datatype	Number
Description	Indicates Over Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

INTPREPAY

Attribute	Description
Name	INTPREPAY
Datatype	Number
Description	Indicates the Interest Prepaid.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.3.LD-DeleteLDPaymentSimReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *FCCREF*
    - *XREF*
    - *TOTPAID*
    - *VALDT*
    - *LIMITDT*
    - *Payment-Breakup*
      - *COMP*
      - *AMTDUE*
      - *OVERDUE*
      - *AMTPAID*
      - *INTPREPAY*
      - *TAXPAID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Includes Contract Reference Number

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Includes External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid.
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	

Description	Includes Payment Break up Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

OVERDUE

Attribute	Description
Name	OVERDUE
Datatype	Number
Description	Indicates Over Due.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

INTPREPAY

Attribute	Description
Name	INTPREPAY
Datatype	Number
Description	Indicates the Interest Prepaid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

2.22.4.LD-DeleteLDPaymentSimRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Summary*
    - *XREF*
    - *FCCREF*
    - *CPTY*
    - *STATUS*
    - *OSBAL*
    - *CCY*
    - *OLDMATDT*
    - *NEWMATDT*
    - *EFFFROM*
    - *PREPMTBASIS*
    - *PREPMTEFFFROM*
    - *VALDT*
    - *TOTPAID*
    - *LIMITDT*
    - *DISCRATE*
    - *TOTPREPAID*
    - *LIMITAMT*
    - *LIQDFACEVAL*

PREPMTPENRATE
PREPMTPENAMT
PREPMTADJAMT1
PREPMTADJAMT2
PAYMNTREM
LCYEQVTTOTPAID
LCYEQVTTOTPREPAID
LCYEQVTLIMITAMT
LCYEQVTLIQDFACEVALUE
OSBALREP
SYNDNO
SUBSYSTEMSTAT
CURRPMNT
TOTPAMNT
Payment-Breakup
  FCCREF
  COMP
  AMTDUE
  AMTPAID
Schedule-Details
  FCCREF
  SCOMP
  DUEDT
  AMTDUE
  AMTSETTL
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  REVR_MAKERID
  REVR_CHECKERID
  REVR_MAKERSTAMP
  REVR_CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
  REVR_AUTHSTAT
  REVR_CONTSTAT
Settlement-Addl-Details
  ACCBRN
  ACC_CCY
  ACC
  AMTTAG
  CUSTSPRD

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*
    - *TAXCCY*
    - *VALDT*
    - *COMPDT*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*

- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*

MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Payment-Summary

Attribute	Description
Name	Payment-Summary
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

OSBAL

Attribute	**Description**	
Name	OSBAL	
Datatype	Number	
Description	Indicates Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

OLDMATDT

Attribute	**Description**
Name	OLDMATDT
Datatype	Date
Description	Indicates Old Maturity Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEWMATDT

Attribute	**Description**	
Name	NEWMATDT	
Datatype	Date	
Description	Indicates New Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EFFFROM

Attribute	**Description**	
Name	EFFFROM	
Datatype	String	
Description	Indicates Effective From	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	2

TOP

PREPMTBASIS

Attribute	**Description**	
Name	PREPMTBASIS	
Datatype	String	
Description	Indicates Recomputation Basis	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PREPMTEFFFROM

Attribute	**Description**	
Name	PREPMTEFFFROM	
Datatype	String	
Description	Indicates Prepayment Effective From	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIMITDT

Attribute	Description
Name	LIMITDT
Datatype	Date
Description	Indicates Limit Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCRATE

Attribute	Description
Name	DISCRATE
Datatype	Number
Description	Indicates Disc. Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TOTPREPAID

Attribute	Description
Name	TOTPREPAID
Datatype	Number
Description	Indicates Amount Prepaid

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDFACEVAL

Attribute	Description
Name	LIQDFACEVAL
Datatype	Number
Description	Indicates Liquidated Nominal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

PREPMTPENRATE

Attribute	Description
Name	PREPMTPENRATE
Datatype	Number
Description	Indicates Prepayment Penalty Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREPMTPENAMT

Attribute	Description
Name	PREPMTPENAMT
Datatype	Number
Description	Indicates Penalty Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREPMTADJAMT1

Attribute	**Description**	
Name	PREPMTADJAMT1	
Datatype	Number	
Description	Indicates Adjust Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREPMTADJAMT2

Attribute	**Description**	
Name	PREPMTADJAMT2	
Datatype	Number	
Description	Indicates Addl. Adj. Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PAYMNTREM

Attribute	**Description**	
Name	PAYMNTREM	
Datatype	String	
Description	Indicates Payment Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYEQVTTOTPAID

Attribute	**Description**
Name	LCYEQVTTOTPAID
Datatype	Number
Description	Indicates Local Currency Equivalent of Total Paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LCYEQVTTOTPREPAID

Attribute	**Description**	
Name	LCYEQVTTOTPREPAID	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Amount Prepaid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LCYEQVTLIMITAMT

Attribute	**Description**	
Name	LCYEQVTLIMITAMT	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Limit Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

LCYEQVTLIQDFACEVALUE

Attribute	**Description**	
Name	LCYEQVTLIQDFACEVALUE	
Datatype	Number	
Description	Indicates Local Currency Equivalent of Liquidated Nominal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

OSBALREP

Attribute	**Description**
Name	OSBALREP
Datatype	Number
Description	Indicates O/S Bal- Rep

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SYNDNO

Attribute	Description
Name	SYNDNO
Datatype	Number
Description	Indicates Syndication Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates SubSystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CURRPMNT

Attribute	Description
Name	CURRPMNT
Datatype	Number
Description	Indicates Current Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TOTPAMNT

Attribute	Description
Name	TOTPAMNT
Datatype	Number
Description	Indicates Total Payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

Payment-Breakup

Attribute	**Description**	
Name	Payment-Breakup	
Datatype		
Description	Includes Payment Break Up details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

AMTDUE

Attribute	**Description**	
Name	AMTDUE	
Datatype	Number	
Description	Indicates Amount Due	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates Amount Paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedules details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DUEDT

Attribute	Description
Name	DUEDT

Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Payment Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance Rate details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date

Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Field details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

DENOBASIS

Attribute	Description	
Name	DENOBASIS	
Datatype	String	
Description	Indicates the Denominator basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description	Indicates the BASIS_366	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOINTPRD

Attribute	Description	
Name	NOINTPRD	
Datatype	Number	
Description	Indicates the No of Interest Period.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	Description	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax Main details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Inlcudes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates Schedule Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Inlcudes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Inlcudes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.DeleteLDSIMContract

Deletion of Deposit contract simulation

2.23.1.LD-DeleteLDSIMContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE

Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC

Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT

ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT

Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Change-Log

- FLDDESC
- OLDISVAL
- NWDISVAL

Contract-Event-Log

- MAKERID
- MAKERSTAMP
- CHECKERID
- CHECKERSTAMP
- AUTHSTAT
- CONTSTAT
- REVR_MAKERID
- REVR_MAKERSTAMP
- REVR_CHECKERID
- REVR_CHECKERSTAMP
- REVR_AUTHSTAT
- REVR_CONTSTAT

Schedule-Dates

- ESN
- DTOFCHNG
- EVNTCD

Schedule-Summ

- DUEDT
- SUBAMT
- CCYAMTDUE
- DISAMTDUE
- DISAMTSETTL
- DISADJAMT
- Schedule-Details
  - SCOMP
  - AMTDUE
  - CCYAMTDUE
  - AMTSET
  - ADJAMT
  - Amount-Settle
    - PAIDDT
    - CCYSETTL
    - LCYEQSET
    - AMTSETTL

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description

Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String

Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINE

Attribute	**Description**	
Name	LINE	
Datatype	String	
Description	Indicates Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description	Indicates Dealer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DFLT_ACC

Attribute	**Description**	
Name	DFLT_ACC	
Datatype	String	
Description	Indicates Default Settlement Credit Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description	
Name	DFLT_ACC_BRN	
Datatype	String	
Description	Indicates Default Settlement Credit Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description	
Name	DRSETLAC	
Datatype	String	
Description	Indicates Debit Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description	
Name	DRSETLACBR	
Datatype	String	
Description	Indicates Debit Settlement Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description	
Name	EXPCAT	
Datatype	String	
Description	Indicates Exposure Category	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,T,B,E</td></tr></table>

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	**Description**	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	**Description**	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	**Description**	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLOVRIND

Attribute	Description
Name	ROLLOVRIND
Datatype	String
Description	Indicates Rollover Details Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicates Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

SUBSIDYPER

Attribute	Description
Name	SUBSIDYPER
Datatype	Number
Description	Indicates Subsidy Percentage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 2 totalDigits / 4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String

Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CASCADESCHD

Attribute	**Description**	
Name	CASCADESCHD	
Datatype	String	
Description	Indicates Cascade Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VFYFUNDS

Attribute	**Description**	
Name	VFYFUNDS	
Datatype	String	
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBCKVALSCHD

Attribute	**Description**	
Name	LIQBCKVALSCHD	
Datatype	String	
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDTAXCAP

Attribute	**Description**
Name	DEDTAXCAP

Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String
Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String

Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL

Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

CHKRATECDCCY

Attribute	**Description**	
Name	CHKRATECDCCY	
Datatype	String	
Description	Indicates Rate Code Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHCCY

Attribute	**Description**	
Name	MSCHCCY	
Datatype	String	
Description	Indicates Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	**Description**	
Name	MSCHAPLYFACLTYHOLCCY	
Datatype	String	
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHAPLYCONTHOLCCY

Attribute	**Description**	
Name	MSCHAPLYCONTHOLCCY	
Datatype	String	
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

ROLLALLW

Attribute	Description	
Name	ROLLALLW	
Datatype	String	
Description	Indicates Rollover Yes : Y No : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

PRINCLIQ

Attribute	Description	
Name	PRINCLIQ	
Datatype	String	
Description	Indicates Liquidation Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String

Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT

Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description**: maxLength / 25; minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	Description	
Name	ORDER_CUST6	
Datatype	String	
Description	Country to which the ordering customer belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	Description	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	Description	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description	
Name	INSTRCDTXT1	
Datatype	String	
Description	Indicates the Instruction Code Text1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details

Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM3

Attribute	Description

Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR

Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1

Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5

Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS

Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE

Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	**Description**
Name	EVNT
Datatype	String
Description	Indicates the event.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	Description	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	Description	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	Description	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MINRATE

Attribute	Description	
Name	MINRATE	
Datatype	Number	
Description	Indicates the Minimum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

RETENOR

Attribute	Description	
Name	RETENOR	
Datatype	Number	
Description	Indicates the Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	5

TOP

BORLENIND

Attribute	Description	
Name	BORLENIND	
Datatype	String	
Description	Indicates the Borrow \ Lend Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M

TOP

RTCALCTYP

Attribute	Description	
Name	RTCALCTYP	
Datatype	String	
Description	Indicates the Interest Rate Calculation type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	Description	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description

Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	

Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R,C,D</td></tr></table>

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description

Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BRKNAM

Attribute	Description	
Name	BRKNAM	
Datatype	String	
Description	Indicates Broker name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RULEDESC

Attribute	Description	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	Description	
Name	Brokerage-Details	
Datatype		
Description	Indicates Brokerage details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	Description	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	Number	
Description	Indicates the priority of the message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	1

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description	Indicates Change Request	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

Settlement-Split-Master

Attribute	**Description**	
Name	Settlement-Split-Master	
Datatype		
Description	Includes Settlement Split Master details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	Description	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description

Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	**Description**	
Name	NO_OF_SCHD	
Datatype	Number	
Description	Indicates the No of Schedules.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

Change-Log

Attribute	**Description**	
Name	Change-Log	
Datatype		
Description	Includes Change Log details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	Description
Name	OLDISVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NWDISVAL

Attribute	Description
Name	NWDISVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Indicates Contract Event log
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String

Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description
Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description

Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description

Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates rollover type Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,T

TOP

ROLLMATTYPE

Attribute	Description	
Name	ROLLMATTYPE	
Datatype	String	
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM

Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Includes Interest basis details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.23.2.LD-DeleteLDSIMContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

Charge-Association

CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC

Charge-Liquidation

ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS

Interest-Main

INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

Contract_Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*

- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*

- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*

AMT

ROLSTENOR

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYCONFSTAT

Attribute	**Description**	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ORGL_STDT

Attribute	**Description**
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**
Name	PRCCYTYP
Datatype	String
Description	Indicate Prov Currency Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

UREF

Attribute	**Description**
Name	UREF
Datatype	String
Description	Indicate User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PCREF

Attribute	**Description**
Name	PCREF
Datatype	String
Description	Indicate PC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlement-Addl-Details

Attribute	**Description**
Name	Settlement-Addl-Details
Datatype	
Description	Include Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	Description	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates the Supplement Identification	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PYRIDFR

Attribute	Description	
Name	PYRIDFR	
Datatype	String	
Description	Indicates the Payer Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PYMTTYPE

Attribute	Description	
Name	PYMTTYPE	
Datatype	String	
Description	Indicates the Payment type	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRRES4

Attribute	Description	
Name	REPRRES4	
Datatype	String	
Description	Indicates the Repair Reason 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description	
Name	ADDIDFR	
Datatype	String	
Description	Indicates the Additional Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	**Description**	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	**Description**
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description	Indicates the Effective date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	Description	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

STDT

Attribute	Description	
Name	STDT	
Datatype	Date	
Description	Indicates the Start Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLMATDT

Attribute	**Description**	
Name	ROLLMATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ROLLNOTDAYS

Attribute	**Description**	
Name	ROLLNOTDAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ROLLICCFFROM

Attribute	**Description**	
Name	ROLLICCFFROM	
Datatype	String	
Description	Indicates ICCF Rollover Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

ROLLBY

Attribute	**Description**
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	Description	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	Description	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	Description	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.3.LD-DeleteLDSIMContractReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	Description	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	Description	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	Description	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates the Supplement Identification	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PYRIDFR

Attribute	Description	
Name	PYRIDFR	
Datatype	String	
Description	Indicates the Payer Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PYMTTYPE

Attribute	Description	
Name	PYMTTYPE	
Datatype	String	
Description	Indicates the Payment type	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	**Description**	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	**Description**
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description	Indicates the Effective date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,I,T</td></tr></table>

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.23.4.LD-DeleteLDSIMContractRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
- *Advice-Details*
  - *MSGTYPE*
  - *PARTYID*
  - *MEDIUM*
  - *SUPPRESS*
  - *PRIORITY*
  - *CHGREQ*
- *Settlement-Split-Master*
  - *SNO*
  - *SPAMTTG*
  - *AMT*
  - *BRN*
  - *ACCCY*
  - *ACC*
  - *EXRATE*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description

Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

AMTINRPTCCY

Attribute	**Description**	
Name	AMTINRPTCCY	
Datatype	String	
Description	Indicates Amount in Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RPTCCY

Attribute	**Description**	
Name	RPTCCY	
Datatype	String	
Description	Indicates Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

OSBALRPTCCY

Attribute	**Description**	
Name	OSBALRPTCCY	
Datatype	String	
Description	Indicates Outstanding Balance in Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

IGRHOLDYS

Attribute	**Description**
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	Description	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	Description	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	Description	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	Description	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**	
Name	INTDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 5 totalDigits: 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxInclusive: 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.DeleteProduct

Deletion of Loans and Deposit Product

2.24.1.LD-DeleteProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*

ACCRSTRTMNTH
ACCRSTRTDT
COLCTDRNGAMNDT
MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ

TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*

- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*
- *MORATRMPERD*

Liquidation-Order

- *CMPNT*
- *LIQORDR*

Grace-Levels

- *LVLNO*
- *NOOFUNITS*
- *UNIT*

Ccy-Days-Details

- *CCY*
- *EXCRATFXNGDAYS*
- *INTRATFXNGDAYS*

Trs-Components-Details

- *COMPNT*

Status-Master-Details

- *STATUS*
- *TRANSACTIONCD*
- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *COMPLETEACCRUALS*
- *TRNSFRCAPITLIZDINCM*
- *AUTOFRWD*
- *AUTOREVERSE*
- *DERVTNRUL*
- *RBKPROVSN*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*
  - *GLDESC*
  - *TRNSFERGL*
  - *DWNWRDTRANSFERFRMGL*
  - *DWNWRDTRANSFERTOGL*
- *Acc-Status-Gl-Details*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Tax-Scheme

- SCHME
- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
  - Ccy-Tax-Details
    - CCY
    - MAXTAXINTPERD
    - PERDUNIT
    - MININTTAXAMT
- Product-Interest
  - Interest-Components
    - BASISAMNTTYP
    - BASISAMNTCATG
    - RATCDUSGE
    - RATTYP
    - RATCD
    - SETTLMNTCCY
    - STPAPPLICTION
    - RESETTENOR
    - BRWLENDIND
    - LVLNO
    - PREPMTMETD
    - PROPREQD
    - MARGNBASIS
    - MARGNAPPLN
    - RATECALCTYP
    - ACQREQD
    - CHNGDRGAMNDMNT
    - SHWNINCNTRTMAINSCR
    - BLKAMTFLG
    - DEPORATECD
    - DISCACCRAPP
    - UNIT
    - NOUNIT
    - EVNT
    - COMPNENT
    - COMPNENTDESC
    - RUL
    - COLTYP
    - EVNTDESC

- *RULEDESC*
- *Interest-Ccy-Preferences*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *DFLTSPRD*
  - *MINSPRD*
  - *MAXSPRD*
  - *INTBASIS*
  - *DENOMBASIS*
  - *BAS366*
  - *NOOFINTPRD*
  - *PRPMTRT*
- *Product-Accrual-Fee*
  - *Accrual-Fee-Details*
    - *LIQINT*
    - *LIQPRNCHNG*
    - *DISCACCRAPP*
    - *ACCRREQD*
    - *BASISAMT*
    - *ENDDTINP*
    - *RULFEE*
    - *FEETYP*
    - *ACCRFREQ*
    - *FREQVAL*
    - *COMP*
    - *STPASSN*
    - *COMPNENTDESC*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*
    - *SWIFTQLF*
    - *SETTCCY*
    - *DFTWAIV*
    - *ALWRULAMND*
    - *AMNDAFTRASSOC*
    - *ALWAMTAMND*
    - *AMNDAFTRAPPL*
    - *STPASOCIATN*

- ADVCHG
- CAPTLIZE
- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences

CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Deletion details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description
Name	PROD_TYPE_DESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,M</td></tr></table>

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String

Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String
Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description

Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String
Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description	
Name	VRFY_DRWDNAMT	
Datatype	String	
Description	Indicates Verify Drawdown Amount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAXNOOFLNS

Attribute	Description	
Name	MAXNOOFLNS	
Datatype	Number	
Description	Indicates Maximum Number of Loans	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNPRD

Attribute	Description	
Name	LNPRD	
Datatype	String	
Description	Indicates Loan Product	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description	
Name	ALLWSCHEAMNDAFTRSGEN	
Datatype	String	
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates Statement Generation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DMNDBASIS

Attribute	Description
Name	DMNDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B,

TOP

AUTOACC

Attribute	Description
Name	AUTOACC
Datatype	String
Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number

Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String

Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String

Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN
Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String

Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Product Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEDCTTAXONRLOVR

Attribute	Description
Name	DEDCTTAXONRLOVR
Datatype	String
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMANRLOVR

Attribute	Description
Name	AUTOMANRLOVR
Datatype	String
Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String

Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	

Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Status-Advices-Details

Attribute	**Description**	
Name	Status-Advices-Details	
Datatype		
Description	Includes Status Advices detail	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MESSAGECD

Attribute	**Description**	
Name	MESSAGECD	
Datatype	String	
Description	Indicates Message of Status Advices	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Product-Status-Gl-Details

Attribute	**Description**	
Name	Product-Status-Gl-Details	
Datatype		
Description	Includes Product Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCNTROLE

Attribute	**Description**	
Name	ACCNTROLE	
Datatype	String	
Description	Indicates Accounting Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

UPWARDTRANFERFRMGL

Attribute	Description	
Name	UPWARDTRANFERFRMGL	
Datatype	String	
Description	Indicates Upward From GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TRNSFERGL

Attribute	Description	
Name	TRNSFERGL	
Datatype	String	
Description	Indicates Accounting Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description	
Name	DWNWRDTRANSFERFRMGL	
Datatype	String	
Description	Indicates Downward Movement FROM GL Account Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String

Description	Indicates Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description

Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PERDUNIT

Attribute	**Description**	
Name	PERDUNIT	
Datatype	String	
Description	Indicates Period Unit Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

MININTTAXAMT

Attribute	**Description**	
Name	MININTTAXAMT	
Datatype	Number	
Description	Indicates Minimum Interest Amount for Tax	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Product-Interest

Attribute	**Description**	
Name	Product-Interest	
Datatype		
Description	Includes Product Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Interest-Components

Attribute	**Description**	
Name	Interest-Components	
Datatype		
Description	Includes Interest Components details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description

Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description

Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

EVNTDESC

Attribute	**Description**	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Interest-Ccy-Preferences

Attribute	**Description**	
Name	Interest-Ccy-Preferences	
Datatype		
Description	Includes Interest Currency preferences details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQPRNCHNG

Attribute	**Description**	
Name	LIQPRNCHNG	
Datatype	String	
Description	Indicates Increase In Principal Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BASISAMT

Attribute	**Description**
Name	BASISAMT
Datatype	String

Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description

Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description

Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DRCRTYPE

Attribute	**Description**	
Name	DRCRTYPE	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

NTCNSINDI

Attribute	**Description**	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	**Description**	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	**Description**
Name	SWIFTQLF

Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD

Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description

Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes Product Customer Restriction details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details

Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET

Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.24.2.LD-DeleteProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Deletion-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.24.3.LD-DeleteProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*
    - *ACCRSTRTMNTH*
    - *ACCRSTRTDT*
    - *COLCTDRNGAMNDT*

MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO

TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*
- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*

- *MORATRMPERD*
- *Liquidation-Order*
  - *CMPNT*
  - *LIQORDR*
- *Grace-Levels*
  - *LVLNO*
  - *NOOFUNITS*
  - *UNIT*
- *Ccy-Days-Details*
  - *CCY*
  - *EXCRATFXNGDAYS*
  - *INTRATFXNGDAYS*
- *Trs-Components-Details*
  - *COMPNT*
- *Status-Master-Details*
  - *STATUS*
  - *TRANSACTIONCD*
  - *STATUSSEQ*
  - *STPACCRUALS*
  - *REVERSEACCRUALS*
  - *COMPLETEACCRUALS*
  - *TRNSFRCAPITLIZDINCM*
  - *AUTOFRWD*
  - *AUTOREVERSE*
  - *DERVTNRUL*
  - *RBKPROVSN*
  - *Status-Advices-Details*
    - *MESSAGECD*
  - *Product-Status-Gl-Details*
    - *ACCNTROLE*
    - *UPWARDTRANFERFRMGL*
    - *GLDESC*
    - *TRNSFERGL*
    - *DWNWRDTRANSFERFRMGL*
    - *DWNWRDTRANSFERTOGL*
  - *Acc-Status-Gl-Details*
    - *ACCROL*
    - *ROLDESC*
    - *ACCHD*
    - *GLDESC*
- *Tax-Scheme*
  - *SCHME*
  - *SCHEMEDESC*
  - *Tax-Details*

RUL
AMNTTAG
BASISAMNTTAG
COMPTATIONEVNT
TYP
Ccy-Tax-Details
CCY
MAXTAXINTPERD
PERDUNIT
MININTTAXAMT
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY

DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
Product-Accrual-Fee
Accrual-Fee-Details
LIQINT
LIQPRNCHNG
DISCACCRAPP
ACCRREQD
BASISAMT
ENDDTINP
RULFEE
FEETYP
ACCRFREQ
FREQVAL
COMP
STPASSN
COMPNENTDESC
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY
DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB

- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR
    - CHGREQD

Role-To-Head-Mapping

- CLASCD

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Discount-Accrual*
  - *CLASCD*
  - *CLASDESC*
  - *CLSDFLT*
  - *Disc-Accr-Details*
    - *DISCACCRREQD*
    - *ACCRFREQ*
    - *PREPAYTBDTREAT*
    - *ACQTYP*
  - *Ccy-Preferences*
    - *CCYCODE*
    - *CCYNAME*
    - *DENOMDCNTMET*

DENOMMETHOD

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISCLS

MISCD

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Deletion details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP

Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description
Name	PROD_TYPE_DESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String

Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String

Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description

Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number

Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String

Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description

Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String

Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXNOOFLNS

Attribute	Description
Name	MAXNOOFLNS
Datatype	Number
Description	Indicates Maximum Number of Loans
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	**Description**	
Name	SGENREQD	
Datatype	String	
Description	Indicates Statement Generation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTCREQD

Attribute	**Description**	
Name	NOTCREQD	
Datatype	String	
Description	Indicates Whether Notice is Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DMNDBASIS

Attribute	**Description**	
Name	DMNDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,B,

TOP

AUTOACC

Attribute	**Description**
Name	AUTOACC
Datatype	String

Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number
Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN

Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String
Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTNRATTYP

Attribute	**Description**	
Name	REVALTNRATTYP	
Datatype	String	
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates Checker ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Product Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Auth Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDCTTAXONRLOVR

Attribute	Description	
Name	DEDCTTAXONRLOVR	
Datatype	String	
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMANRLOVR

Attribute	Description	
Name	AUTOMANRLOVR	
Datatype	String	
Description	Indicates Rollover Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

RLOVRMECHNSM

Attribute	Description	
Name	RLOVRMECHNSM	
Datatype	String	
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description

Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number

Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Status-Master-Details

Attribute	Description	
Name	Status-Master-Details	
Datatype		
Description	Includes Status control Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TRANSACTIONCD

Attribute	Description	
Name	TRANSACTIONCD	
Datatype	String	
Description	Indicates Transaction code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STATUSSEQ

Attribute	Description

Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String

Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN

Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description	
Name	DWNWRDTRANSFERTOGL	
Datatype	String	
Description	Indicates Downward Movement To GL Account Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Acc-Status-Gl-Details

Attribute	Description	
Name	Acc-Status-Gl-Details	
Datatype		
Description	Includes Account Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCROL

Attribute	Description	
Name	ACCROL	
Datatype	String	
Description	Indicates Account Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCHD

Attribute	Description

Name	ACCHD
Datatype	String
Description	Indicates Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,M,Y,</td></tr></table>

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String

Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR

Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**	
Name	MARGNAPPLN	
Datatype	String	
Description	Indicates Margin Application Periodic : P Automatic : A None : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,A,N

TOP

RATECALCTYP

Attribute	**Description**	
Name	RATECALCTYP	
Datatype	String	
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNT

Attribute	**Description**	
Name	EVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COMPNENT

Attribute	**Description**	
Name	COMPNENT	
Datatype	String	
Description	Indicates Component	
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description

Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description

Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String

Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQPRNCHNG

Attribute	Description
Name	LIQPRNCHNG
Datatype	String
Description	Indicates Increase In Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTAPPLIDESC

Attribute	**Description**	
Name	EVNTAPPLIDESC	
Datatype	String	
Description	Indicates Event Application Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULDESC

Attribute	Description	
Name	RULDESC	
Datatype	String	
Description	Indicates rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Includes Product Events details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description	
Name	ACCRLCD	
Datatype	String	
Description	Indicates the Role code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes Product Customer Restriction details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description	Includes Branch Currency Restrictions details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CLSDFLT

Attribute	**Description**	
Name	CLSDFLT	
Datatype	String	
Description	Indicates Class Default	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description

Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.4.LD-DeleteProduct-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Product-Details-PK*
    - *PRDCD*
  - *Product-Details-IO*
    - *PRDCD*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Indicates Loans and Deposit Product Deletion-PK details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Deletion-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.25.LDActivateSimulate

Simulation of Active Deposit simulation

2.25.1.LD-LDActivateSimulate-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description

Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String

Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINE

Attribute	**Description**	
Name	LINE	
Datatype	String	
Description	Indicates Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description	Indicates Dealer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DFLT_ACC

Attribute	**Description**	
Name	DFLT_ACC	
Datatype	String	
Description	Indicates Default Settlement Credit Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	**Description**	
Name	DFLT_ACC_BRN	
Datatype	String	
Description	Indicates Default Settlement Credit Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	**Description**	
Name	DRSETLAC	
Datatype	String	
Description	Indicates Debit Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	**Description**	
Name	DRSETLACBR	
Datatype	String	
Description	Indicates Debit Settlement Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	**Description**	
Name	EXPCAT	
Datatype	String	
Description	Indicates Exposure Category	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INTPERBAS

Attribute	Description	
Name	INTPERBAS	
Datatype	String	
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

INTREFNO

Attribute	Description	
Name	INTREFNO	
Datatype	String	
Description	Indicates External Interface Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LASTAVLDT

Attribute	Description	
Name	LASTAVLDT	
Datatype	Date	
Description	Indicates Last Available Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYEQINDLN

Attribute	Description	
Name	LCYEQINDLN	
Datatype	Number	
Description	Indicates Local Currency Equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,Q,M,F,W,D</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	**Description**	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	**Description**	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	**Description**	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLOVRIND

Attribute	Description
Name	ROLLOVRIND
Datatype	String
Description	Indicates Rollover Details Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicates Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

SUBSIDYPER

Attribute	Description
Name	SUBSIDYPER
Datatype	Number
Description	Indicates Subsidy Percentage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 2 totalDigits / 4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4; minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String

Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RPTCCY

Attribute	**Description**	
Name	RPTCCY	
Datatype	String	
Description	Indicates Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

OSBALRPTCCY

Attribute	**Description**	
Name	OSBALRPTCCY	
Datatype	String	
Description	Indicates Outstanding Balance in Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

IGRHOLDYS

Attribute	**Description**	
Name	IGRHOLDYS	
Datatype	String	
Description	Indicates Ignore Holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOLDYCCY

Attribute	**Description**
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description
Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP

Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String
Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String

Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL

Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

CHKRATECDCCY

Attribute	**Description**	
Name	CHKRATECDCCY	
Datatype	String	
Description	Indicates Rate Code Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHCCY

Attribute	**Description**	
Name	MSCHCCY	
Datatype	String	
Description	Indicates Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	**Description**	
Name	MSCHAPLYFACLTYHOLCCY	
Datatype	String	
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHAPLYCONTHOLCCY

Attribute	**Description**	
Name	MSCHAPLYCONTHOLCCY	
Datatype	String	
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String

Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT

Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	Description	
Name	ORDER_CUST6	
Datatype	String	
Description	Country to which the ordering customer belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	Description	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	Description	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	**Description**	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details

Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM3

Attribute	Description

Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR

Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1

Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5

Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	Description	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	Description	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	Description	
Name	PERIOD	
Datatype	String	
Description	Indicates Period	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

FINYR

Attribute	Description	
Name	FINYR	
Datatype	String	
Description	Indicates Financial Year	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS

Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE

Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	**Description**
Name	EVNT
Datatype	String
Description	Indicates the event.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description

Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	

Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R,C,D</td></tr></table>

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	Description	
Name	LCYEQINDLN	
Datatype	Number	
Description	Indicates Local Currency Equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

STDT

Attribute	Description	
Name	STDT	
Datatype	Date	
Description	Indicates the Start Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	Description

Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description	
Name	BRKNAM	
Datatype	String	
Description	Indicates Broker name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RULEDESC

Attribute	Description	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	Description	
Name	Brokerage-Details	
Datatype		
Description	Indicates Brokerage details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	Description	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description

Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	**Description**	
Name	NO_OF_SCHD	
Datatype	Number	
Description	Indicates the No of Schedules.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

Change-Log

Attribute	**Description**	
Name	Change-Log	
Datatype		
Description	Includes Change Log details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	Description
Name	OLDISVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NWDISVAL

Attribute	Description
Name	NWDISVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Indicates Contract Event log
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String

Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description
Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description

Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description

Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates rollover type Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,T

TOP

ROLLMATTYPE

Attribute	Description	
Name	ROLLMATTYPE	
Datatype	String	
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM

Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Includes Interest basis details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.25.2.LD-LDActivateSimulate-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Balance-Trnsfer-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*
- *PERIOD*
- *FINYR*
- *GLCODE*
- *CCY*
- *AMT*
- *EXRATE*

Mis-Change-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*

Mis-Amend

- *CONTREF*
- *RTYPE*
- *RCODE*
- *SPD*

Refinance-Rate

- *UNITREF*
- *BKDATE*
- *EFFDT*
- *REFRT*

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*

- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*

- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*

AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYCONFSTAT

Attribute	**Description**	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ORGL_STDT

Attribute	**Description**
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description	
Name	LIQODSCH	
Datatype	String	
Description	Indicate Liquidate Od Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LNSTMTCYC

Attribute	Description	
Name	LNSTMTCYC	
Datatype	String	
Description	Indicate Loan Statement Cycle	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicate loan statement type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MVACRMTH

Attribute	Description	
Name	MVACRMTH	
Datatype	String	
Description	Indicate Move Across Months Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicate Prov Currency Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicate User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PCREF

Attribute	Description
Name	PCREF
Datatype	String
Description	Indicate PC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Include Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRRES4

Attribute	Description	
Name	REPRRES4	
Datatype	String	
Description	Indicates the Repair Reason 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description	
Name	ADDIDFR	
Datatype	String	
Description	Indicates the Additional Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	**Description**	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	**Description**
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description	Indicates the Effective date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,I,T</td></tr></table>

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.3.LD-LDActivateSimulateReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRNDT

Attribute	**Description**	
Name	TRNDT	
Datatype	Date	
Description	Indicate Transfer Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicate value date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAT_TYPE

Attribute	**Description**	
Name	MAT_TYPE	
Datatype	String	
Description	Indicate maturity type C Call N Notice F Fixed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

NOTC_DAYS

Attribute	**Description**	
Name	NOTC_DAYS	
Datatype	String	
Description	Indicate Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	**Description**	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	**Description**
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description	Indicates the Effective date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**	
Name	INTCMPDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicate value date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	Description	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

STDT

Attribute	Description	
Name	STDT	
Datatype	Date	
Description	Indicates the Start Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	1

TOP

LINK_SRNO

Attribute	Description	
Name	LINK_SRNO	
Datatype	String	
Description	Indicates the Link-serial Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the amount block number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKEFFDT

Attribute	Description	
Name	LINKEFFDT	
Datatype	String	
Description	Indicates the link effective date.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description	
Name	CONVPAIDAMT	
Datatype	String	
Description	Indicates the converted amount paid.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.25.4.LD-LDActivateSimulateRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
- *Advice-Details*
  - *MSGTYPE*
  - *PARTYID*
  - *MEDIUM*
  - *SUPPRESS*
  - *PRIORITY*
  - *CHGREQ*
- *Settlement-Split-Master*
  - *SNO*
  - *SPAMTTG*
  - *AMT*
  - *BRN*
  - *ACCCY*
  - *ACC*
  - *EXRATE*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

- CCYDESC
- Contract-Rollover
  - ROLLAMT
  - ROLLMATDT
  - ROLLNOTDAYS
  - UPDATEUTIL
  - LIQDODSCHD
  - DRAWDOWNNO
  - ROLLBY
  - ROLLINTST
  - ROLLMECH
  - ROLLMETHD
  - ROLLTYPE
  - ROLLAMTTYP
  - ROLLMATTYPE
  - ROLLICCFFROM
  - SCHDBASIS
  - TRESPLAMT
  - APPROLLTAX
  - NEWCOMPALL
  - ROLLMATDAYS
  - APPCHG
  - REFRATE
  - Rvrintrates
    - INTCOMP
    - DEFFROM
    - RATETYPE
    - INTBASIS
  - INTBAS
    - INTCOMP
    - ROLLOIFROM
    - RATETYPE
    - RATEUSCD
    - INTRATE
    - INTBASIS
    - RATECD
    - SPREAD
    - MARGIN
    - AMT
    - ROLSTENOR
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description

Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Counterparty	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINE

Attribute	Description	
Name	LINE	
Datatype	String	
Description	Indicates Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

DEALER

Attribute	Description	
Name	DEALER	
Datatype	String	
Description	Indicates Dealer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTC_DAYS

Attribute	Description	
Name	NOTC_DAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	Description	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	Description	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String
Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Specifies The MIS Group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	**Description**	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLMETHD

Attribute	Description	
Name	ROLLMETHD	
Datatype	String	
Description	Indicates Rollover Method	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates rollover type Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.LDInactivateSimulate

Simulation of InactiveActive Deposit simulation

2.26.1.LD-LDInactivateSimulate-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE

Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC

Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT

ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT

Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Change-Log

- FLDDESC
- OLDISVAL
- NWDISVAL

Contract-Event-Log

- MAKERID
- MAKERSTAMP
- CHECKERID
- CHECKERSTAMP
- AUTHSTAT
- CONTSTAT
- REVR_MAKERID
- REVR_MAKERSTAMP
- REVR_CHECKERID
- REVR_CHECKERSTAMP
- REVR_AUTHSTAT
- REVR_CONTSTAT

Schedule-Dates

- ESN
- DTOFCHNG
- EVNTCD

Schedule-Summ

- DUEDT
- SUBAMT
- CCYAMTDUE
- DISAMTDUE
- DISAMTSETTL
- DISADJAMT
- Schedule-Details
  - SCOMP
  - AMTDUE
  - CCYAMTDUE
  - AMTSET
  - ADJAMT
  - Amount-Settle
    - PAIDDT
    - CCYSETTL
    - LCYEQSET
    - AMTSETTL

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description

Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String

Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINE

Attribute	**Description**	
Name	LINE	
Datatype	String	
Description	Indicates Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description	Indicates Dealer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DFLT_ACC

Attribute	**Description**	
Name	DFLT_ACC	
Datatype	String	
Description	Indicates Default Settlement Credit Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description	
Name	DFLT_ACC_BRN	
Datatype	String	
Description	Indicates Default Settlement Credit Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description	
Name	DRSETLAC	
Datatype	String	
Description	Indicates Debit Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description	
Name	DRSETLACBR	
Datatype	String	
Description	Indicates Debit Settlement Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description	
Name	EXPCAT	
Datatype	String	
Description	Indicates Exposure Category	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,Q,M,F,W,D</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	**Description**	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	**Description**	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	**Description**	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLOVRIND

Attribute	Description
Name	ROLLOVRIND
Datatype	String
Description	Indicates Rollover Details Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicates Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

SUBSIDYPER

Attribute	Description
Name	SUBSIDYPER
Datatype	Number
Description	Indicates Subsidy Percentage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 2 totalDigits / 4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String

Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description
Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP

Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description	
Name	VERIFUND	
Datatype	String	
Description	Indicates Verify Funds	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PARTPAYMLIQ

Attribute	Description	
Name	PARTPAYMLIQ	
Datatype	String	
Description	Indicates Partial Manual Liquidation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

SUBSALLOW

Attribute	Description	
Name	SUBSALLOW	
Datatype	String	
Description	Indicates Subsidy Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

USERDEFSCHED

Attribute	Description	
Name	USERDEFSCHED	
Datatype	String	
Description	Indicates User Defined Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String
Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String

Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL

Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

CHKRATECDCCY

Attribute	**Description**	
Name	CHKRATECDCCY	
Datatype	String	
Description	Indicates Rate Code Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHCCY

Attribute	**Description**	
Name	MSCHCCY	
Datatype	String	
Description	Indicates Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	**Description**	
Name	MSCHAPLYFACLTYHOLCCY	
Datatype	String	
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHAPLYCONTHOLCCY

Attribute	**Description**	
Name	MSCHAPLYCONTHOLCCY	
Datatype	String	
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

ROLLALLW

Attribute	Description	
Name	ROLLALLW	
Datatype	String	
Description	Indicates Rollover Yes : Y No : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

PRINCLIQ

Attribute	Description	
Name	PRINCLIQ	
Datatype	String	
Description	Indicates Liquidation Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String

Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT

Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details

Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM3

Attribute	Description

Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR

Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1

Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5

Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**
	maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**
	maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description**
	maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description**
	maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS

Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE

Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	**Description**
Name	EVNT
Datatype	String
Description	Indicates the event.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	Description	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	Description	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MINRATE

Attribute	Description	
Name	MINRATE	
Datatype	Number	
Description	Indicates the Minimum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description

Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	

Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R,C,D</td></tr></table>

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	Description	
Name	LCYEQINDLN	
Datatype	Number	
Description	Indicates Local Currency Equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

STDT

Attribute	Description	
Name	STDT	
Datatype	Date	
Description	Indicates the Start Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	Description

Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description	
Name	BRKNAM	
Datatype	String	
Description	Indicates Broker name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RULEDESC

Attribute	Description	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	Description	
Name	Brokerage-Details	
Datatype		
Description	Indicates Brokerage details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	Description	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	Number	
Description	Indicates the priority of the message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	1

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description	Indicates Change Request	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

Settlement-Split-Master

Attribute	**Description**	
Name	Settlement-Split-Master	
Datatype		
Description	Includes Settlement Split Master details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description

Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	**Description**	
Name	NO_OF_SCHD	
Datatype	Number	
Description	Indicates the No of Schedules.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

Change-Log

Attribute	**Description**	
Name	Change-Log	
Datatype		
Description	Includes Change Log details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	Description
Name	OLDISVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NWDISVAL

Attribute	Description
Name	NWDISVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Indicates Contract Event log
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String

Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String
Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description
Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description

Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description

Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates rollover type Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,T

TOP

ROLLMATTYPE

Attribute	Description	
Name	ROLLMATTYPE	
Datatype	String	
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM

Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Includes Interest basis details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.26.2.LD-LDInactivateSimulate-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Balance-Trnsfer-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*
- *PERIOD*
- *FINYR*
- *GLCODE*
- *CCY*
- *AMT*
- *EXRATE*

Mis-Change-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*

Mis-Amend

- *CONTREF*
- *RTYPE*
- *RCODE*
- *SPD*

Refinance-Rate

- *UNITREF*
- *BKDATE*
- *EFFDT*
- *REFRT*

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

Contract_Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*

- STDT
- NO_OF_SCHD
- AMT

Contract_Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Holiday-Currencies

- CCY
- CCYDESC

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY
  - BKMTHD
  - BOOKAMT
  - LIQSTAT
  - LREFNO

Advice-Details

- MSGTYPE

- PARTYID
- MEDIUM
- SUPPRESS
- PRIORITY
- CHGREQ

Settlement-Split-Master

- SNO
- SPAMTTG
- AMT
- BRN
- ACCCY
- ACC
- EXRATE

Contract-Rollover

- ROLLTYPE
- ROLLAMTTYP
- ROLLAMT
- LIQDODSCHD
- SCHDBASIS
- UPDATEUTIL
- ROLLMATTYPE
- ROLLMATDT
- ROLLNOTDAYS
- ROLLICCFFROM
- ROLLBY
- APPCHG
- APPROLLTAX
- TRESPLAMT
- REFRATE
- ROLLMATDAYS
- ROLLMECH
- ROLLMETHD
- DRAWDOWNNO
- NEWCOMPALL
- INTBAS
  - INTCOMP
  - ROLLOIFROM
  - RATETYPE
  - RATEUSCD
  - INTRATE
  - INTBASIS
  - RATECD
  - SPREAD
  - MARGIN

AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYCONFSTAT

Attribute	**Description**	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ORGL_STDT

Attribute	**Description**
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	Description	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	Description	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	Description	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.3.LD-LDInactivateSimulateReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	Description	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	Description	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	Description	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	Description	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	Description

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates the Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.26.4.LD-LDInactivateSimulateRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description

Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTC_DAYS

Attribute	Description	
Name	NOTC_DAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	Description	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	Description	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String
Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	Description	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	Description	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Specifies The MIS Group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	**Description**	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	**Description**	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	**Description**

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	12
totalDigits	24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.LDVamiCreateSim

Creation of deposit vami simulation

2.27.1.LD-LDVamiCreateSim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*

VALDT
PRD
PROTYPEDESC
LATVERNO
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*

CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4

RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3

INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1

REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6

COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Interest-Main

- *INTCOMP*
- *VALDT*
- *TXNDT*
- *INTAMT*
- *CHDAMDMNT*
- *INTCCY*
- *EVNT*
- *ESN*
- *PKUPEVSQ*
- *INTBASIS*
- *INTRATE*
- *INTRATECODE*
- *INTSPREAD*

- *AQRDAMT*
- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*

Taxrule-Detail

ESN

TAXAMT

TAXCCY

VALDT

COMPDT

Contract-Schedules

SCOMP

SCHD_TYPE

FREQ

FREQ_UNIT

LCYEQINDLN

STDT

NO_OF_SCHD

AMT

Contract-Linkages

LINK_REF

LINK_TYPE

LINK_CCY

LINK_AMT

XRATE

AVLAMT

CONV_LINK_AMT

LOAN_CCY

LINKBRANCH

LINKVALID

LINK_SRNO

AMTBLKNO

LINKEFFDT

CONVPAIDAMT

Relationship-Linkage

DESCP

CUSTOMER

RELATIONSHIP

INHERIT

Brokerage-Master

FCCREF

ESN

BROKER

BRKAMT

BRKCCY

RULE

DSCACR

BRKNAM

- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Amountdue

- *FCCREF*
- *COMP*
- *DUEDT*
- *AMTDUE*
- *AMTSTD*
- *ADJAMT*

Change-Log

- *FCCREF*
- *FLDDESC*
- *OLDDISPVAL*
- *NEWDISPVAL*

Overrides

- *FCCREF*
- *OVDSN*
- *MODULE*
- *ERRCODE*
- *PARAM*
- *ONLAUTHID*
- *REMARKS*
- *AUTHBY*
- *AUTHDTSTAMP*

TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NAME

Attribute	Description

Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date

Description	Indicate Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PROTYPEDESC

Attribute	Description	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates the ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates the ERI currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST6

Attribute	**Description**	
Name	ACC_INST6	
Datatype	String	
Description	Country to which the AWI belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AGRID

Attribute	**Description**	
Name	AGRID	
Datatype	String	
Description	Indicates Agreement Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

BNKPRIO

Attribute	**Description**
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

BNFINSTCVR1

Attribute	**Description**	
Name	BNFINSTCVR1	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	**Description**	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	Description	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	Description	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	**Description**
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	**Description**
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	**Description**
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	**Description**

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>0,1,2,3,4,5,6,7,8,9,-1,-2</td></tr></table>

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,M,Y</td></tr></table>

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>5</td></tr></table>

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,P</td></tr></table>

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicate value date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Include Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement Split Master details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicate amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.27.2.LD-LDVamiCreateSim-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-Pk*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *EVNT*
      - *EVNTDT*
      - *MAKERID*
      - *AMT*
      - *MATDT*
      - *VALDT*
      - *Settlement-Addl-Details*
        - *ACCBRN*
        - *ACC_CCY*
        - *ACC*
        - *AMTTAG*
        - *CUSTSPRD*

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*
- *COSTCOD1*

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*

- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*

EXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-Pk

Attribute	Description
Name	Contract-Master-Pk
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicates the Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT

Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM4

Attribute	Description	
Name	RCVR_CUSNM4	
Datatype	String	
Description	Indicates the Receiver Name 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description	
Name	SNDR_ACC	
Datatype	String	
Description	Indicates the Sender Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

RCVR_ACC

Attribute	Description	
Name	RCVR_ACC	
Datatype	String	
Description	Indicates the Receiver Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Indicates MIS Amendment Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE

Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description

Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,M,Y</td></tr></table>

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>5</td></tr></table>

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,P</td></tr></table>

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOBASIS

Attribute	Description	
Name	DENOBASIS	
Datatype	String	
Description	Indicates the Denominator basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description	Indicates the BASIS_366	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOINTPRD

Attribute	Description	
Name	NOINTPRD	
Datatype	Number	
Description	Indicates the No of Interest Period.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	Description	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Indicates Tax Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Indicates Contract Schedules Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT

Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description

Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC

Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.3.LD-LDVamiCreateSimReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *MATDT*
    - *VALDT*
    - *Settlement-Addl-Details*
      - *ACCBRN*
      - *ACC_CCY*
      - *ACC*
      - *AMTTAG*
      - *CUSTSPRD*
      - *ERIAMT*
      - *ERICCY*
      - *XRATE*
      - *GENMSG*

NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF

ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2

- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*
- *COSTCOD1*
- *COSTCOD2*
- *COSTCOD3*
- *COSTCOD4*
- *COSTCOD5*

LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*
- *PERIOD*
- *FINYR*
- *GLCODE*
- *CCY*
- *AMT*
- *EXRATE*

Mis-Change-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*

Mis-Amend

- *CONTREF*
- *RTYPE*
- *RCODE*
- *SPD*

Refinance-Rate

- *UNITREF*
- *BKDATE*
- *EFFDT*
- *REFRT*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*

LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC

- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*

LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT
CONVPAIDAMT
Relationship-Linkage
DESCP
CUSTOMER
RELATIONSHIP
INHERIT
Brokerage-Master
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicates the Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	

Restrictions	Description
maxLength	3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	

Restrictions	Description
maxLength	3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	

Restrictions	Description
maxLength	15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	

Restrictions	Description
maxLength	20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description

Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description	
Name	CALCMETH	
Datatype	Number	
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS8LBL8

Attribute	Description	
Name	TXNMIS8LBL8	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Indicates MIS Amendment Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String

Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	**Description**	
Name	LQDSTS	
Datatype	String	
Description	Indicates the Liquidation Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Interest-Main

Attribute	**Description**	
Name	Interest-Main	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>totalDigits</td><td>10</td></tr></table>

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Indicates Tax Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Contract-Schedules

Attribute	Description	
Name	Contract-Schedules	
Datatype		
Description	Indicates Contract Schedules Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCOMP

Attribute	Description	
Name	SCOMP	
Datatype	String	
Description	Indicates the component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	Description	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	Description

Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

2.27.4.LD-LDVamiCreateSimRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*
    - *VALDT*
    - *PRD*
    - *PROTYPEDESC*

LATVERNO

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*
  - *XPTACC*

XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER

RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4

- *CDFDOC*
- *ADDIDFR*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9

COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD

- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*

- TAXCCY
- VALDT
- COMPDT

Contract-Schedules

- SCOMP
- SCHD_TYPE
- FREQ
- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Contract-Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY

BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
Amountdue
FCCREF
COMP
DUEDT
AMTDUE
AMTSTD
ADJAMT
Change-Log
FCCREF
FLDDESC
OLDDISPVAL
NEWDISPVAL
Overrides
FCCREF
OVDSN
MODULE
ERRCODE
PARAM
ONLAUTHID
REMARKS
AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED

OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROTYPEDESC

Attribute	**Description**	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	

Restrictions	Description
maxLength	3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	

Restrictions	Description
maxLength	3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	

Restrictions	Description
maxLength	15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	

Restrictions	Description
maxLength	20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Mis-Amend

Attribute	**Description**	
Name	Mis-Amend	
Datatype		
Description	Include MIS amend Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONTREF

Attribute	**Description**
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates the Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Include Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>14</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	**Description**	
Name	RELATIONSHIP	
Datatype	String	
Description	Relation element, It can be of alpha numerical with special characters.	
Restrictions	**Restrictions**	**Description**
	maxLength	10
	pattern	[a-zA-Z0-9]*

TOP

INHERIT

Attribute	**Description**	
Name	INHERIT	
Datatype	String	
Description	Indicates the Include Relationship.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Brokerage-Master

Attribute	**Description**	
Name	Brokerage-Master	
Datatype		
Description	Include Brokerage Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates flexcube Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.LDVamiDeleteSim

Deletion of Deposit Vami simulation

2.28.1.LD-LDVamiDeleteSim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*

VALDT
PRD
PROTYPEDESC
LATVERNO
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*

CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4

RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3

INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1

REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6

COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Interest-Main

- *INTCOMP*
- *VALDT*
- *TXNDT*
- *INTAMT*
- *CHDAMDMNT*
- *INTCCY*
- *EVNT*
- *ESN*
- *PKUPEVSQ*
- *INTBASIS*
- *INTRATE*
- *INTRATECODE*
- *INTSPREAD*

- *AQRDAMT*
- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*

- *Taxrule-Detail*
  - *ESN*
  - *TAXAMT*
  - *TAXCCY*
  - *VALDT*
  - *COMPDT*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*
  - *LINKVALID*
  - *LINK_SRNO*
  - *AMTBLKNO*
  - *LINKEFFDT*
  - *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*

- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *Advice-Details*
  - *MSGTYPE*
  - *PARTYID*
  - *MEDIUM*
  - *SUPPRESS*
  - *PRIORITY*
  - *CHGREQ*
- *Settlement-Split-Master*
  - *SNO*
  - *SPAMTTG*
  - *AMT*
  - *BRN*
  - *ACCCY*
  - *ACC*
  - *EXRATE*
- *Amountdue*
  - *FCCREF*
  - *COMP*
  - *DUEDT*
  - *AMTDUE*
  - *AMTSTD*
  - *ADJAMT*
- *Change-Log*
  - *FCCREF*
  - *FLDDESC*
  - *OLDDISPVAL*
  - *NEWDISPVAL*
- *Overrides*
  - *FCCREF*
  - *OVDSN*
  - *MODULE*
  - *ERRCODE*
  - *PARAM*
  - *ONLAUTHID*
  - *REMARKS*
  - *AUTHBY*
  - *AUTHDTSTAMP*

TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NAME

Attribute	Description

Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date

Description	Indicate Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PROTYPEDESC

Attribute	Description	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates the ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates the ERI currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST6

Attribute	**Description**	
Name	ACC_INST6	
Datatype	String	
Description	Country to which the AWI belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AGRID

Attribute	**Description**	
Name	AGRID	
Datatype	String	
Description	Indicates Agreement Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

BNKPRIO

Attribute	**Description**
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	Description	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	Description	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM4

Attribute	Description	
Name	RCVR_CUSNM4	
Datatype	String	
Description	Indicates the Receiver Name 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description	
Name	SNDR_ACC	
Datatype	String	
Description	Indicates the Sender Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

RCVR_ACC

Attribute	Description	
Name	RCVR_ACC	
Datatype	String	
Description	Indicates the Receiver Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicate event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicate value date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Include Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	Description	
Name	AVLAMT	
Datatype	Number	
Description	Indicates the Available amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	Description	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	Description	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement Split Master details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicate amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.28.2.LD-LDVamiDeleteSim-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-Pk*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *EVNT*
      - *EVNTDT*
      - *MAKERID*
      - *AMT*
      - *MATDT*
      - *VALDT*
      - *Settlement-Addl-Details*
        - *ACCBRN*
        - *ACC_CCY*
        - *ACC*
        - *AMTTAG*
        - *CUSTSPRD*

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*

- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*

EXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-Pk

Attribute	Description
Name	Contract-Master-Pk
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicates the Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT

Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM2

Attribute	Description

Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM4

Attribute	Description	
Name	RCVR_CUSNM4	
Datatype	String	
Description	Indicates the Receiver Name 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description	
Name	SNDR_ACC	
Datatype	String	
Description	Indicates the Sender Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

RCVR_ACC

Attribute	Description	
Name	RCVR_ACC	
Datatype	String	
Description	Indicates the Receiver Account	
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID

Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR

Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date

Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String

Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Indicates MIS Amendment Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE

Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description

Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	Description	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE

Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

DENOBASIS

Attribute	Description	
Name	DENOBASIS	
Datatype	String	
Description	Indicates the Denominator basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description	Indicates the BASIS_366	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOINTPRD

Attribute	Description	
Name	NOINTPRD	
Datatype	Number	
Description	Indicates the No of Interest Period.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	Description	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

Taxdetails-Main

Attribute	Description	
Name	Taxdetails-Main	
Datatype		
Description	Indicates Tax Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	Description	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Indicates Contract Schedules Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT

Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description

Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC

Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.3.LD-LDVamiDeleteSimReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *XREF*
    - *FCCREF*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *MATDT*
    - *VALDT*
    - *Settlement-Addl-Details*
      - *ACCBRN*
      - *ACC_CCY*
      - *ACC*
      - *AMTTAG*
      - *CUSTSPRD*
      - *ERIAMT*
      - *ERICCY*
      - *XRATE*
      - *GENMSG*

NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF

ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2

FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5

LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*
- *PERIOD*
- *FINYR*
- *GLCODE*
- *CCY*
- *AMT*
- *EXRATE*

Mis-Change-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*

Mis-Amend

- *CONTREF*
- *RTYPE*
- *RCODE*
- *SPD*

Refinance-Rate

- *UNITREF*
- *BKDATE*
- *EFFDT*
- *REFRT*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*

LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC

- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*

LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT
CONVPAIDAMT
Relationship-Linkage
DESCP
CUSTOMER
RELATIONSHIP
INHERIT
Brokerage-Master
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the Event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTDT

Attribute	Description	
Name	EVNTDT	
Datatype	Date	
Description	Indicates the Event Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	

Restrictions	Description
maxLength	3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	

Restrictions	Description
maxLength	3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	

Restrictions	Description
maxLength	15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	

Restrictions	Description
maxLength	20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description

Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description	
Name	CALCMETH	
Datatype	Number	
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Mis-Amend

Attribute	**Description**	
Name	Mis-Amend	
Datatype		
Description	Indicates MIS Amendment Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREF

Attribute	**Description**
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String

Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	**Description**	
Name	LQDSTS	
Datatype	String	
Description	Indicates the Liquidation Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Interest-Main

Attribute	**Description**	
Name	Interest-Main	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Indicates Tax Details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Indicates Contract Schedules Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description

Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

2.28.4.LD-LDVamiDeleteSimRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*
    - *VALDT*
    - *PRD*
    - *PROTYPEDESC*

LATVERNO

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*
  - *XPTACC*

XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER

RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4

- *CDFDOC*
- *ADDIDFR*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9

COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD

- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*

- TAXCCY
- VALDT
- COMPDT

Contract-Schedules

- SCOMP
- SCHD_TYPE
- FREQ
- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Contract-Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY

BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
Amountdue
FCCREF
COMP
DUEDT
AMTDUE
AMTSTD
ADJAMT
Change-Log
FCCREF
FLDDESC
OLDDISPVAL
NEWDISPVAL
Overrides
FCCREF
OVDSN
MODULE
ERRCODE
PARAM
ONLAUTHID
REMARKS
AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED

OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROTYPEDESC

Attribute	**Description**	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	**Description**	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Mis-Amend

Attribute	**Description**	
Name	Mis-Amend	
Datatype		
Description	Include MIS amend Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONTREF

Attribute	**Description**
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	Description	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

UNT

Attribute	Description	
Name	UNT	
Datatype	String	
Description	Indicates the Unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y

TOP

NOUNIT

Attribute	Description	
Name	NOUNIT	
Datatype	Number	
Description	Indicates the No Of Units.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	5

TOP

RTCDUSE

Attribute	Description	
Name	RTCDUSE	
Datatype	String	
Description	Indicates the Interest rate code usage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Taxdetails

Attribute	Description	
Name	Taxdetails	
Datatype		
Description	Include Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TAXRULE

Attribute	Description	
Name	TAXRULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

BASAMTTAG

Attribute	Description	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	**Description**	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	**Description**	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	**Description**	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description**
	maxLength / 10
	pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 1

TOP

Brokerage-Master

Attribute	**Description**
Name	Brokerage-Master
Datatype	
Description	Include Brokerage Master details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description**
	pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.LDVamiQuerySim

Query of Deposit VAMI

2.29.1.LD-LDVamiQuerySimReq-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*

LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP

UREF

PCREF

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*

XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6

RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1

INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3

REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER

- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*

- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*
  - *AMT*

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description

Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date

Description	Indicate Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description
Name	BRKCONFSTAT
Datatype	String
Description	Indicate broker confirmation status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description	
Name	LIQODSCH	
Datatype	String	
Description	Indicate Liquidate Od Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LNSTMTCYC

Attribute	Description	
Name	LNSTMTCYC	
Datatype	String	
Description	Indicate Loan Statement Cycle	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicate loan statement type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MVACRMTH

Attribute	Description	
Name	MVACRMTH	
Datatype	String	
Description	Indicate Move Across Months Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**
Name	PRCCYTYP
Datatype	String
Description	Indicate Prov Currency Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

UREF

Attribute	**Description**
Name	UREF
Datatype	String
Description	Indicate User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PCREF

Attribute	**Description**
Name	PCREF
Datatype	String
Description	Indicate PC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlement-Addl-Details

Attribute	**Description**
Name	Settlement-Addl-Details
Datatype	
Description	Include Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	**Description**	
Name	ACC_INST3	
Datatype	String	
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST4

Attribute	**Description**
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRRES4

Attribute	Description	
Name	REPRRES4	
Datatype	String	
Description	Indicates the Repair Reason 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description	
Name	ADDIDFR	
Datatype	String	
Description	Indicates the Additional Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	**Description**	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	**Description**
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description	Indicates the Effective date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates the Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQDODSCHD

Attribute	Description	
Name	LIQDODSCHD	
Datatype	String	
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SCHDBASIS

Attribute	Description	
Name	SCHDBASIS	
Datatype	String	
Description	Indicates Schedule Basis Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

UPDATEUTIL

Attribute	Description	
Name	UPDATEUTIL	
Datatype	String	
Description	Indicates Update Limits Utilisation Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.29.2.LD-LDVamiQuerySimRes-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *LDvws-Contract-master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

LDvws-Contract-master

Attribute	Description

Name	LDvws-Contract-master
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Counterparty	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINE

Attribute	Description	
Name	LINE	
Datatype	String	
Description	Indicates Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

DEALER

Attribute	Description	
Name	DEALER	
Datatype	String	
Description	Indicates Dealer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTC_DAYS

Attribute	Description	
Name	NOTC_DAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	Description	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	Description	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT
Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.ModifyBrnPrm

Modification of Loans and Deposit Branch Parameters

2.30.1.LD-ModifyBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	This Includes Modify LD Branch Parameters Full Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS

Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF

Datatype	String
Description	Indicates Button For UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicate the maker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the maker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String

Description	Indicates the checker stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates transaction status Open : O Closed :C
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.30.2.LD-ModifyBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-IO*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *MODNO*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	This Includes LD Branch Parameters Input Only Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PROCTILL

Attribute	**Description**	
Name	PROCTILL	
Datatype	String	
Description	Indicate Process Till S System Date N Next Working Day -1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,N

TOP

ACCRLVL

Attribute	**Description**	
Name	ACCRLVL	
Datatype	String	
Description	Indicate Accrual Level P Product C Contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

TAXCOMPBASIS

Attribute	**Description**	
Name	TAXCOMPBASIS	
Datatype	String	
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**
Name	SGENMANLIQ

Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.30.3.LD-ModifyBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *BTN_UDF*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	This Includes LD Branch Parameters Full Details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BTN_UDF

Attribute	**Description**	
Name	BTN_UDF	
Datatype	String	
Description	Indicates Button For UDF Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description	Indicate Use User Reference No in Messages Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Indicate the maker	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the maker stamp	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates the checker

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the checker stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates transaction status Open : O Closed :C	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.4.LD-ModifyBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
      - *PROCTILL*
      - *ACCRLVL*
      - *TAXCOMPBASIS*
      - *SGENMANLIQ*
      - *APYCALC*
      - *MODNO*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	Include Loans and deposits Branch parameters PK type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	Include Loans and deposits Branch parameters modify IO type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,N

TOP

ACCRLVL

Attribute	**Description**	
Name	ACCRLVL	
Datatype	String	
Description	Indicate Accrual Level P Product C Contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

TAXCOMPBASIS

Attribute	**Description**	
Name	TAXCOMPBASIS	
Datatype	String	
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**
Name	APYCALC

Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.ModifyFeeAccrualLDContract

Modification of FeeAccrual Loans and Deposit Contract

2.31.1.LD-ModifyFeeAccrual-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*

COMP
FEEAMT
REFAMT
VALDT
ACCBRN
ACC
BASAMT
CALCSTDT
CALCENDDT
FEETYP
CONSDISCNT
ACCREQD
FEECCY
REFCCY
COMPCCY
COMPESN
AMT
AMTCCY
FEEAUDIT
ESN
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT
REVR_MAKERID
REVR_MAKERSTAMP
REVR_CHECKERID
REVR_CHECKERSTAMP
STLDETAILS_IS_MAIN
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4

BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP

PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Advices

MSGTYPE
PARTYID
MEDIUM
SUPPRESS

PRIORITY

CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Fee Accrual modification that has been successfully modified

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Modification details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 4; pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MATDATE

Attribute	Description
Name	MATDATE
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREF

Attribute	Description
Name	CUSTREF
Datatype	String
Description	Indicates Custom Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST5

Attribute	Description

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

2.31.2.LD-ModifyFeeAccrual-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *XREF*
    - *Contract-Accr-Fee*
      - *FCCREF*
      - *COMPCCY*
      - *FEEAMT*
      - *REFAMT*
      - *VALDT*
      - *CALCSTDT*
      - *CALCENDDT*
      - *FEETYP*
      - *ACCREQD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual modification that has been successfully modified

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Modification-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	**Description**	
Name	Contract-Accr-Fee	
Datatype		
Description	Include Loans and Deposits Contract fee type details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	**Description**	
Name	COMPCCY	
Datatype	String	
Description	Indicate Component Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

FEEAMT

Attribute	Description	
Name	FEEAMT	
Datatype	Number	
Description	Indicate Fee Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

REFAMT

Attribute	Description	
Name	REFAMT	
Datatype	Number	
Description	Indicate Refund Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description	Indicate value date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.31.3.LD-ModifyFeeAccrual-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*
      - *COMP*
      - *FEEAMT*
      - *REFAMT*

- *VALDT*
- *ACCBRN*
- *ACC*
- *BASAMT*
- *CALCSTDT*
- *CALCENDDT*
- *FEETYP*
- *CONSDISCNT*
- *ACCREQD*
- *FEECCY*
- *REFCCY*
- *COMPCCY*
- *COMPESN*
- *AMT*
- *AMTCCY*

FEEAUDIT

- *ESN*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *CONTSTAT*
- *AUTHSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*

STLDETAILS_IS_MAIN

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*

BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2

PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the Fee Accrual that has been successfully modified

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Modification details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MATDATE

Attribute	Description	
Name	MATDATE	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREF

Attribute	Description	
Name	USRREF	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREF

Attribute	Description	
Name	CUSTREF	
Datatype	String	
Description	Indicates Custom Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description
Name	BASAMT
Datatype	String
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicates Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

COMPCCY

Attribute	Description	
Name	COMPCCY	
Datatype	String	
Description	Indicates Component Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

COMPESN

Attribute	Description	
Name	COMPESN	
Datatype	Number	
Description	Indicates Component Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Outstanding Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

AMTCCY

Attribute	Description	
Name	AMTCCY	
Datatype	String	
Description	Indicates Amount Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST5

Attribute	Description

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.31.4.LD-ModifyFeeAccrual-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-PK*
      - *FCCREF*
      - *USRREF*
    - *Contract-IO*
      - *FCCREF*
      - *XREF*
      - *Contract-Accr-Fee*
        - *FCCREF*
        - *COMPCCY*
        - *FEEAMT*
        - *REFAMT*
        - *VALDT*
        - *CALCSTDT*
        - *CALCENDDT*
        - *FEETYP*
        - *ACCREQD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual that has been successfully modified

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-PK

Attribute	Description
Name	Contract-PK
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Modification-Primary key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicate User Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Contract-IO

Attribute	Description
Name	Contract-IO
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Modification-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	Description
Name	Contract-Accr-Fee
Datatype	
Description	Include Loans and Deposits Contract fee type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicate Component Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number
Description	Indicate Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicate Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.ModifyLDBrnPrm

Modify Branch Parameter for LD / MM

2.32.1.LD-ModifyLDBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ld-Branch-Params-Full

Attribute	Description

Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: S,L

TOP

SGENMANLIQ

Attribute	Description	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	Description	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	Description	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Ld-Branch-Params-IO*
  - *BRNCD*
  - *PROCTILL*
  - *ACCRLVL*
  - *TAXCOMPBASIS*
  - *SGENMANLIQ*
  - *APYCALC*
  - *MAKER*
  - *MAKERSTAMP*
  - *UDFDETAILS*
    - *FLDNAM*
    - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.32.3.LD-ModifyLDBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-Full*
    - *BRNCD*
    - *PROCTILL*
    - *ACCRLVL*
    - *TAXCOMPBASIS*
    - *SGENMANLIQ*
    - *APYCALC*
    - *BRNNAME*
    - *USRREFINMSGS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,N</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	**Description**	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

USRREFINMSGS

Attribute	**Description**	
Name	USRREFINMSGS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Maker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Maker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Checker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.4.LD-ModifyLDBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-PK*
      - *BRNCD*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
      - *PROCTILL*
      - *ACCRLVL*
      - *TAXCOMPBASIS*
      - *SGENMANLIQ*
      - *APYCALC*
      - *MAKER*
      - *MAKERSTAMP*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-PK

Attribute	Description
Name	Ld-Branch-Params-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions**	**Description**
	enumeration	S,N

TOP

ACCRLVL

Attribute	Description	
Name	ACCRLVL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

TAXCOMPBASIS

Attribute	Description	
Name	TAXCOMPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,L

TOP

SGENMANLIQ

Attribute	Description	
Name	SGENMANLIQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APYCALC

Attribute	Description	
Name	APYCALC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.ModifyProduct

Modification of Loans and Deposit Product

2.33.1.LD-ModifyProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*

ACCRSTRTMNTH
ACCRSTRTDT
COLCTDRNGAMNDT
MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ

TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*

- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*
- *MORATRMPERD*

Liquidation-Order

- *CMPNT*
- *LIQORDR*

Grace-Levels

- *LVLNO*
- *NOOFUNITS*
- *UNIT*

Ccy-Days-Details

- *CCY*
- *EXCRATFXNGDAYS*
- *INTRATFXNGDAYS*

Trs-Components-Details

- *COMPNT*

Status-Master-Details

- *STATUS*
- *TRANSACTIONCD*
- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *COMPLETEACCRUALS*
- *TRNSFRCAPITLIZDINCM*
- *AUTOFRWD*
- *AUTOREVERSE*
- *DERVTNRUL*
- *RBKPROVSN*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*
  - *GLDESC*
  - *TRNSFERGL*
  - *DWNWRDTRANSFERFRMGL*
  - *DWNWRDTRANSFERTOGL*
- *Acc-Status-Gl-Details*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Tax-Scheme

- SCHME
- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
  - Ccy-Tax-Details
    - CCY
    - MAXTAXINTPERD
    - PERDUNIT
    - MININTTAXAMT
- Product-Interest
  - Interest-Components
    - BASISAMNTTYP
    - BASISAMNTCATG
    - RATCDUSGE
    - RATTYP
    - RATCD
    - SETTLMNTCCY
    - STPAPPLICTION
    - RESETTENOR
    - BRWLENDIND
    - LVLNO
    - PREPMTMETD
    - PROPREQD
    - MARGNBASIS
    - MARGNAPPLN
    - RATECALCTYP
    - ACQREQD
    - CHNGDRGAMNDMNT
    - SHWNINCNTRTMAINSCR
    - BLKAMTFLG
    - DEPORATECD
    - DISCACCRAPP
    - UNIT
    - NOUNIT
    - EVNT
    - COMPNENT
    - COMPNENTDESC
    - RUL
    - COLTYP
    - EVNTDESC

- RULEDESC
- Interest-Ccy-Preferences
  - CCY
  - DEFRAT
  - MINRATE
  - MAXRAT
  - DFLTSPRD
  - MINSPRD
  - MAXSPRD
  - INTBASIS
  - DENOMBASIS
  - BAS366
  - NOOFINTPRD
  - PRPMTRT
- Product-Accrual-Fee
  - Accrual-Fee-Details
    - LIQINT
    - LIQPRNCHNG
    - DISCACCRAPP
    - ACCRREQD
    - BASISAMT
    - ENDDTINP
    - RULFEE
    - FEETYP
    - ACCRFREQ
    - FREQVAL
    - COMP
    - STPASSN
    - COMPNENTDESC
- Product-Charges
  - Charge-Details
    - CHGTYP
    - THRDPTYTY
    - DRCRTYPE
    - NTCNSINDI
    - NETCONSPLSMINS
    - SWIFTQLF
    - SETTCCY
    - DFTWAIV
    - ALWRULAMND
    - AMNDAFTRASSOC
    - ALWAMTAMND
    - AMNDAFTRAPPL
    - STPASOCIATN

- ADVCHG
- CAPTLIZE
- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences

CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Modification-Full details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description	
Name	PROD_TYPE_DESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	Attribute: minOccurs Description: 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	Attribute: minOccurs Description: 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 255

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: enumeration Description: B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String

Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String
Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description

Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String
Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description	
Name	VRFY_DRWDNAMT	
Datatype	String	
Description	Indicates Verify Drawdown Amount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAXNOOFLNS

Attribute	Description	
Name	MAXNOOFLNS	
Datatype	Number	
Description	Indicates Maximum Number of Loans	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNPRD

Attribute	Description	
Name	LNPRD	
Datatype	String	
Description	Indicates Loan Product	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description	
Name	ALLWSCHEAMNDAFTRSGEN	
Datatype	String	
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates Statement Generation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DMNDBASIS

Attribute	Description
Name	DMNDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B,

TOP

AUTOACC

Attribute	Description
Name	AUTOACC
Datatype	String
Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number

Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String

Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String

Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINAMTPREPMNTPNLTY

Attribute	**Description**	
Name	MINAMTPREPMNTPNLTY	
Datatype	Number	
Description	Indicates Minimum Amount for Prepayment Penalty	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRTCPNTPRD

Attribute	**Description**	
Name	PRTCPNTPRD	
Datatype	String	
Description	Indicates Participant Product	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESCLS

Attribute	**Description**	
Name	PRDDESCLS	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CASCDEPRTCPTN

Attribute	**Description**	
Name	CASCDEPRTCPTN	
Datatype	String	
Description	Indicates Cascade Participation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String

Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Product Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEDCTTAXONRLOVR

Attribute	Description
Name	DEDCTTAXONRLOVR
Datatype	String
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMANRLOVR

Attribute	Description
Name	AUTOMANRLOVR
Datatype	String
Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String

Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	

Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Status-Advices-Details

Attribute	**Description**	
Name	Status-Advices-Details	
Datatype		
Description	Includes Status Advices detail	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MESSAGECD

Attribute	**Description**	
Name	MESSAGECD	
Datatype	String	
Description	Indicates Message of Status Advices	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Product-Status-Gl-Details

Attribute	**Description**	
Name	Product-Status-Gl-Details	
Datatype		
Description	Includes Product Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCNTROLE

Attribute	**Description**	
Name	ACCNTROLE	
Datatype	String	
Description	Indicates Accounting Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String

Description	Indicates Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description

Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PERDUNIT

Attribute	**Description**	
Name	PERDUNIT	
Datatype	String	
Description	Indicates Period Unit Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

MININTTAXAMT

Attribute	**Description**	
Name	MININTTAXAMT	
Datatype	Number	
Description	Indicates Minimum Interest Amount for Tax	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Product-Interest

Attribute	**Description**	
Name	Product-Interest	
Datatype		
Description	Includes Product Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Interest-Components

Attribute	**Description**	
Name	Interest-Components	
Datatype		
Description	Includes Interest Components details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

RATCD

Attribute	Description	
Name	RATCD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SETTLMNTCCY

Attribute	Description	
Name	SETTLMNTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STPAPPLICTION

Attribute	Description	
Name	STPAPPLICTION	
Datatype	String	
Description	Indicates Stop Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RESETTENOR

Attribute	Description	
Name	RESETTENOR	
Datatype	Number	
Description	Indicates Reset Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description

Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description

Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

EVNTDESC

Attribute	**Description**	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Interest-Ccy-Preferences

Attribute	**Description**	
Name	Interest-Ccy-Preferences	
Datatype		
Description	Includes Interest Currency preferences details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQPRNCHNG

Attribute	**Description**	
Name	LIQPRNCHNG	
Datatype	String	
Description	Indicates Increase In Principal Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BASISAMT

Attribute	**Description**
Name	BASISAMT
Datatype	String

Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description

Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description

Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF

Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD

Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	**Description**	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	**Description**	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	**Description**	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

GENTIME

Attribute	Description	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description

Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes Product Customer Restriction details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details

Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET

Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	**Description**	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.33.2.LD-ModifyProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*
    - *ACCRSTRTMNTH*
    - *ACCRSTRTDT*
    - *COLCTDRNGAMNDT*
    - *MINTNR*
    - *MAXTNR*
    - *STDTNR*
    - *TNRUNIT*
    - *RKYCCY*
    - *RKYVALDAT*
    - *RKYCNTRCTAMT*
    - *RKYMATURTYDT*
    - *RKYCPRTY*

RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
UTLIZTNREVALREQD
MODNO
Rollover-Details

- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules

- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*
- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*
- *MORATRMPERD*

Liquidation-Order

- *CMPNT*
- *LIQORDR*

Grace-Levels

- *LVLNO*
- *NOOFUNITS*
- *UNIT*

Ccy-Days-Details

- *CCY*
- *EXCRATFXNGDAYS*
- *INTRATFXNGDAYS*

Trs-Components-Details

- *COMPNT*

Status-Master-Details

- *STATUS*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *COMPLETEACCRUALS*
- *TRNSFRCAPITLIZDINCM*
- *AUTOFRWD*
- *AUTOREVERSE*
- *DERVTNRUL*
- *RBKPROVSN*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*

- TRNSFERGL
- DWNWRDTRANSFERFRMGL
- DWNWRDTRANSFERTOGL
- Acc-Status-Gl-Details
  - ACCROL
  - ACCHD
- Tax-Scheme
  - Tax-Details
    - RUL
    - BASISAMNTTAG
    - COMPTATIONEVNT
    - Ccy-Tax-Details
      - RULE
      - CCY
      - MAXTAXINTPERD
      - PERDUNIT
      - MININTTAXAMT
- Product-Interest
  - Interest-Components
    - BASISAMNTTYP
    - BASISAMNTCATG
    - RATCDUSGE
    - RATTYP
    - RATCD
    - SETTLMNTCCY
    - STPAPPLICTION
    - RESETTENOR
    - BRWLENDIND
    - LVLNO
    - PREPMTMETD
    - PROPREQD
    - MARGNBASIS
    - MARGNAPPLN
    - RATECALCTYP
    - ACQREQD
    - CHNGDRGAMNDMNT
    - SHWNINCNTRTMAINSCR
    - BLKAMTFLG
    - DEPORATECD
    - DISCACCRAPP
    - UNIT
    - NOUNIT
    - EVNT
    - COMPNENT

- *COMPNENTDESC*
- *RUL*
- *COLTYP*
- *EVNTDESC*
- *RULEDESC*
- *Interest-Ccy-Preferences*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *DFLTSPRD*
  - *MINSPRD*
  - *MAXSPRD*
  - *INTBASIS*
  - *DENOMBASIS*
  - *BAS366*
  - *NOOFINTPRD*
  - *PRPMTRT*
  - *COMP*

Product-Accrual-Fee

- *Accrual-Fee-Details*
  - *LIQINT*
  - *LIQPRNCHNG*
  - *DISCACCRAPP*
  - *ACCRREQD*
  - *BASISAMT*
  - *ENDDTINP*
  - *RULFEE*
  - *FEETYP*
  - *ACCRFREQ*
  - *FREQVAL*
  - *COMP*
  - *STPASSN*

Product-Charges

- *Charge-Details*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *DFTRULE*

- COMPNT
- Product-Events
  - CLASCD
  - Event-Details
    - EVNTCD
    - Accounting-Entries
      - ACCRLCD
      - AMTTAG
      - DRCRINDICTR
      - TRNCD
      - NETINDICTR
      - MISHD
      - REVALPRGL
      - REVALLSGL
      - REVALRTCD
      - REVALTXNCD
      - HOLTREAT
      - REVALREQD
    - Advices
      - MSGTYP
      - SUPRS
      - PRIOR
      - CHGREQD
- Role-To-Head-Mapping
  - CLASCD
  - Mapping-Details
    - ACCTRL
    - ACCTHD
    - STAT
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
  - Customers
    - CSTID
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - Branch-List
    - BRNDISALOW
  - Ccy-List

BGTDLCCY
SOLDCCY
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Discount-Accrual
CLASCD
CLASTYP
PRD
CLASDESC
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Modification-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String
Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAXNOOFLNS

Attribute	**Description**	
Name	MAXNOOFLNS	
Datatype	Number	
Description	Indicates Maximum Number of Loans	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNPRD

Attribute	**Description**	
Name	LNPRD	
Datatype	String	
Description	Indicates Loan Product	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	**Description**	
Name	ALLWSCHEAMNDAFTRSGEN	
Datatype	String	
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	**Description**	
Name	SGENREQD	
Datatype	String	
Description	Indicates Statement Generation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DMNDBASIS

Attribute	Description
Name	DMNDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B,

TOP

AUTOACC

Attribute	Description
Name	AUTOACC
Datatype	String
Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

USRDEFSCHD

Attribute	**Description**	
Name	USRDEFSCHD	
Datatype	String	
Description	Indicates User Defined Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LOANSTMTCYCL

Attribute	**Description**	
Name	LOANSTMTCYCL	
Datatype	String	
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	**Description**	
Name	STMNTDAY	
Datatype	Number	
Description	Indicates Loan Statement Day (of)	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANSTMTTYP

Attribute	**Description**
Name	LOANSTMTTYP
Datatype	String

Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provision Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS

Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Roll over details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDCTTAXONRLOVR

Attribute	Description
Name	DEDCTTAXONRLOVR
Datatype	String
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMANRLOVR

Attribute	Description
Name	AUTOMANRLOVR
Datatype	String
Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number
Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String

Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS

Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL

Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCROL

Attribute	**Description**	
Name	ACCROL	
Datatype	String	
Description	Indicates Account Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCHD

Attribute	**Description**	
Name	ACCHD	
Datatype	String	
Description	Indicates Account Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Tax-Scheme

Attribute	**Description**	
Name	Tax-Scheme	
Datatype		
Description	Includes Tax Scheme details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Includes Product Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,A,N

TOP

RATECALCTYP

Attribute	**Description**	
Name	RATECALCTYP	
Datatype	String	
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

ACQREQD

Attribute	**Description**	
Name	ACQREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHNGDRGAMNDMNT

Attribute	**Description**	
Name	CHNGDRGAMNDMNT	
Datatype	String	
Description	Indicates Allow Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	**Description**

Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String

Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT

Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQPRNCHNG

Attribute	Description
Name	LIQPRNCHNG
Datatype	String

Description	Indicates Increase In Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description	
Name	FREQVAL	
Datatype	Number	
Description	Indicates Frequency Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	Description	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	Description	
Name	STPASSN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Product-Charges

Attribute	Description	
Name	Product-Charges	
Datatype		
Description	Includes Product Charge details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	**Description**	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	**Description**	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

MSGTYP

Attribute	Description

Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	Description

Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes Product Customer Restriction details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description

Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SOLDCCY

Attribute	Description	
Name	SOLDCCY	
Datatype	String	
Description	Indicates Sold Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Product-Fields

Attribute	Description

Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASTYP

Attribute	Description
Name	CLASTYP
Datatype	String
Description	Indicates Class Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details

Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Name
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

DENOMMETHOD

Attribute	**Description**	
Name	DENOMMETHOD	
Datatype	String	
Description	Indicates Denominator Method The possible values are L, H, X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H,X,

TOP

Product-Mis-Details

Attribute	**Description**	
Name	Product-Mis-Details	
Datatype		
Description	Includes Product MIS details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	Description	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>100</td></tr></table>

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String

Description	Indicates Key ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

2.33.3.LD-ModifyProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDTYP*
    - *PROD_TYPE_DESC*
    - *PRDSLG*
    - *PRDGRP*
    - *DESC*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *RTCODEPRFERD*
    - *PMNTMTHD*
    - *PRDSCHTYP*
    - *DFLTCLSTR*
    - *ACCRFREQ*
    - *ACCRSTRTMNTH*
    - *ACCRSTRTDT*
    - *COLCTDRNGAMNDT*

MINTNR
MAXTNR
STDTNR
TNRUNIT
INTPERDBASIS
RKYCCY
RKYVALDAT
RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
SETTLMNTREQD
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO

TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT
MINAMTCCY
MINAMTPREPMNTPNLTY
PRTCPNTPRD
PRDDESCLS
CASCDEPRTCPTN
HOLDFLTBASIS
TRNCHETYP
UTLIZTNREVALREQD
REVALTNFREQ
REVALSTRTMNTH
REVALSTRTDT
REVALTNRATCD
REVALTNRATTYP
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Rollover-Details
- *RLOVRICCFFRM*
- *APLYTAX*
- *RLOVRWITHINT*
- *DEDCTTAXONRLOVR*
- *AUTOMANRLOVR*
- *RLOVRMECHNSM*

Default-Schedules
- *CMPNT*
- *REF*
- *FREQ*
- *FREQUNIT*
- *STRTDAY*
- *STRTMNTH*
- *STRTDT*
- *MORATRMPERDUNIT*

- *MORATRMPERD*
Liquidation-Order
  - *CMPNT*
  - *LIQORDR*
Grace-Levels
  - *LVLNO*
  - *NOOFUNITS*
  - *UNIT*
Ccy-Days-Details
  - *CCY*
  - *EXCRATFXNGDAYS*
  - *INTRATFXNGDAYS*
Trs-Components-Details
  - *COMPNT*
Status-Master-Details
  - *STATUS*
  - *TRANSACTIONCD*
  - *STATUSSEQ*
  - *STPACCRUALS*
  - *REVERSEACCRUALS*
  - *COMPLETEACCRUALS*
  - *TRNSFRCAPITLIZDINCM*
  - *AUTOFRWD*
  - *AUTOREVERSE*
  - *DERVTNRUL*
  - *RBKPROVSN*
  - *Status-Advices-Details*
    - *MESSAGECD*
  - *Product-Status-Gl-Details*
    - *ACCNTROLE*
    - *UPWARDTRANFERFRMGL*
    - *GLDESC*
    - *TRNSFERGL*
    - *DWNWRDTRANSFERFRMGL*
    - *DWNWRDTRANSFERTOGL*
  - *Acc-Status-Gl-Details*
    - *ACCROL*
    - *ROLDESC*
    - *ACCHD*
    - *GLDESC*
Tax-Scheme
  - *SCHME*
  - *SCHEMEDESC*
  - *Tax-Details*

RUL
AMNTTAG
BASISAMNTTAG
COMPTATIONEVNT
TYP
Ccy-Tax-Details
CCY
MAXTAXINTPERD
PERDUNIT
MININTTAXAMT
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY

DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
Product-Accrual-Fee
Accrual-Fee-Details
LIQINT
LIQPRNCHNG
DISCACCRAPP
ACCRREQD
BASISAMT
ENDDTINP
RULFEE
FEETYP
ACCRFREQ
FREQVAL
COMP
STPASSN
COMPNENTDESC
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY
DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB

PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD
EVENTDESC
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
DESC
GENTIME
SUPRS
PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD

- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
    - DESCRIPTION
  - Customers
    - CSTID
    - CUSTNAME
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - CLASDESC
  - Branch-List
    - BRNDISALOW
    - BRNNAME
  - Ccy-List
    - BGTDLCCY
    - CCYNAME
- Product-Fields
  - Field-Details
    - FLDNUM
    - FLDNAME
- Product-Discount-Accrual
  - CLASCD
  - CLASDESC
  - CLSDFLT
  - Disc-Accr-Details
    - DISCACCRREQD
    - ACCRFREQ
    - PREPAYTBDTREAT
    - ACQTYP
  - Ccy-Preferences
    - CCYCODE
    - CCYNAME
    - DENOMDCNTMET

DENOMMETHOD

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISCLS

MISCD

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Indicates Loans and Deposit Product Modification-Full details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP

Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROD_TYPE_DESC

Attribute	Description
Name	PROD_TYPE_DESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Product Group Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates Product Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description	Indicates Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Rate Code Buy /Sell Rate : B Middle Rate : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,M

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String

Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

INTPERDBASIS

Attribute	Description
Name	INTPERDBASIS
Datatype	String

Description	Indicates Interest Period Basis Include From Date : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String
Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description

Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description
Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number

Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SETTLMNTREQD

Attribute	Description
Name	SETTLMNTREQD
Datatype	String
Description	Indicates Settlement Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREPMNTPNLTY

Attribute	Description
Name	PREPMNTPNLTY
Datatype	String

Description	Indicates Prepayment Penalty Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RECMPUTESCHDLS

Attribute	Description
Name	RECMPUTESCHDLS
Datatype	String
Description	Indicates Recompute Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FWDDATNGALLWD

Attribute	Description
Name	FWDDATNGALLWD
Datatype	String
Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description

Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description
Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String

Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXNOOFLNS

Attribute	Description
Name	MAXNOOFLNS
Datatype	Number
Description	Indicates Maximum Number of Loans
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SGENREQD

Attribute	**Description**	
Name	SGENREQD	
Datatype	String	
Description	Indicates Statement Generation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTCREQD

Attribute	**Description**	
Name	NOTCREQD	
Datatype	String	
Description	Indicates Whether Notice is Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DMNDBASIS

Attribute	**Description**	
Name	DMNDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,B,

TOP

AUTOACC

Attribute	**Description**
Name	AUTOACC
Datatype	String

Description	Indicates Auto Account Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCCLSS

Attribute	Description
Name	ACCCLSS
Datatype	String
Description	Indicates Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

USRDEFSCHD

Attribute	Description
Name	USRDEFSCHD
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number
Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRSRAT

Attribute	Description
Name	TRSRAT
Datatype	Number
Description	Indicates TRS Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRSLNKDTO

Attribute	Description
Name	TRSLNKDTO
Datatype	String
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,

TOP

TRSMINCCY

Attribute	Description
Name	TRSMINCCY
Datatype	String
Description	Indicates the TRS Minimum Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRSMINAMT

Attribute	Description
Name	TRSMINAMT
Datatype	Number
Description	Indicates the TRS Minimum Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

MINAMTCCY

Attribute	Description
Name	MINAMTCCY
Datatype	String
Description	Indicates Minimum Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINAMTPREPMNTPNLTY

Attribute	Description
Name	MINAMTPREPMNTPNLTY
Datatype	Number
Description	Indicates Minimum Amount for Prepayment Penalty
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTCPNTPRD

Attribute	Description
Name	PRTCPNTPRD
Datatype	String
Description	Indicates Participant Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESCLS

Attribute	Description
Name	PRDDESCLS
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CASCDEPRTCPTN

Attribute	Description
Name	CASCDEPRTCPTN

Datatype	String
Description	Indicates Cascade Participation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDFLTBASIS

Attribute	Description
Name	HOLDFLTBASIS
Datatype	String
Description	Indicates Holiday Default Basis Facility : F Product : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

TRNCHETYP

Attribute	Description
Name	TRNCHETYP
Datatype	String
Description	Indicates Tranche Type Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALTNFREQ

Attribute	Description
Name	REVALTNFREQ
Datatype	String
Description	Indicates Revaluation Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

REVALSTRTMNTH

Attribute	Description
Name	REVALSTRTMNTH
Datatype	Number
Description	Indicates Revaluation Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTRTDT

Attribute	Description
Name	REVALSTRTDT
Datatype	Number
Description	Indicates Revaluation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALTNRATCD

Attribute	Description
Name	REVALTNRATCD
Datatype	String
Description	Indicates Revaluation Reval Rate Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTNRATTYP

Attribute	Description
Name	REVALTNRATTYP
Datatype	String
Description	Indicates Revaluation Reval Rate Type Mid : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Checker Date Time	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Product Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Auth Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Rollover details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDCTTAXONRLOVR

Attribute	Description
Name	DEDCTTAXONRLOVR
Datatype	String
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMANRLOVR

Attribute	Description
Name	AUTOMANRLOVR
Datatype	String
Description	Indicates Rollover Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RLOVRMECHNSM

Attribute	Description
Name	RLOVRMECHNSM
Datatype	String
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description

Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number

Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Status-Master-Details

Attribute	Description	
Name	Status-Master-Details	
Datatype		
Description	Includes Status control Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TRANSACTIONCD

Attribute	Description	
Name	TRANSACTIONCD	
Datatype	String	
Description	Indicates Transaction code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STATUSSEQ

Attribute	Description

Name	STATUSSEQ
Datatype	Number
Description	Indicates status Sequence
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String

Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN

Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description	
Name	DWNWRDTRANSFERTOGL	
Datatype	String	
Description	Indicates Downward Movement To GL Account Head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Acc-Status-Gl-Details

Attribute	Description	
Name	Acc-Status-Gl-Details	
Datatype		
Description	Includes Account Status GL details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCROL

Attribute	Description	
Name	ACCROL	
Datatype	String	
Description	Indicates Account Role	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCHD

Attribute	Description

Name	ACCHD
Datatype	String
Description	Indicates Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description	
Name	COMPTATIONEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	Description	
Name	TYP	
Datatype	String	
Description	Indicates Tax Type WITHHOLDING : W Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Ccy-Tax-Details

Attribute	Description	
Name	Ccy-Tax-Details	
Datatype		
Description	Includes Currency Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,M,Y,</td></tr></table>

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String

Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR

Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**	
Name	MARGNAPPLN	
Datatype	String	
Description	Indicates Margin Application Periodic : P Automatic : A None : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,A,N

TOP

RATECALCTYP

Attribute	**Description**	
Name	RATECALCTYP	
Datatype	String	
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNT

Attribute	**Description**	
Name	EVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COMPNENT

Attribute	**Description**	
Name	COMPNENT	
Datatype	String	
Description	Indicates Component	
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description

Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description

Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String

Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Accrual-Fee-Details

Attribute	Description
Name	Accrual-Fee-Details
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LIQINT

Attribute	Description
Name	LIQINT
Datatype	String
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQPRNCHNG

Attribute	Description
Name	LIQPRNCHNG
Datatype	String
Description	Indicates Increase In Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Includes Product Charge details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULDESC

Attribute	Description	
Name	RULDESC	
Datatype	String	
Description	Indicates rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Includes Product Events details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates Role Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes Product Customer Restriction details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CLSDFLT

Attribute	**Description**	
Name	CLSDFLT	
Datatype	String	
Description	Indicates Class Default	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description

Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.4.LD-ModifyProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PMNTMTHD*
      - *PRDSCHTYP*
      - *DFLTCLSTR*
      - *ACCRFREQ*
      - *ACCRSTRTMNTH*
      - *ACCRSTRTDT*
      - *COLCTDRNGAMNDT*
      - *MINTNR*
      - *MAXTNR*
      - *STDTNR*
      - *TNRUNIT*
      - *RKYCCY*
      - *RKYVALDAT*

RKYCNTRCTAMT
RKYMATURTYDT
RKYCPRTY
RKYRATAMT
NRMLRATVAR
MAXRATVAR
LIQDTNDMODE
APYCALC
PREPMNTPNLTY
RECMPUTESCHDLS
FWDDATNGALLWD
PRTIALPYMNTMLIQ
TAXAPPLCBL
CRTIFCATEOFDEP
ROLOVRALLWD
DYSFORAPYCALC
ALLWPRTIALREDNONCMNT
VRFY_DRWDNAMT
MAXNOOFLNS
LNPRD
ALLWSCHEAMNDAFTRSGEN
SGENREQD
NOTCREQD
DMNDBASIS
AUTOACC
ACCCLSS
USRDEFSCHD
LOANSTMTCYCL
STMNTDAY
LOANSTMTTYP
AUTPROVREQD
PROVCCYTYP
PROVFREQ
TRSAPPLCBL
TRSRAT
TRSLNKDTO
TRSMINCCY
TRSMINAMT
HOLDYCCY
CONSDRBRNHOL
IGNRHOLDYS
CSCDESCHDLS
MVACRSMNTHS
SCHDLEMVMNT

UTLIZTNREVALREQD
MODNO
Rollover-Details
  RLOVRICCFFRM
  APLYTAX
  RLOVRWITHINT
  DEDCTTAXONRLOVR
  AUTOMANRLOVR
  RLOVRMECHNSM
Default-Schedules
  CMPNT
  REF
  FREQ
  FREQUNIT
  STRTDAY
  STRTMNTH
  STRTDT
  MORATRMPERDUNIT
  MORATRMPERD
Liquidation-Order
  CMPNT
  LIQORDR
Grace-Levels
  LVLNO
  NOOFUNITS
  UNIT
Ccy-Days-Details
  CCY
  EXCRATFXNGDAYS
  INTRATFXNGDAYS
Trs-Components-Details
  COMPNT
Status-Master-Details
  STATUS
  STPACCRUALS
  REVERSEACCRUALS
  COMPLETEACCRUALS
  TRNSFRCAPITLIZDINCM
  AUTOFRWD
  AUTOREVERSE
  DERVTNRUL
  RBKPROVSN
  Status-Advices-Details
    MESSAGECD

- *Product-Status-Gl-Details*
  - *ACCNTROLE*
  - *UPWARDTRANFERFRMGL*
  - *TRNSFERGL*
  - *DWNWRDTRANSFERFRMGL*
  - *DWNWRDTRANSFERTOGL*
- *Acc-Status-Gl-Details*
  - *ACCROL*
  - *ACCHD*

Tax-Scheme

- *Tax-Details*
  - *RUL*
  - *BASISAMNTTAG*
  - *COMPTATIONEVNT*
  - *Ccy-Tax-Details*
    - *RULE*
    - *CCY*
    - *MAXTAXINTPERD*
    - *PERDUNIT*
    - *MININTTAXAMT*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*
  - *STPAPPLICTION*
  - *RESETTENOR*
  - *BRWLENDIND*
  - *LVLNO*
  - *PREPMTMETD*
  - *PROPREQD*
  - *MARGNBASIS*
  - *MARGNAPPLN*
  - *RATECALCTYP*
  - *ACQREQD*
  - *CHNGDRGAMNDMNT*
  - *SHWNINCNTRTMAINSCR*
  - *BLKAMTFLG*
  - *DEPORATECD*
  - *DISCACCRAPP*
  - *UNIT*

NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
COMP
Product-Accrual-Fee
Accrual-Fee-Details
LIQINT
LIQPRNCHNG
DISCACCRAPP
ACCRREQD
BASISAMT
ENDDTINP
RULFEE
FEETYP
ACCRFREQ
FREQVAL
COMP
STPASSN
Product-Charges
Charge-Details
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL

- STPASOCIATN
- ADVCHG
- DFTRULE
- COMPNT

Product-Events

- CLASCD
- Event-Details
  - EVNTCD
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
  - Advices
    - MSGTYP
    - SUPRS
    - PRIOR
    - CHGREQD

Role-To-Head-Mapping

- CLASCD
- Mapping-Details
  - ACCTRL
  - ACCTHD
  - STAT

Prod-Cust-Restrictions

- CATGLIS
- CLASCD
- Cust-Categories
  - CATGDSAW
- Customers
  - CSTID
  - ALWD

Branch-Ccy-Restrictions

- CCYLST
- BRNLST
- CLASCD

Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Discount-Accrual
CLASCD
CLASTYP
PRD
CLASDESC
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Indicates Loans and Deposit Product Modification-PK details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Indicates Loans and Deposit Product Modification-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PMNTMTHD

Attribute	Description
Name	PMNTMTHD
Datatype	String
Description	Indicates Payments Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,D,T,

TOP

PRDSCHTYP

Attribute	Description
Name	PRDSCHTYP
Datatype	String
Description	Indicates product Schedule Type Normal : N Capitalized : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,C,

TOP

DFLTCLSTR

Attribute	Description
Name	DFLTCLSTR
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String

Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

ACCRSTRTMNTH

Attribute	Description
Name	ACCRSTRTMNTH
Datatype	Number
Description	Indicates Accrual Start Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTRTDT

Attribute	Description
Name	ACCRSTRTDT
Datatype	Number
Description	Indicates Accrual Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLCTDRNGAMNDT

Attribute	Description
Name	COLCTDRNGAMNDT
Datatype	String
Description	Indicates Collect During Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTNR

Attribute	Description
Name	STDTNR
Datatype	Number
Description	Indicates Default Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNRUNIT

Attribute	Description
Name	TNRUNIT
Datatype	String
Description	Indicates Tenor Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

RKYCCY

Attribute	Description
Name	RKYCCY
Datatype	String

Description	Indicates Rekey Of Currency of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYVALDAT

Attribute	Description
Name	RKYVALDAT
Datatype	String
Description	Indicates Value Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCNTRCTAMT

Attribute	Description
Name	RKYCNTRCTAMT
Datatype	String
Description	Indicates Contract Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYMATURTYDT

Attribute	Description
Name	RKYMATURTYDT
Datatype	String
Description	Indicates Maturity Date of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYCPRTY

Attribute	Description

Name	RKYCPRTY
Datatype	String
Description	Indicates Counterparty of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYRATAMT

Attribute	Description
Name	RKYRATAMT
Datatype	String
Description	Indicates Interest Rate / Amount of Authorization Rekey Fields Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NRMLRATVAR

Attribute	Description
Name	NRMLRATVAR
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDTNDMODE

Attribute	Description
Name	LIQDTNDMODE
Datatype	String
Description	Indicates Automatic Liquidation of Preferences A for ON; M for OFF

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

APYCALC

Attribute	**Description**	
Name	APYCALC	
Datatype	String	
Description	Indicates Annual Percentage Yield Calculation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREPMNTPNLTY

Attribute	**Description**	
Name	PREPMNTPNLTY	
Datatype	String	
Description	Indicates Prepayment Penalty Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RECMPUTESCHDLS

Attribute	**Description**	
Name	RECMPUTESCHDLS	
Datatype	String	
Description	Indicates Recompute Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FWDDATNGALLWD

Attribute	**Description**
Name	FWDDATNGALLWD
Datatype	String

Description	Indicates Forward Dating Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTIALPYMNTMLIQ

Attribute	Description
Name	PRTIALPYMNTMLIQ
Datatype	String
Description	Indicates Partial Payment - Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXAPPLCBL

Attribute	Description
Name	TAXAPPLCBL
Datatype	String
Description	Indicates Tax Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTIFCATEOFDEP

Attribute	Description
Name	CRTIFCATEOFDEP
Datatype	String
Description	Indicates Certificate of Deposit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLOVRALLWD

Attribute	Description

Name	ROLOVRALLWD
Datatype	String
Description	Indicates Allow Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DYSFORAPYCALC

Attribute	Description
Name	DYSFORAPYCALC
Datatype	Number
Description	Indicates Day Basis for Annual Percentage Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLWPRTIALREDNONCMNT

Attribute	Description
Name	ALLWPRTIALREDNONCMNT
Datatype	String
Description	Indicates Allow Partial Reduction Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFY_DRWDNAMT

Attribute	Description
Name	VRFY_DRWDNAMT
Datatype	String
Description	Indicates Verify Drawdown Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXNOOFLNS

Attribute	Description
Name	MAXNOOFLNS
Datatype	Number

Description	Indicates Maximum Number of Loans
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNPRD

Attribute	Description
Name	LNPRD
Datatype	String
Description	Indicates Loan Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ALLWSCHEAMNDAFTRSGEN

Attribute	Description
Name	ALLWSCHEAMNDAFTRSGEN
Datatype	String
Description	Indicates Allow Schedules Amendment After Statement Generation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates Statement Generation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DMNDBASIS

Attribute	**Description**	
Name	DMNDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,B,

TOP

AUTOACC

Attribute	**Description**	
Name	AUTOACC	
Datatype	String	
Description	Indicates Auto Account Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCCLSS

Attribute	**Description**	
Name	ACCCLSS	
Datatype	String	
Description	Indicates Account Class	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

USRDEFSCHD

Attribute	**Description**
Name	USRDEFSCHD
Datatype	String

Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANSTMTCYCL

Attribute	Description
Name	LOANSTMTCYCL
Datatype	String
Description	Indicates Loan statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D,

TOP

STMNTDAY

Attribute	Description
Name	STMNTDAY
Datatype	Number
Description	Indicates Loan Statement Day (of)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANSTMTTYP

Attribute	Description
Name	LOANSTMTTYP
Datatype	String
Description	Indicates Loan Statement Type None : N Summary : S Detail : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	Indicates Provision Currency Local Currency : L Contract Currency : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

PROVFREQ

Attribute	Description
Name	PROVFREQ
Datatype	String
Description	Indicates Provision Frequency Monthly : M Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,

TOP

TRSAPPLCBL

Attribute	Description
Name	TRSAPPLCBL
Datatype	String
Description	Indicates TRS Applicable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRSRAT

Attribute	Description	
Name	TRSRAT	
Datatype	Number	
Description	Indicates TRS Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRSLNKDTO

Attribute	Description	
Name	TRSLNKDTO	
Datatype	String	
Description	Indicates the TRS Linked to the product PRINCIPAL : P INTEREST : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,

TOP

TRSMINCCY

Attribute	Description	
Name	TRSMINCCY	
Datatype	String	
Description	Indicates the TRS Minimum Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRSMINAMT

Attribute	Description	
Name	TRSMINAMT	
Datatype	Number	
Description	Indicates the TRS Minimum Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONSDRBRNHOL

Attribute	Description
Name	CONSDRBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGNRHOLDYS

Attribute	Description
Name	IGNRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CSCDESCHDLS

Attribute	Description
Name	CSCDESCHDLS
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRSMNTHS

Attribute	Description
Name	MVACRSMNTHS
Datatype	String
Description	Indicates Move Across Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDLEMVMNT

Attribute	Description
Name	SCHDLEMVMNT
Datatype	String
Description	Indicates Schedule Movement Move Forward : N Move Backward : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P

TOP

UTLIZTNREVALREQD

Attribute	Description
Name	UTLIZTNREVALREQD
Datatype	String
Description	Indicates Util Reval Required Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Rollover-Details

Attribute	Description
Name	Rollover-Details
Datatype	
Description	Includes Roll over details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLOVRICCFFRM

Attribute	Description
Name	RLOVRICCFFRM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

APLYTAX

Attribute	Description
Name	APLYTAX
Datatype	String
Description	Indicates Apply Tax Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RLOVRWITHINT

Attribute	Description
Name	RLOVRWITHINT
Datatype	String
Description	Indicates Rollover With Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDCTTAXONRLOVR

Attribute	Description	
Name	DEDCTTAXONRLOVR	
Datatype	String	
Description	Indicates Deduct Tax on Rollover Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMANRLOVR

Attribute	Description	
Name	AUTOMANRLOVR	
Datatype	String	
Description	Indicates Rollover Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

RLOVRMECHNSM

Attribute	Description	
Name	RLOVRMECHNSM	
Datatype	String	
Description	Indicates Rollover Mechanism New Version : V Spawn Contract : C Linked Contract : L	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,C,L,

TOP

Default-Schedules

Attribute	Description
Name	Default-Schedules
Datatype	
Description	Includes Default Schedules details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REF

Attribute	Description
Name	REF
Datatype	String
Description	Indicates Refer Calender : C Value Date : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,V,

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Frequency Daily : D Weekly : W Monthly : M Quarterly : Q Half Yearly: H Yearly : Y Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B,

TOP

FREQUNIT

Attribute	Description

Name	FREQUNIT
Datatype	Number
Description	Indicates Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAY

Attribute	Description
Name	STRTDAY
Datatype	Number
Description	Indicates Day Sunday : 1 Monday : 2 Tuesday : 3 Wednesday : 4 Thursday : 5 Friday : 6 Saturday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTMNTH

Attribute	Description
Name	STRTMNTH
Datatype	Number
Description	Indicates Month January : 1 February : 2 March : 3 April : 4 May : 5 June : 6 July : 7 August : 8 September : 9 October : 10 November : 11 December : 12
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDT

Attribute	Description
Name	STRTDT
Datatype	Number
Description	Indicates Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MORATRMPERDUNIT

Attribute	Description
Name	MORATRMPERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MORATRMPERD

Attribute	Description
Name	MORATRMPERD
Datatype	Number
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Liquidation-Order

Attribute	Description
Name	Liquidation-Order
Datatype	
Description	Includes Liquidation Order details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LIQORDR

Attribute	Description
Name	LIQORDR
Datatype	Number

Description	Indicates Liquidation Order
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Grace-Levels

Attribute	Description
Name	Grace-Levels
Datatype	
Description	Includes Grace Level details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

NOOFUNITS

Attribute	Description
Name	NOOFUNITS
Datatype	Number
Description	Indicates Number of Units / Nominal Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

Ccy-Days-Details

Attribute	Description
Name	Ccy-Days-Details
Datatype	
Description	Includes Currency Days details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXCRATFXNGDAYS

Attribute	Description
Name	EXCRATFXNGDAYS
Datatype	Number
Description	Indicates Exchange Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATFXNGDAYS

Attribute	Description
Name	INTRATFXNGDAYS
Datatype	Number
Description	Indicates Interest Rate Fixing Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Trs-Components-Details

Attribute	Description
Name	Trs-Components-Details
Datatype	
Description	Includes TRS Component details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Status-Master-Details

Attribute	Description
Name	Status-Master-Details
Datatype	
Description	Includes Status control Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	Indicates Stop Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	Indicates Reverse Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	Indicates Complete Accruals Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNSFRCAPITLIZDINCM

Attribute	Description
Name	TRNSFRCAPITLIZDINCM
Datatype	String
Description	Indicates Transfer Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	Indicates Forward of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	Indicates Reverse of Automatic Movement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	Indicates Rebook Provisioning on Status Change Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices detail
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message of Status Advices
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Product-Status-Gl-Details

Attribute	Description
Name	Product-Status-Gl-Details
Datatype	
Description	Includes Product Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANFERFRMGL

Attribute	Description
Name	UPWARDTRANFERFRMGL
Datatype	String
Description	Indicates Upward From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL

Datatype	String
Description	Indicates Accounting Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGL

Attribute	Description
Name	DWNWRDTRANSFERFRMGL
Datatype	String
Description	Indicates Downward Movement FROM GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGL

Attribute	Description
Name	DWNWRDTRANSFERTOGL
Datatype	String
Description	Indicates Downward Movement To GL Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Acc-Status-Gl-Details

Attribute	Description
Name	Acc-Status-Gl-Details
Datatype	
Description	Includes Account Status GL details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	Indicates Account Role
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	Indicates Account Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Product Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTTAG

Attribute	Description

Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Ccy-Tax-Details

Attribute	Description
Name	Ccy-Tax-Details
Datatype	
Description	Includes Currency Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAXTAXINTPERD

Attribute	Description
Name	MAXTAXINTPERD
Datatype	Number
Description	Indicates Maximum Interest Period for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PERDUNIT

Attribute	Description
Name	PERDUNIT
Datatype	String
Description	Indicates Period Unit Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y,

TOP

MININTTAXAMT

Attribute	Description
Name	MININTTAXAMT
Datatype	Number
Description	Indicates Minimum Interest Amount for Tax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes Product Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description

Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description

Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD

Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEPORATECD

Attribute	**Description**	
Name	DEPORATECD	
Datatype	String	
Description	Indicates Link Contract As Ratecode Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description	Indicates Units Days : D Months : M Years : Y	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y,

TOP

NOUNIT

Attribute	**Description**
Name	NOUNIT

Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Accrual-Fee

Attribute	Description
Name	Product-Accrual-Fee
Datatype	
Description	Includes Product Accrual details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Accrual-Fee-Details

Attribute	**Description**	
Name	Accrual-Fee-Details	
Datatype		
Description	Includes Accrual Fee details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LIQINT

Attribute	**Description**	
Name	LIQINT	
Datatype	String	
Description	Indicates Liquidate Fee Initiation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQPRNCHNG

Attribute	**Description**	
Name	LIQPRNCHNG	
Datatype	String	
Description	Indicates Increase In Principal Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPP

Attribute	**Description**	
Name	DISCACCRAPP	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	String
Description	Indicates Basis Amount Expected Out Fact : O Expected Balance : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,E

TOP

ENDDTINP

Attribute	Description
Name	ENDDTINP
Datatype	String
Description	Indicates Allow End Date Input Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RULFEE

Attribute	Description
Name	RULFEE
Datatype	String
Description	Indicates Fee Rule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicates Fee Type Income : I Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	Number
Description	Indicates Frequency Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Includes Product Charge details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Includes Product Events details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR

Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	**Description**	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

MSGTYP

Attribute	Description	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRS

Attribute	Description	
Name	SUPRS	
Datatype	String	
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Includes Role To Head Mapping details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes Product Customer Restriction details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers

Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes Branch Currency Restrictions details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Branch-List

Attribute	Description	
Name	Branch-List	
Datatype		
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	Description

Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASTYP

Attribute	Description
Name	CLASTYP
Datatype	String
Description	Indicates Class Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M Half Yearly : H Quarterly : Q Yearly : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,H,Q,Y,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	

Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Name
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes Product MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String

Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.QueryBrnPrm

Query of Loans and Deposit Branch Parameters

2.34.1.LD-QueryBrnPrm-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Ld-Branch-Params-IO*
  - *BRNCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	Include Loans and deposits Branch parameters query IO type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

2.34.2.LD-QueryBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
    - *Ld-Branch-Params-Full*
      - *BRNCD*
      - *PROCTILL*
      - *ACCRLVL*
      - *TAXCOMPBASIS*
      - *SGENMANLIQ*
      - *APYCALC*
      - *BRNNAME*
      - *BTN_UDF*
      - *USRREFINMSGS*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*

AUTHSTAT
ONCEAUTH
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	Include Loans and deposits Branch parameters Query IO type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	Include Loans and deposits branch parameters full details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicate branch code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	Indicate Process Till S System Date N Next Working Day -1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	Indicate Accrual Level P Product C Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	Indicate Tax Basis S Schedule Amount L Liquidation Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String

Description	Indicate Settlement Message At Manual Liquidation Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	Indicate Annual Percentage Yield Calculation Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Inidctae branch name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates Button For UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	Indicate Use User Reference No in Messages Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicate the maker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the maker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the checker stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates transaction status Open : O Closed :C
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates if its once authorised
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Include UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.QueryFeeAccrualLDContract

Query of FeeAccrual Loans and Deposit Contract

2.35.1.LD-QueryFeeAccrual-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *XREF*
    - *Contract-Accr-Fee*
      - *FCCREF*
      - *COMPCCY*
      - *FEEAMT*
      - *REFAMT*
      - *VALDT*
      - *CALCSTDT*
      - *CALCENDDT*
      - *FEETYP*
      - *ACCREQD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual that has been successfully Queried

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Query-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	Description
Name	Contract-Accr-Fee
Datatype	
Description	Include Loans and Deposits Contract fee type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicate Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number
Description	Indicate Fee Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicate Refund Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.35.2.LD-QueryFeeAccrual-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*
      - *COMP*
      - *FEEAMT*
      - *REFAMT*

- *VALDT*
- *ACCBRN*
- *ACC*
- *BASAMT*
- *CALCSTDT*
- *CALCENDDT*
- *FEETYP*
- *CONSDISCNT*
- *ACCREQD*
- *FEECCY*
- *REFCCY*
- *COMPCCY*
- *COMPESN*
- *AMT*
- *AMTCCY*

FEEAUDIT

- *ESN*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *CONTSTAT*
- *AUTHSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*

STLDETAILS_IS_MAIN

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*

BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2

PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the Fee Accrual that has been successfully Queried

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Query details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MATDATE

Attribute	Description	
Name	MATDATE	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREF

Attribute	Description	
Name	USRREF	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREF

Attribute	Description	
Name	CUSTREF	
Datatype	String	
Description	Indicates Custom Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**	
Name	TRNFRTYP	
Datatype	String	
Description	Indicates Transfer Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.36.QueryLDBrnPrm

Query Branch Parameter for LD /MM

2.36.1.LD-QueryLDBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ld-Branch-Params-IO*
    - *BRNCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

2.36.2.LD-QueryLDBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ld-Branch-Params-IO*
      - *BRNCD*
    - *Ld-Branch-Params-Full*
      - *BRNCD*
      - *PROCTILL*
      - *ACCRLVL*
      - *TAXCOMPBASIS*
      - *SGENMANLIQ*
      - *APYCALC*
      - *BRNNAME*
      - *USRREFINMSGS*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ld-Branch-Params-IO

Attribute	Description
Name	Ld-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Ld-Branch-Params-Full

Attribute	Description
Name	Ld-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILL

Attribute	Description
Name	PROCTILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,N

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,C

TOP

TAXCOMPBASIS

Attribute	Description
Name	TAXCOMPBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,L

TOP

SGENMANLIQ

Attribute	Description
Name	SGENMANLIQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

APYCALC

Attribute	Description
Name	APYCALC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

USRREFINMSGS

Attribute	Description
Name	USRREFINMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Maker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Maker Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Checker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Modification No
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Contract Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.37.QueryProvisionLDContract

Query of Provision Loans and Deposit Contract

2.37.1.LDProvision-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CONTRACT_PROVISION-IO-IO*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for LD Contract Provision

TOP

CONTRACT_PROVISION-IO-IO

Attribute	Description
Name	CONTRACT_PROVISION-IO-IO
Datatype	
Description	Includes Loans and Deposits Query Contract Provision Input Only details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates the Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEQ

Attribute	Description	
Name	SEQ	
Datatype	Number	
Description	Indicates the Sequence number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.37.2.LDProvision-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *PROVISION-DETAILS*
    - *FCCREF*
    - *CCY*
    - *AMT*
    - *SEQ*
    - *STAT*
    - *CONTRACT-EVENT-LOG*
      - *MAKERID*
      - *MAKERSTAMP*
      - *CHECKERID*
      - *CHECKERSTAMP*
      - *CONTSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the LD Contract Provision that has been successfully quered

TOP

PROVISION-DETAILS

Attribute	Description
Name	PROVISION-DETAILS
Datatype	
Description	Includes Loans and Deposits Query Provision details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SEQ

Attribute	Description
Name	SEQ
Datatype	Number
Description	Indicates the Sequence number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CONTRACT-EVENT-LOG

Attribute	Description
Name	CONTRACT-EVENT-LOG
Datatype	
Description	Includes the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the Checker Id.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.ReassignLDContract

Reassignment of Loans and Deposits Contract

2.38.1.LDReassign-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CONTRACT_REASSIGN*
    - *PRD*
    - *FCCREF*
    - *CURRENTUSER*
    - *NEWUSER*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for creation of LD Contract Reassign User.

TOP

CONTRACT_REASSIGN

Attribute	Description
Name	CONTRACT_REASSIGN
Datatype	
Description	Includes Loans and Deposits Create Contract Reassign full details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CURRENTUSER

Attribute	Description
Name	CURRENTUSER
Datatype	String
Description	Indicates the Current User Identity.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

NEWUSER

Attribute	Description
Name	NEWUSER
Datatype	String
Description	Indicates the New User Identity.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

2.38.2.LDReassign-Create-Req-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CONTRACT_REASSIGN-IO-IO
PRD
FCCREF
CURRENTUSER
NEWUSER

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format for primary request for LD Contract Reassing User .

TOP

CONTRACT_REASSIGN-IO-IO

Attribute	Description
Name	CONTRACT_REASSIGN-IO-IO
Datatype	
Description	Includes Loans and Deposits Create Contract Reassign Input Only details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CURRENTUSER

Attribute	Description
Name	CURRENTUSER
Datatype	String
Description	Indicates the Current User Identity.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

NEWUSER

Attribute	Description
Name	NEWUSER
Datatype	String
Description	Indicates the New User Identity.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

2.38.3.LDReassign-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Reas*
    - *PRD*
    - *FCCREF*
    - *CURRENTUSER*
    - *NEWUSER*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the LD Contract Reassign User that has been successfully Created

TOP

Product-Reas

Attribute	Description
Name	Product-Reas
Datatype	
Description	Includes Loans and Deposits Create Product Reassign details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String

Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CURRENTUSER

Attribute	Description
Name	CURRENTUSER
Datatype	String
Description	Indicates the Current User Identity.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [a-zA-Z0-9]*

TOP

NEWUSER

Attribute	Description
Name	NEWUSER
Datatype	String
Description	Indicates the New User Identity.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [a-zA-Z0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.38.4.LDReassign-Create-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Reas*
      - *PRD*
      - *FCCREF*
      - *CURRENTUSER*
      - *NEWUSER*
    - *CONTRACT_REASSIGN-IO*
      - *PRD*
      - *FCCREF*
      - *CURRENTUSER*
      - *NEWUSER*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Registered

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Reas

Attribute	Description
Name	Product-Reas
Datatype	
Description	Includes Loans and Deposits Create Product Reassign details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CURRENTUSER

Attribute	Description
Name	CURRENTUSER
Datatype	String
Description	Indicates the Current User Identity.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

NEWUSER

Attribute	Description
Name	NEWUSER
Datatype	String
Description	Indicates the New User Identity.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

CONTRACT_REASSIGN-IO

Attribute	Description
Name	CONTRACT_REASSIGN-IO
Datatype	
Description	Includes Loans and Deposits Create Contract Reassign Input Only details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CURRENTUSER

Attribute	Description
Name	CURRENTUSER
Datatype	String
Description	Indicates the Current User Identity.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [a-zA-Z0-9]*

TOP

NEWUSER

Attribute	Description
Name	NEWUSER
Datatype	String
Description	Indicates the New User Identity.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [a-zA-Z0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.ReverseFeeAccrualLDContract

Reversal of FeeAccrual Loans and Deposit Contract

2.39.1.LD-ReverseFeeAccrual-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*

COMP
FEEAMT
REFAMT
VALDT
ACCBRN
ACC
BASAMT
CALCSTDT
CALCENDDT
FEETYP
CONSDISCNT
ACCREQD
FEECCY
REFCCY
COMPCCY
COMPESN
AMT
AMTCCY
FEEAUDIT
ESN
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
CONTSTAT
AUTHSTAT
REVR_MAKERID
REVR_MAKERSTAMP
REVR_CHECKERID
REVR_CHECKERSTAMP
STLDETAILS_IS_MAIN
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4

BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP

PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS

PRIORITY

CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Fee Accrual has been successfully reversed

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Reversal details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MATDATE

Attribute	Description	
Name	MATDATE	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRREF

Attribute	Description	
Name	USRREF	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREF

Attribute	Description	
Name	CUSTREF	
Datatype	String	
Description	Indicates Custom Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

2.39.2.LD-ReverseFeeAccrual-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *XREF*
    - *Contract-Accr-Fee*
      - *FCCREF*
      - *COMPCCY*
      - *FEEAMT*
      - *REFAMT*
      - *VALDT*
      - *CALCSTDT*
      - *CALCENDDT*
      - *FEETYP*
      - *ACCREQD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual has been successfully reversed

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Reversal-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	**Description**	
Name	Contract-Accr-Fee	
Datatype		
Description	Include Loans and Deposits Contract fee type details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	**Description**	
Name	COMPCCY	
Datatype	String	
Description	Indicate Component Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

FEEAMT

Attribute	Description	
Name	FEEAMT	
Datatype	Number	
Description	Indicate Fee Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

REFAMT

Attribute	Description	
Name	REFAMT	
Datatype	Number	
Description	Indicate Refund Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description	Indicate value date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.39.3.LD-ReverseFeeAccrual-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *PROD*
    - *COUNTPTY*
    - *CUSTNAME*
    - *MATDATE*
    - *VALDATE*
    - *USRREF*
    - *CUSTREF*
    - *CONTCCY*
    - *PRINCOUTBAL*
    - *USRSTAT*
    - *LATESTESN*
    - *CURRESN*
    - *SUBSYSTEMSTAT*
    - *FEEACCRUAL*
      - *COMP*
      - *FEEAMT*
      - *REFAMT*

- *VALDT*
- *ACCBRN*
- *ACC*
- *BASAMT*
- *CALCSTDT*
- *CALCENDDT*
- *FEETYP*
- *CONSDISCNT*
- *ACCREQD*
- *FEECCY*
- *REFCCY*
- *COMPCCY*
- *COMPESN*
- *AMT*
- *AMTCCY*

FEEAUDIT

- *ESN*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *CONTSTAT*
- *AUTHSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*

STLDETAILS_IS_MAIN

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*

BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2

PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full responce information relating the Fee Accrual that has been successfully reversed

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Reversal details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

COUNTPTY

Attribute	Description
Name	COUNTPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MATDATE

Attribute	Description
Name	MATDATE
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREF

Attribute	Description
Name	CUSTREF
Datatype	String
Description	Indicates Custom Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PRINCOUTBAL

Attribute	Description
Name	PRINCOUTBAL
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [A-Z]{4}

TOP

LATESTESN

Attribute	Description
Name	LATESTESN
Datatype	Number
Description	Indicates Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CURRESN

Attribute	Description
Name	CURRESN
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

FEEACCRUAL

Attribute	Description
Name	FEEACCRUAL
Datatype	
Description	Includes Accrual Fee details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number

Description	Indicates Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicates Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

BASAMT

Attribute	Description	
Name	BASAMT	
Datatype	String	
Description	Indicates Basis Amount Expected Outstanding Face Value : O Expected Balance : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E

TOP

CALCSTDT

Attribute	Description	
Name	CALCSTDT	
Datatype	Date	
Description	Indicates Calculation Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALCENDDT

Attribute	Description	
Name	CALCENDDT	
Datatype	Date	
Description	Indicates Calculation End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FEETYP

Attribute	Description	
Name	FEETYP	
Datatype	String	
Description	Indicates Fee Type Income : I Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

CONSDISCNT

Attribute	Description
Name	CONSDISCNT
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECCY

Attribute	Description
Name	FEECCY
Datatype	String
Description	Indicates Fee Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REFCCY

Attribute	Description
Name	REFCCY
Datatype	String
Description	Indicates Refund Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

COMPESN

Attribute	Description
Name	COMPESN
Datatype	Number
Description	Indicates Component Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAUDIT

Attribute	Description
Name	FEEAUDIT
Datatype	
Description	Includes Fee Audit details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates Maker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,A

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for UnAuthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_MAKERSTAMP

Attribute	**Description**	
Name	REVR_MAKERSTAMP	
Datatype	Date	
Description	Indicates the Maker DateTime when the maker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVR_CHECKERID

Attribute	**Description**	
Name	REVR_CHECKERID	
Datatype	String	
Description	Indicates the Checker id who has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REVR_CHECKERSTAMP

Attribute	**Description**	
Name	REVR_CHECKERSTAMP	
Datatype	Date	
Description	Indicates the Checker DateTime when the Checker has done the reversal of contract	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STLDETAILS_IS_MAIN

Attribute	**Description**	
Name	STLDETAILS_IS_MAIN	
Datatype		
Description	Includes Settlement Main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**

Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST4

Attribute	Description	
Name	INT_REIM_INST4	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST5

Attribute	Description	
Name	INT_REIM_INST5	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST6

Attribute	Description	
Name	INT_REIM_INST6	
Datatype	String	
Description	Country to which the Intermediary remitter institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**	
Name	ORDER_CUST4	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**

Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description

Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.39.4.LD-ReverseFeeAccrual-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-PK*
      - *FCCREF*
      - *USRREF*
    - *Contract-IO*
      - *FCCREF*
      - *XREF*
      - *Contract-Accr-Fee*
        - *FCCREF*
        - *COMPCCY*
        - *FEEAMT*
        - *REFAMT*
        - *VALDT*
        - *CALCSTDT*
        - *CALCENDDT*
        - *FEETYP*
        - *ACCREQD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Fee Accrual that has been successfully reversed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-PK

Attribute	Description
Name	Contract-PK
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Reversal-Primary Key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	Indicate User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Contract-IO

Attribute	Description
Name	Contract-IO
Datatype	
Description	Indicates Loans and Deposit Contract Fee Accrual Reversal-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Accr-Fee

Attribute	Description
Name	Contract-Accr-Fee
Datatype	
Description	Include Loans and Deposits Contract fee type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicate Component Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FEEAMT

Attribute	Description
Name	FEEAMT
Datatype	Number
Description	Indicate Fee Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

REFAMT

Attribute	Description
Name	REFAMT
Datatype	Number
Description	Indicate Refund Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCSTDT

Attribute	Description
Name	CALCSTDT
Datatype	Date
Description	Indicates Calculation Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALCENDDT

Attribute	Description
Name	CALCENDDT
Datatype	Date
Description	Indicate Calculation End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FEETYP

Attribute	Description
Name	FEETYP
Datatype	String
Description	Indicate fee type I Income E Expense
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E

TOP

ACCREQD

Attribute	Description
Name	ACCREQD
Datatype	String
Description	Indicate Accrual Required Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.AuthorizeLDContract

Authorization of Loans and Deposits Contract

2.40.1.LDContract-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Auth-Details*
    - *XREF*
    - *FCCREF*
    - *ESN*
    - *EVENTCD*
    - *EVENTDT*
    - *INPUTBY*
    - *Rekey-Details*
      - *CCY*
      - *AMT*
      - *VALDT*
      - *MATDT*
    - *Contract-Ovd*
      - *OVDSN*
      - *MODULE*
      - *ERRCODE*

PARAM
ONLAUTHID
REMARKS
AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT
Contract-Change-Log
CHGSN
DTCHANGED
FLDCHANGED
FLDDESC
OLDVAL
OLDDISPVAL
NEWVAL
NEWDISPVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Flexcube Reference number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{4}

TOP

EVENTDT

Attribute	Description
Name	EVENTDT
Datatype	Date
Description	Indicates Event Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	Indicates the Maker ID of the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Rekey-Details

Attribute	Description
Name	Rekey-Details
Datatype	
Description	Include Loans and Deposits ReKey fields type details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd

Datatype	
Description	Include contract override type details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	Number
Description	Indicates Override Sequence Number.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicate the Remarks provided by the online authorizer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized the booked contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	Date	
Description	Indicates date and stamp when the user has authorized the booked contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

OVDSTATUS

Attribute	Description
Name	OVDSTATUS
Datatype	String
Description	Indicates the Overridden status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates whether the override is confirmed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Include Contract chnage log type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGSN

Attribute	Description
Name	CHGSN
Datatype	Number
Description	Indicates Change Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr></table>

TOP

DTCHANGED

Attribute	Description
Name	DTCHANGED
Datatype	String
Description	Indicates Date Changed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

FLDCHANGED

Attribute	Description
Name	FLDCHANGED
Datatype	String
Description	Indicates Field Changed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

OLDVAL

Attribute	**Description**	
Name	OLDVAL	
Datatype	String	
Description	Indicates Old Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

OLDDISPVAL

Attribute	**Description**	
Name	OLDDISPVAL	
Datatype	String	
Description	Indicates Old Display Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NEWVAL

Attribute	**Description**	
Name	NEWVAL	
Datatype	String	
Description	Indicates New Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

NEWDISPVAL

Attribute	**Description**	
Name	NEWDISPVAL	
Datatype	String	
Description	Indicates New Display Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.40.2.LDContract-Auth-Req-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Auth-Details*
  - *XREF*
  - *FCCREF*
  - *Rekey-Details*
    - *CCY*
    - *AMT*
    - *VALDT*
    - *MATDT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a Auth request for LD Contract.This is the normal request which has Input only fields

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	Include Loans and deposits contract authorization IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Rekey-Details

Attribute	Description
Name	Rekey-Details
Datatype	
Description	Include ReKey type details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	Indicates value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.40.3.LDContract-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Auth-Details*
    - *XREF*
    - *FCCREF*
    - *ESN*
    - *EVENTCD*
    - *EVENTDT*
    - *INPUTBY*
    - *Rekey-Details*
      - *CCY*
      - *AMT*
      - *VALDT*
      - *MATDT*
    - *Contract-Ovd*
      - *OVDSN*
      - *MODULE*
      - *ERRCODE*
      - *PARAM*
      - *ONLAUTHID*
      - *REMARKS*

AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT
Contract-Change-Log
CHGSN
DTCHANGED
FLDCHANGED
FLDDESC
OLDVAL
OLDDISPVAL
NEWVAL
NEWDISPVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully Authorized in FLEXCUBE UBS

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	Include Loans and deposits contract authorization type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Flexcube Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{4}

TOP

EVENTDT

Attribute	Description
Name	EVENTDT
Datatype	Date
Description	Indicates Event Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	Indicates the Maker ID of the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Rekey-Details

Attribute	Description
Name	Rekey-Details

Datatype	
Description	Include Loans and Deposits ReKey fields type details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Include contract override type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	Number
Description	Indicates Override Sequence Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AUTHBY

Attribute	Description
Name	AUTHBY
Datatype	String
Description	Indicates the User id who has authorized the booked contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

AUTHDTSTAMP

Attribute	Description
Name	AUTHDTSTAMP
Datatype	Date
Description	Indicates date and stamp when the user has authorized the booked contract.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXTSTATUS

Attribute	Description
Name	TXTSTATUS

Datatype	String
Description	Indicates the Authorization status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

OVDSTATUS

Attribute	Description
Name	OVDSTATUS
Datatype	String
Description	Indicates the Overridden status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates whether the override is confirmed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Contract-Change-Log

Attribute	**Description**	
Name	Contract-Change-Log	
Datatype		
Description	Include Contract chnage log type details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGSN

Attribute	**Description**	
Name	CHGSN	
Datatype	Number	
Description	Indicates Change Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

DTCHANGED

Attribute	**Description**	
Name	DTCHANGED	
Datatype	String	
Description	Indicates Date Changed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

FLDCHANGED

Attribute	**Description**	
Name	FLDCHANGED	
Datatype	String	
Description	Indicates Field Changed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

OLDVAL

Attribute	Description
Name	OLDVAL
Datatype	String
Description	Indicates Old Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Display Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NEWVAL

Attribute	Description
Name	NEWVAL
Datatype	String
Description	Indicates New Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Display Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.4.LDContract-Auth-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Auth-Details-PK*
      - *XREF*
      - *FCCREF*
    - *Auth-Details*
      - *XREF*
      - *FCCREF*
      - *Rekey-Details*
        - *CCY*
        - *AMT*
        - *VALDT*
        - *MATDT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd gives the message format for detailing the primary information relating the LD Contract that has been successfully Authorized

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Auth-Details-PK

Attribute	Description
Name	Auth-Details-PK
Datatype	
Description	Include Loans and deposits contract authorization PK type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	Include Loans and deposits contract authorization IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Rekey-Details

Attribute	Description
Name	Rekey-Details
Datatype	
Description	Include ReKey type details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	Indicates value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.41.DeleteLDContract

Deletion of Loans and Deposits Contract

2.41.1.LDContract-Delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*
- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Deletion of LDContract. This request is a full screen request and includes the display fields

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	

Description	Include Loans and deposits contract master full type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK

Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String

Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	**Description**	
Name	DFLT_ACC_BRN	
Datatype	String	
Description	Indicates Default Settlement Credit Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	**Description**	
Name	DRSETLAC	
Datatype	String	
Description	Indicates Debit Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	**Description**	
Name	DRSETLACBR	
Datatype	String	
Description	Indicates Debit Settlement Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS

Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description	
Name	TAXSCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 6 minLength: 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxInclusive: 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description
Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

SGENREQD

Attribute	Description	
Name	SGENREQD	
Datatype	String	
Description	Indicates SGEN Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

DEMANDBASIS

Attribute	Description	
Name	DEMANDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEPAYSCH

Attribute	Description	
Name	MOVEPAYSCH	
Datatype	String	
Description	Indicates Move Payment Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String

Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description

Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY

Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String

Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP

Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT
Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15 minLength: 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6

Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4

Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description

Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	Description	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Clearing-Details

Attribute	**Description**	
Name	Clearing-Details	
Datatype		
Description	Includes Clearing details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description

Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description

Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	Restrictions: maxLength; Description: 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description

Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3LBL3

Attribute	Description	
Name	TXNMIS3LBL3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4LBL4

Attribute	Description	
Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	**Description**	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	**Description**

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>0,1,2,3,4,5,6,7,8,9,-1,-2</td></tr></table>

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**	
Name	INTDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>totalDigits</td><td>10</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.41.2.LDContract-Delete-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Deletion of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Include Loans and deposits contract master IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description

Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date

Description	Indicate Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS7LBL7

Attribute	**Description**	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	**Description**	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS9LBL9

Attribute	**Description**	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	**Description**
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNITREF

Attribute	**Description**	
Name	UNITREF	
Datatype	String	
Description	Indicates the Unit Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BKDATE

Attribute	**Description**
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description	Indicates the Effective date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	Description	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	Description	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	Description	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.41.3.LDContract-Delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- CONVPAIDAMT
- Relationship-Linkage
  - DESCP
  - CUSTOMER
  - RELATIONSHIP
  - INHERIT
- Brokerage-Master
  - FCCREF
  - ESN
  - BROKER
  - BRKAMT
  - BRKCCY
  - RULE
  - DSCACR
  - BRKNAM
  - RULEDESC
  - Brokerage-Details
    - BOOKCCY
    - BKMTHD
    - BOOKAMT
    - LIQSTAT
    - LREFNO
- Advice-Details
  - MSGTYPE
  - PARTYID
  - MEDIUM
  - SUPPRESS
  - PRIORITY
  - CHGREQ
- Settlement-Split-Master
  - SNO
  - SPAMTTG
  - AMT
  - BRN
  - ACCCY
  - ACC
  - EXRATE
- Contract-Schedules
  - SCOMP
  - SCHD_TYPE
  - FREQ
  - FREQ_UNIT
  - LCYEQINDLN
  - STDT

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Include Loans and deposits contract master full type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTC_DAYS

Attribute	Description	
Name	NOTC_DAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	Description	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	Description	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHMOVEACROSSMNTH

Attribute	**Description**	
Name	MSCHMOVEACROSSMNTH	
Datatype	String	
Description	Indicates Move Across Month on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHIGHOL

Attribute	**Description**	
Name	MSCHIGHOL	
Datatype	String	
Description	Indicates Ignore Holidays on Schedule Movement	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

LNSTMTTYPE

Attribute	**Description**	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicates Type None : N Detailed : D Summary : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MAT_TYPE

Attribute	**Description**
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	**Description**	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	**Description**	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS6

Attribute	**Description**

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	Description	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	Description	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	Description	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REFRATE

Attribute	Description	
Name	REFRATE	
Datatype	Number	
Description	Indicates Refinance Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	11

TOP

Rvrintrates

Attribute	Description	
Name	Rvrintrates	
Datatype		
Description	Includes Rollover Interest Rates details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DEFFROM

Attribute	Description	
Name	DEFFROM	
Datatype	String	
Description	Indicates Basis Product : P Contract : C User Rate : U	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Includes Interest basis details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.41.4.LDContract-Delete-Res-IOPK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Balance-Trnsfer-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*
- *PERIOD*
- *FINYR*
- *GLCODE*
- *CCY*
- *AMT*
- *EXRATE*

Mis-Change-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*

Mis-Amend

- *CONTREF*
- *RTYPE*
- *RCODE*
- *SPD*

Refinance-Rate

- *UNITREF*
- *BKDATE*
- *EFFDT*
- *REFRT*

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

Contract_Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*

- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*

- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*

AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for deleting the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Include Loans and deposits contract master PK type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Include Loans and deposits contract master IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description	
Name	LIQODSCH	
Datatype	String	
Description	Indicate Liquidate Od Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LNSTMTCYC

Attribute	Description	
Name	LNSTMTCYC	
Datatype	String	
Description	Indicate Loan Statement Cycle	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicate loan statement type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MVACRMTH

Attribute	Description	
Name	MVACRMTH	
Datatype	String	
Description	Indicate Move Across Months Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	4
minLength	1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates the Supplement Identification	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PYRIDFR

Attribute	Description	
Name	PYRIDFR	
Datatype	String	
Description	Indicates the Payer Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PYMTTYPE

Attribute	Description	
Name	PYMTTYPE	
Datatype	String	
Description	Indicates the Payment type	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.ModifyLDContract

Modification of Loans and Deposits Contract

2.42.1.LDContract-Master-Modify-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Change-Log

- FLDDESC
- OLDISVAL
- NWDISVAL

Contract-Event-Log

- MAKERID
- MAKERSTAMP
- CHECKERID
- CHECKERSTAMP
- AUTHSTAT
- CONTSTAT
- REVR_MAKERID
- REVR_MAKERSTAMP
- REVR_CHECKERID
- REVR_CHECKERSTAMP
- REVR_AUTHSTAT
- REVR_CONTSTAT

Schedule-Dates

- ESN
- DTOFCHNG
- EVNTCD

Schedule-Summ

- DUEDT
- SUBAMT
- CCYAMTDUE
- DISAMTDUE
- DISAMTSETTL
- DISADJAMT
- Schedule-Details
  - SCOMP
  - AMTDUE
  - CCYAMTDUE
  - AMTSET
  - ADJAMT
  - Amount-Settle
    - PAIDDT
    - CCYSETTL
    - LCYEQSET
    - AMTSETTL

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request to Modify the LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	

Description	Include Loans and deposits contract master full type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK

Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String

Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	**Description**	
Name	DFLT_ACC_BRN	
Datatype	String	
Description	Indicates Default Settlement Credit Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	**Description**	
Name	DRSETLAC	
Datatype	String	
Description	Indicates Debit Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	**Description**	
Name	DRSETLACBR	
Datatype	String	
Description	Indicates Debit Settlement Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS

Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLOVRIND

Attribute	Description
Name	ROLLOVRIND
Datatype	String
Description	Indicates Rollover Details Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicates Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

SUBSIDYPER

Attribute	Description
Name	SUBSIDYPER
Datatype	Number
Description	Indicates Subsidy Percentage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 2 totalDigits / 4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description
Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

SGENREQD

Attribute	Description	
Name	SGENREQD	
Datatype	String	
Description	Indicates SGEN Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

DEMANDBASIS

Attribute	Description	
Name	DEMANDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEPAYSCH

Attribute	Description	
Name	MOVEPAYSCH	
Datatype	String	
Description	Indicates Move Payment Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String

Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description

Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY

Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String

Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP

Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT
Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15 minLength: 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6

Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4

Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description

Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP5

Attribute	Description	
Name	RCVR_CORRESP5	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP6

Attribute	Description	
Name	RCVR_CORRESP6	
Datatype	String	
Description	Country to which the receiver correspondent belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates the receiver.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	Description	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description

Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description

Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description

Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Includes Interest basis details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>0,1,2,3,4,5,6,7,8,9,-1,-2</td></tr></table>

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>totalDigits</td><td>10</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.42.2.LDContract-Modify-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request to Modify the LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	

Description	This Includes the LD Contract Input Only Details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,N,C</td></tr></table>

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description
Name	BRKCONFSTAT
Datatype	String
Description	Indicate broker confirmation status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description	
Name	AUTPROVREQD	
Datatype	String	
Description	Indicates Auto Provisioning required N:no Y:yes	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CASCADESCHD

Attribute	Description	
Name	CASCADESCHD	
Datatype	String	
Description	Indicate Cascade Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDTAXCAP

Attribute	Description	
Name	DEDTAXCAP	
Datatype	String	
Description	Indicates Deduct Tax on Capitalisatio	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DFLTSETTCCY

Attribute	Description	
Name	DFLTSETTCCY	
Datatype	String	
Description	Indicates dafault settlement currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

DRSETLAC

Attribute	Description	
Name	DRSETLAC	
Datatype	String	
Description	Indicate Debit sett Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description	
Name	DRSETLACBR	
Datatype	String	
Description	Indicate Debit sett Account branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description	
Name	DRSETLCCY	
Datatype	String	
Description	Indicate debit settlement surrency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EXPCAT

Attribute	Description	
Name	EXPCAT	
Datatype	String	
Description	Indicate Exposure Category	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description	
Name	LIQODSCH	
Datatype	String	
Description	Indicate Liquidate Od Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LNSTMTCYC

Attribute	Description	
Name	LNSTMTCYC	
Datatype	String	
Description	Indicate Loan Statement Cycle	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicate loan statement type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MVACRMTH

Attribute	Description	
Name	MVACRMTH	
Datatype	String	
Description	Indicate Move Across Months Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description

Name	TRCKRECVALIQ
Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates the Supplement Identification	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PYRIDFR

Attribute	Description	
Name	PYRIDFR	
Datatype	String	
Description	Indicates the Payer Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PYMTTYPE

Attribute	Description	
Name	PYMTTYPE	
Datatype	String	
Description	Indicates the Payment type	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRRES4

Attribute	Description	
Name	REPRRES4	
Datatype	String	
Description	Indicates the Repair Reason 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description	
Name	ADDIDFR	
Datatype	String	
Description	Indicates the Additional Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS7LBL7

Attribute	**Description**	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	**Description**	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS9LBL9

Attribute	**Description**	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	**Description**
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates the Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQDODSCHD

Attribute	Description	
Name	LIQDODSCHD	
Datatype	String	
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SCHDBASIS

Attribute	Description	
Name	SCHDBASIS	
Datatype	String	
Description	Indicates Schedule Basis Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

UPDATEUTIL

Attribute	Description	
Name	UPDATEUTIL	
Datatype	String	
Description	Indicates Update Limits Utilisation Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.42.3.LDContract-Modify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
- *Advice-Details*
  - *MSGTYPE*
  - *PARTYID*
  - *MEDIUM*
  - *SUPPRESS*
  - *PRIORITY*
  - *CHGREQ*
- *Settlement-Split-Master*
  - *SNO*
  - *SPAMTTG*
  - *AMT*
  - *BRN*
  - *ACCCY*
  - *ACC*
  - *EXRATE*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Modification of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	This Includes Modify LD Contract Full Details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description	
Name	SRC	
Datatype	String	
Description	Indicates Source	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ALLOWPREPAY

Attribute	Description	
Name	ALLOWPREPAY	
Datatype	String	
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ANNLOAN

Attribute	Description	
Name	ANNLOAN	
Datatype	String	
Description	Indicates Annuity Loan Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

AMTINRPTCCY

Attribute	**Description**	
Name	AMTINRPTCCY	
Datatype	String	
Description	Indicates Amount in Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RPTCCY

Attribute	**Description**	
Name	RPTCCY	
Datatype	String	
Description	Indicates Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

OSBALRPTCCY

Attribute	**Description**	
Name	OSBALRPTCCY	
Datatype	String	
Description	Indicates Outstanding Balance in Report Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

IGRHOLDYS

Attribute	**Description**
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	Description	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	Description	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Regulatory Report 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	**Description**	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	**Description**

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>0,1,2,3,4,5,6,7,8,9,-1,-2</td></tr></table>

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.4.LDContract-Modify-Res-IOPK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-PK*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*

- STDT
- NO_OF_SCHD
- AMT

Contract_Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Holiday-Currencies

- CCY
- CCYDESC

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY
  - BKMTHD
  - BOOKAMT
  - LIQSTAT
  - LREFNO

Advice-Details

- MSGTYPE

- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*

AMT

ROLSTENOR

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format to Modify the primary information relating the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-PK

Attribute	Description
Name	Contract-Master-PK
Datatype	
Description	Include Loans and deposits contract master PK type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Include Loans and deposits contract master IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions**: pattern; **Description**: [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: length; **Description**: 3 **Restrictions**: pattern; **Description**: [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: length; **Description**: 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	Description	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	Description	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	Description	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLMATDT

Attribute	Description	
Name	ROLLMATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ROLLNOTDAYS

Attribute	Description	
Name	ROLLNOTDAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ROLLICCFFROM

Attribute	Description	
Name	ROLLICCFFROM	
Datatype	String	
Description	Indicates ICCF Rollover Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.CreateLDContract

Input of Loans and Deposits Contract

2.43.1.LDContract-Master-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Change-Log

- FLDDESC
- OLDISVAL
- NWDISVAL

Contract-Event-Log

- MAKERID
- MAKERSTAMP
- CHECKERID
- CHECKERSTAMP
- AUTHSTAT
- CONTSTAT
- REVR_MAKERID
- REVR_MAKERSTAMP
- REVR_CHECKERID
- REVR_CHECKERSTAMP
- REVR_AUTHSTAT
- REVR_CONTSTAT

Schedule-Dates

- ESN
- DTOFCHNG
- EVNTCD

Schedule-Summ

- DUEDT
- SUBAMT
- CCYAMTDUE
- DISAMTDUE
- DISAMTSETTL
- DISADJAMT
- Schedule-Details
  - SCOMP
  - AMTDUE
  - CCYAMTDUE
  - AMTSET
  - ADJAMT
  - Amount-Settle
    - PAIDDT
    - CCYSETTL
    - LCYEQSET
    - AMTSETTL

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a request for Creation of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	

Description	Include Loans and deposits contract master full type details

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTSTAT

Attribute	Description	
Name	CONTSTAT	
Datatype	String	
Description	Indciates Contract Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UREF

Attribute	Description	
Name	UREF	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK

Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String

Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	**Description**	
Name	DFLT_ACC_BRN	
Datatype	String	
Description	Indicates Default Settlement Credit Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	**Description**	
Name	DRSETLAC	
Datatype	String	
Description	Indicates Debit Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	**Description**	
Name	DRSETLACBR	
Datatype	String	
Description	Indicates Debit Settlement Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS

Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description	
Name	TAXSCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>9999</td></tr></table>

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description
Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VERIFUND

Attribute	**Description**	
Name	VERIFUND	
Datatype	String	
Description	Indicates Verify Funds	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PARTPAYMLIQ

Attribute	**Description**	
Name	PARTPAYMLIQ	
Datatype	String	
Description	Indicates Partial Manual Liquidation Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

SUBSALLOW

Attribute	**Description**	
Name	SUBSALLOW	
Datatype	String	
Description	Indicates Subsidy Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

USERDEFSCHED

Attribute	**Description**
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

SGENREQD

Attribute	Description	
Name	SGENREQD	
Datatype	String	
Description	Indicates SGEN Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

DEMANDBASIS

Attribute	Description	
Name	DEMANDBASIS	
Datatype	String	
Description	Indicates Demand Basis SGEN : S Billing Notice : B	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEPAYSCH

Attribute	Description	
Name	MOVEPAYSCH	
Datatype	String	
Description	Indicates Move Payment Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String

Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description

Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY

Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String

Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHIGHOL

Attribute	**Description**	
Name	MSCHIGHOL	
Datatype	String	
Description	Indicates Ignore Holidays on Schedule Movement	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

LNSTMTTYPE

Attribute	**Description**	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicates Type None : N Detailed : D Summary : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MAT_TYPE

Attribute	**Description**	
Name	MAT_TYPE	
Datatype	String	
Description	Indicates Maturity Type Fixed : F Notice : N Call : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

PRCCYTYP

Attribute	**Description**
Name	PRCCYTYP

Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT
Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15 minLength: 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6

Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4

Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description

Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Clearing-Details

Attribute	**Description**	
Name	Clearing-Details	
Datatype		
Description	Includes Clearing details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description

Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description

Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description

Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>totalDigits</td><td>10</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.43.2.LDContract-Master-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*
- *SNDR_ACC*
- *RCVR_ACC*
- *ULT_BKCD*
- *ADDINFO1*
- *ADDINFO2*
- *ADDINFO3*
- *ADDINFO4*
- *NIPPYR*
- *SUPPID*
- *PYRIDFR*
- *PYMTTYPE*
- *DLCLR*
- *NOFDCLR*
- *NOFCHK*
- *REPRRES1*
- *REPRRES2*
- *REPRRES3*
- *REPRRES4*
- *CDFDOC*
- *ADDIDFR*

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a request for Creation of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Include Loans and deposits contract master IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description

Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date

Description	Indicate Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates the Supplement Identification	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PYRIDFR

Attribute	Description	
Name	PYRIDFR	
Datatype	String	
Description	Indicates the Payer Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PYMTTYPE

Attribute	Description	
Name	PYMTTYPE	
Datatype	String	
Description	Indicates the Payment type	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS7LBL7

Attribute	**Description**	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	**Description**	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS9LBL9

Attribute	**Description**	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	**Description**
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.43.3.LDContract-Master-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC

Contract-Rollover

ROLLAMT

ROLLMATDT

ROLLNOTDAYS

UPDATEUTIL

LIQDODSCHD

DRAWDOWNNO

ROLLBY

ROLLINTST

ROLLMECH

ROLLMETHD

ROLLTYPE

ROLLAMTTYP

ROLLMATTYPE

ROLLICCFFROM

SCHDBASIS

TRESPLAMT

APPROLLTAX

NEWCOMPALL

ROLLMATDAYS

APPCHG

REFRATE

Rvrintrates

INTCOMP

DEFFROM

RATETYPE

INTBASIS

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Include Loans and deposits contract master full type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	**Description**	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	**Description**	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	**Description**	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTC_DAYS

Attribute	Description	
Name	NOTC_DAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	Description	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	Description	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	**Description**	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	**Description**

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**	
Name	INTDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxrule-Detail

Attribute	Description	
Name	Taxrule-Detail	
Datatype		
Description	Specifies Tax Rule Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXAMT

Attribute	Description	
Name	TAXAMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLMETHD

Attribute	Description	
Name	ROLLMETHD	
Datatype	String	
Description	Indicates Rollover Method	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates rollover type Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.4.LDContract-Master-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*

- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*

- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*

AMT

ROLSTENOR

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for detailing the primary information relating the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Include Loans and deposits contract master PK response type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Include Loans and deposits contract master IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	4
minLength	1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates the Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.44.QueryLDContract

Query of Loans and Deposits Contract

2.44.1.LDContract-Query-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*

LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP

UREF

PCREF

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*

XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6

RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1

INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3

REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER

- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*

- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*
  - *AMT*

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Query of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	This Includes LD Contract Master Full Details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,N,C</td></tr></table>

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description
Name	BRKCONFSTAT
Datatype	String
Description	Indicate broker confirmation status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 1

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT

Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ
Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicate Prov Currency Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicate User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PCREF

Attribute	Description
Name	PCREF
Datatype	String
Description	Indicate PC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Include Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	Description	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	Description	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String

Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	Description	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	Description	
Name	ORDER_CUST6	
Datatype	String	
Description	Country to which the ordering customer belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	Description	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	Description	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**	
Name	Settlement-Details	
Datatype		
Description	Include Settlement type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details

Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE

Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_CUSNM4

Attribute	Description	
Name	SNDR_CUSNM4	
Datatype	String	
Description	Indicates the Sender Information 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM1

Attribute	Description	
Name	RCVR_CUSNM1	
Datatype	String	
Description	Indicates the Receiver Name 1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM2

Attribute	Description	
Name	RCVR_CUSNM2	
Datatype	String	
Description	Indicates the Receiver Name 2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM3

Attribute	Description	
Name	RCVR_CUSNM3	
Datatype	String	
Description	Indicates the Receiver Name 3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVR_CUSNM4

Attribute	Description	
Name	RCVR_CUSNM4	
Datatype	String	
Description	Indicates the Receiver Name 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDINFO2

Attribute	Description

Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String

Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3

Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5

Attribute	Description	
Name	COMPMIS5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description

Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
fractionDigits	15
minInclusive	0
totalDigits	26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDF type Details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCREQ

Attribute	**Description**	
Name	ACCREQ	
Datatype	String	
Description	Indicates the Accrual required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CHGDESC

Attribute	**Description**	
Name	CHGDESC	
Datatype	String	
Description	The Charge Component Code description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Include charge liquidation type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main

Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description

Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M

TOP

RTCALCTYP

Attribute	**Description**	
Name	RTCALCTYP	
Datatype	String	
Description	Indicates the Interest Rate Calculation type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	**Description**	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

UNT

Attribute	**Description**	
Name	UNT	
Datatype	String	
Description	Indicates the Unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	Number	
Description	Indicates the No Of Units.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description

Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_OF_SCHD

Attribute	**Description**	
Name	NO_OF_SCHD	
Datatype	Number	
Description	Indicates the No of Schedules.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

Contract_Linkages

Attribute	**Description**	
Name	Contract_Linkages	
Datatype		
Description	Include contract linkages type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LINK_REF

Attribute	**Description**	
Name	LINK_REF	
Datatype	String	
Description	Indicates the Link Reference No.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>1</td></tr></table>

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr></table>

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

Contract-Rollover

Attribute	Description	
Name	Contract-Rollover	
Datatype		
Description	Include contract rollover type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates Roll Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROLLMATTYPE

Attribute	Description	
Name	ROLLMATTYPE	
Datatype	String	
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLMATDT

Attribute	Description	
Name	ROLLMATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ROLLNOTDAYS

Attribute	Description	
Name	ROLLNOTDAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ROLLICCFFROM

Attribute	Description	
Name	ROLLICCFFROM	
Datatype	String	
Description	Indicates ICCF Rollover Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String

Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.44.2.LDContract-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*
- *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC

Contract-Rollover

ROLLAMT

ROLLMATDT

ROLLNOTDAYS

UPDATEUTIL

LIQDODSCHD

DRAWDOWNNO

ROLLBY

ROLLINTST

ROLLMECH

ROLLMETHD

ROLLTYPE

ROLLAMTTYP

ROLLMATTYPE

ROLLICCFFROM

SCHDBASIS

TRESPLAMT

APPROLLTAX

NEWCOMPALL

ROLLMATDAYS

APPCHG

REFRATE

Rvrintrates

INTCOMP

DEFFROM

RATETYPE

INTBASIS

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	This Includes the LD Contract Full Details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	Description	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	Description	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description	
Name	SRC	
Datatype	String	
Description	Indicates Source	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ALLOWPREPAY

Attribute	Description	
Name	ALLOWPREPAY	
Datatype	String	
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ANNLOAN

Attribute	Description	
Name	ANNLOAN	
Datatype	String	
Description	Indicates Annuity Loan Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTC_DAYS

Attribute	Description	
Name	NOTC_DAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ORGL_STDT

Attribute	Description	
Name	ORGL_STDT	
Datatype	Date	
Description	Indicates Original Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARFCCREF

Attribute	Description	
Name	PARFCCREF	
Datatype	String	
Description	Indicates Parent Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description	
Name	PAREXTREFNO	
Datatype	String	
Description	Indicates Parent External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description
Name	TAXSCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	Description	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	Description	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>0,1,2,3,4,5,6,7,8,9,-1,-2</td></tr></table>

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**	
Name	INTDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLMETHD

Attribute	Description	
Name	ROLLMETHD	
Datatype	String	
Description	Indicates Rollover Method	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	minLength	1

TOP

ROLLTYPE

Attribute	Description	
Name	ROLLTYPE	
Datatype	String	
Description	Indicates rollover type Auto : A Manual : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ROLLAMTTYP

Attribute	Description	
Name	ROLLAMTTYP	
Datatype	String	
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Includes Interest basis details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.ReverseLDContract

Reversal of Loans and Deposits Contract

2.45.1.LDContract-Reverse-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE

Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC

Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT

ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT

Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Change-Log

- FLDDESC
- OLDISVAL
- NWDISVAL

Contract-Event-Log

- MAKERID
- MAKERSTAMP
- CHECKERID
- CHECKERSTAMP
- AUTHSTAT
- CONTSTAT
- REVR_MAKERID
- REVR_MAKERSTAMP
- REVR_CHECKERID
- REVR_CHECKERSTAMP
- REVR_AUTHSTAT
- REVR_CONTSTAT

Schedule-Dates

- ESN
- DTOFCHNG
- EVNTCD

Schedule-Summ

- DUEDT
- SUBAMT
- CCYAMTDUE
- DISAMTDUE
- DISAMTSETTL
- DISADJAMT
- Schedule-Details
  - SCOMP
  - AMTDUE
  - CCYAMTDUE
  - AMTSET
  - ADJAMT
  - Amount-Settle
    - PAIDDT
    - CCYSETTL
    - LCYEQSET
    - AMTSETTL

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Reversal of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	

Description	This Indicates LD Contract Master Full Details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK

Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String

Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	**Description**	
Name	DFLT_ACC_BRN	
Datatype	String	
Description	Indicates Default Settlement Credit Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	**Description**	
Name	DRSETLAC	
Datatype	String	
Description	Indicates Debit Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	**Description**	
Name	DRSETLACBR	
Datatype	String	
Description	Indicates Debit Settlement Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INTPERBAS

Attribute	**Description**	
Name	INTPERBAS	
Datatype	String	
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

INTREFNO

Attribute	**Description**	
Name	INTREFNO	
Datatype	String	
Description	Indicates External Interface Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LASTAVLDT

Attribute	**Description**	
Name	LASTAVLDT	
Datatype	Date	
Description	Indicates Last Available Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYEQINDLN

Attribute	**Description**
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS

Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description	
Name	TAXSCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 6 minLength: 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxInclusive: 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description
Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String

Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description

Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY

Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String

Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP

Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT
Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6

Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4

Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description

Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	Description	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Clearing-Details

Attribute	**Description**	
Name	Clearing-Details	
Datatype		
Description	Includes Clearing details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description

Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description

Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description

Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>totalDigits</td><td>10</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.45.2.LDContract-Reverse-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Reverse of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	

Description	This Includes the LD Contract Input Only Details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,N,C</td></tr></table>

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description
Name	BRKCONFSTAT
Datatype	String
Description	Indicate broker confirmation status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description	
Name	AUTPROVREQD	
Datatype	String	
Description	Indicates Auto Provisioning required N:no Y:yes	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CASCADESCHD

Attribute	Description	
Name	CASCADESCHD	
Datatype	String	
Description	Indicate Cascade Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDTAXCAP

Attribute	Description	
Name	DEDTAXCAP	
Datatype	String	
Description	Indicates Deduct Tax on Capitalisatio	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DFLTSETTCCY

Attribute	Description	
Name	DFLTSETTCCY	
Datatype	String	
Description	Indicates dafault settlement currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description	
Name	LIQODSCH	
Datatype	String	
Description	Indicate Liquidate Od Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LNSTMTCYC

Attribute	Description	
Name	LNSTMTCYC	
Datatype	String	
Description	Indicate Loan Statement Cycle	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicate loan statement type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MVACRMTH

Attribute	Description	
Name	MVACRMTH	
Datatype	String	
Description	Indicate Move Across Months Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description

Name	TRCKRECVALIQ
Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates the Supplement Identification	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PYRIDFR

Attribute	Description	
Name	PYRIDFR	
Datatype	String	
Description	Indicates the Payer Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PYMTTYPE

Attribute	Description	
Name	PYMTTYPE	
Datatype	String	
Description	Indicates the Payment type	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRRES4

Attribute	Description	
Name	REPRRES4	
Datatype	String	
Description	Indicates the Repair Reason 4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description	
Name	ADDIDFR	
Datatype	String	
Description	Indicates the Additional Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS7LBL7

Attribute	**Description**	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	**Description**	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS9LBL9

Attribute	**Description**	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	**Description**
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQDODSCHD

Attribute	Description	
Name	LIQDODSCHD	
Datatype	String	
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SCHDBASIS

Attribute	Description	
Name	SCHDBASIS	
Datatype	String	
Description	Indicates Schedule Basis Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

UPDATEUTIL

Attribute	Description	
Name	UPDATEUTIL	
Datatype	String	
Description	Indicates Update Limits Utilisation Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.45.3.LDContract-Reverse-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
- *Advice-Details*
  - *MSGTYPE*
  - *PARTYID*
  - *MEDIUM*
  - *SUPPRESS*
  - *PRIORITY*
  - *CHGREQ*
- *Settlement-Split-Master*
  - *SNO*
  - *SPAMTTG*
  - *AMT*
  - *BRN*
  - *ACCCY*
  - *ACC*
  - *EXRATE*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

- CCYDESC
- Contract-Rollover
  - ROLLAMT
  - ROLLMATDT
  - ROLLNOTDAYS
  - UPDATEUTIL
  - LIQDODSCHD
  - DRAWDOWNNO
  - ROLLBY
  - ROLLINTST
  - ROLLMECH
  - ROLLMETHD
  - ROLLTYPE
  - ROLLAMTTYP
  - ROLLMATTYPE
  - ROLLICCFFROM
  - SCHDBASIS
  - TRESPLAMT
  - APPROLLTAX
  - NEWCOMPALL
  - ROLLMATDAYS
  - APPCHG
  - REFRATE
  - Rvrintrates
    - INTCOMP
    - DEFFROM
    - RATETYPE
    - INTBASIS
  - INTBAS
    - INTCOMP
    - ROLLOIFROM
    - RATETYPE
    - RATEUSCD
    - INTRATE
    - INTBASIS
    - RATECD
    - SPREAD
    - MARGIN
    - AMT
    - ROLSTENOR
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	This Includes the LD Contract Full Details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	**Description**	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	**Description**	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	**Description**	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description	
Name	TAXSCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6
	minLength	1

TOP

UDSTAT

Attribute	Description	
Name	UDSTAT	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

USERINPUTMATDT

Attribute	Description	
Name	USERINPUTMATDT	
Datatype	Date	
Description	Indicates User Input Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHMOVEACROSSMNTH

Attribute	**Description**	
Name	MSCHMOVEACROSSMNTH	
Datatype	String	
Description	Indicates Move Across Month on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHIGHOL

Attribute	**Description**	
Name	MSCHIGHOL	
Datatype	String	
Description	Indicates Ignore Holidays on Schedule Movement	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

LNSTMTTYPE

Attribute	**Description**	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicates Type None : N Detailed : D Summary : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MAT_TYPE

Attribute	**Description**
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	**Description**	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	**Description**	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	1

TOP

RTGSNW

Attribute	Description	
Name	RTGSNW	
Datatype	String	
Description	Indicates Real Time Gross Settlement Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	Description	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	Description	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	Description	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Specifies The MIS Group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	**Description**	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	Description	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	Description	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	Description	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**	
Name	INTDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	Description	
Name	LCYEQINDLN	
Datatype	Number	
Description	Indicates Local Currency Equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Includes Interest basis details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 5 totalDigits: 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxInclusive: 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.4.LDContract-Reverse-Res-IOPK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-PK*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

Charge-Association

CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC

Charge-Liquidation

ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS

Interest-Main

INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

Contract_Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*

- *STDT*
- *NO_OF_SCHD*
- *AMT*

Contract_Linkages

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*

- PARTYID
- MEDIUM
- SUPPRESS
- PRIORITY
- CHGREQ

Settlement-Split-Master

- SNO
- SPAMTTG
- AMT
- BRN
- ACCCY
- ACC
- EXRATE

Contract-Rollover

- ROLLTYPE
- ROLLAMTTYP
- ROLLAMT
- LIQDODSCHD
- SCHDBASIS
- UPDATEUTIL
- ROLLMATTYPE
- ROLLMATDT
- ROLLNOTDAYS
- ROLLICCFFROM
- ROLLBY
- APPCHG
- APPROLLTAX
- TRESPLAMT
- REFRATE
- ROLLMATDAYS
- ROLLMECH
- ROLLMETHD
- DRAWDOWNNO
- NEWCOMPALL
- INTBAS
  - INTCOMP
  - ROLLOIFROM
  - RATETYPE
  - RATEUSCD
  - INTRATE
  - INTBASIS
  - RATECD
  - SPREAD
  - MARGIN

AMT
ROLSTENOR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for detailing the primary information relating the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-PK

Attribute	Description
Name	Contract-Master-PK
Datatype	
Description	Include Loans and deposits contract master PK type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Include Loans and deposits contract master IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicate Debit sett Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicate Debit sett Account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description
Name	DRSETLCCY
Datatype	String
Description	Indicate debit settlement surrency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicate Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQODSCH

Attribute	Description
Name	LIQODSCH
Datatype	String
Description	Indicate Liquidate Od Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicate Loan Statement Cycle
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicate loan statement type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicate Move Across Months Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	**Description**	
Name	ACC_INST3	
Datatype	String	
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST4

Attribute	**Description**
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS7LBL7

Attribute	**Description**	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	**Description**	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS9LBL9

Attribute	**Description**	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	**Description**
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	1

TOP

LINK_SRNO

Attribute	Description	
Name	LINK_SRNO	
Datatype	String	
Description	Indicates the Link-serial Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the amount block number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKEFFDT

Attribute	Description	
Name	LINKEFFDT	
Datatype	String	
Description	Indicates the link effective date.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description	
Name	CONVPAIDAMT	
Datatype	String	
Description	Indicates the converted amount paid.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	**Description**	
Name	Brokerage-Details	
Datatype		
Description	Indicates Brokerage details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQDODSCHD

Attribute	Description	
Name	LIQDODSCHD	
Datatype	String	
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SCHDBASIS

Attribute	Description	
Name	SCHDBASIS	
Datatype	String	
Description	Indicates Schedule Basis Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

UPDATEUTIL

Attribute	Description	
Name	UPDATEUTIL	
Datatype	String	
Description	Indicates Update Limits Utilisation Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLMATDT

Attribute	Description	
Name	ROLLMATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ROLLNOTDAYS

Attribute	Description	
Name	ROLLNOTDAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ROLLICCFFROM

Attribute	Description	
Name	ROLLICCFFROM	
Datatype	String	
Description	Indicates ICCF Rollover Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.RolloverLDContract

Rollover of Loans and Deposits Contract

2.46.1.LDContract-Rollover-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*

BOOKDT
BRK
CLUSID
CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY

OSBALRPTCCY
IGRHOLDYS
HOLDYCCY
CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY

RVNCCY
RVNIGHOL
MAXRATEREVPRD
MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2

RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT

EXRATE

Mis-Change-Log

BRN

REFNO

MIS

TXNDT

OLDMIS

NEWMIS

Mis-Amend

CONTREF

RTYPE

RCODE

SPD

Refinance-Rate

UNITREF

BKDATE

EFFDT

REFRT

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC
DENOBASIS
BASIS366
NOINTPRD
MINSPREAD
MAXSPREAD
MARGIN
INTDESC
INTCMPDESC
EFFCTIVERATE
Interest-Details
VALDT
TXNDT

INTAMT
INTCCY
ESN
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID

- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*

- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Change-Log

- FLDDESC
- OLDISVAL
- NWDISVAL

Contract-Event-Log

- MAKERID
- MAKERSTAMP
- CHECKERID
- CHECKERSTAMP
- AUTHSTAT
- CONTSTAT
- REVR_MAKERID
- REVR_MAKERSTAMP
- REVR_CHECKERID
- REVR_CHECKERSTAMP
- REVR_AUTHSTAT
- REVR_CONTSTAT

Schedule-Dates

- ESN
- DTOFCHNG
- EVNTCD

Schedule-Summ

- DUEDT
- SUBAMT
- CCYAMTDUE
- DISAMTDUE
- DISAMTSETTL
- DISADJAMT
- Schedule-Details
  - SCOMP
  - AMTDUE
  - CCYAMTDUE
  - AMTSET
  - ADJAMT
  - Amount-Settle
    - PAIDDT
    - CCYSETTL
    - LCYEQSET
    - AMTSETTL

MAKERDT
Holiday-Currencies
CCY
CCYDESC
Contract-Rollover
ROLLAMT
ROLLMATDT
ROLLNOTDAYS
UPDATEUTIL
LIQDODSCHD
DRAWDOWNNO
ROLLBY
ROLLINTST
ROLLMECH
ROLLMETHD
ROLLTYPE
ROLLAMTTYP
ROLLMATTYPE
ROLLICCFFROM
SCHDBASIS
TRESPLAMT
APPROLLTAX
NEWCOMPALL
ROLLMATDAYS
APPCHG
REFRATE
Rvrintrates
INTCOMP
DEFFROM
RATETYPE
INTBASIS
INTBAS
INTCOMP
ROLLOIFROM
RATETYPE
RATEUSCD
INTRATE
INTBASIS
RATECD
SPREAD
MARGIN
AMT
ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Rollover of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	

Description	This Includes LD Contract Full Details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATEST_VERNO

Attribute	Description
Name	LATEST_VERNO
Datatype	Number
Description	Indicates Latest Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

REVCONREF

Attribute	Description
Name	REVCONREF
Datatype	String
Description	Indicates Reverse Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALLOWPREPAY

Attribute	Description
Name	ALLOWPREPAY
Datatype	String
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ANNLOAN

Attribute	Description
Name	ANNLOAN
Datatype	String
Description	Indicates Annuity Loan Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK

Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String

Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INTPERBAS

Attribute	Description	
Name	INTPERBAS	
Datatype	String	
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

INTREFNO

Attribute	Description	
Name	INTREFNO	
Datatype	String	
Description	Indicates External Interface Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LASTAVLDT

Attribute	Description	
Name	LASTAVLDT	
Datatype	Date	
Description	Indicates Last Available Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS

Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description
Name	ROLLOVRCNT
Datatype	Number
Description	Indicates Rollover Count
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description	
Name	TAXSCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 6 minLength: 1

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

USERINPUTMATDT

Attribute	Description
Name	USERINPUTMATDT
Datatype	Date
Description	Indicates User Input Maturity Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxInclusive: 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String
Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description
Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEREVSCH

Attribute	Description
Name	MOVEREVSCH
Datatype	String

Description	Indicates Move Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVECOMMREDNSCH

Attribute	Description
Name	MOVECOMMREDNSCH
Datatype	String
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEDISSCH

Attribute	Description
Name	MOVEDISSCH
Datatype	String
Description	Indicates Move Disburse Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RNDNGREQ

Attribute	Description
Name	RNDNGREQ
Datatype	String
Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description

Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY

Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String
Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String

Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP

Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNSCHDMOVE

Attribute	Description
Name	RVNSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHSCHDMOVE

Attribute	Description
Name	MSCHSCHDMOVE
Datatype	String
Description	Indicates Schedule Movement on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PRDSCHTYPE

Attribute	Description
Name	PRDSCHTYPE
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsytem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PURPOFSYND

Attribute	Description
Name	PURPOFSYND
Datatype	String
Description	Indicates Purpose Of Syndication
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description
Name	LATINTRAT
Datatype	Number
Description	Indicates Latest Interest effective rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15 minLength: 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST2

Attribute	**Description**	
Name	INT_REIM_INST2	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST3

Attribute	**Description**	
Name	INT_REIM_INST3	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST4

Attribute	**Description**	
Name	INT_REIM_INST4	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6

Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4

Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description

Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Clearing-Details

Attribute	**Description**	
Name	Clearing-Details	
Datatype		
Description	Includes Clearing details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description

Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description

Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description

Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**	
Name	GENRT	
Datatype	String	
Description	Indicates to Generate Data	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FRETXT1

Attribute	**Description**	
Name	FRETXT1	
Datatype	String	
Description	Indicates Free text 1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description	Indicates the event.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PKUPEVSQ

Attribute	Description	
Name	PKUPEVSQ	
Datatype	Number	
Description	Indicates the Pick Up Event Sequence of the Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**	
Name	INTDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINK_TYPE

Attribute	Description	
Name	LINK_TYPE	
Datatype	String	
Description	Indicates the link type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	Description	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	Description	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Includes Contract Rollover details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Rollover Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>totalDigits</td><td>10</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

TOP

2.46.2.LDContract-Rollover-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *BRN*
    - *PRD*
    - *CPTY*
    - *CPTYCONFSTAT*
    - *AMT*
    - *CCY*
    - *ORGL_STDT*
    - *TRNDT*
    - *VALDT*
    - *MAT_TYPE*
    - *NOTC_DAYS*
    - *DFLT_ACC*
    - *DFLT_ACC_BRN*
    - *LINE*
    - *DEALER*
    - *BRK*

BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS
PRCCYTYP
UREF
PCREF
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4

INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract_Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract_Linkages*

- *LINK_REF*
- *LINK_TYPE*
- *LINK_CCY*
- *LINK_AMT*
- *XRATE*
- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Holiday-Currencies

- *CCY*
- *CCYDESC*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*

CHGREQ

Settlement-Split-Master

SNO

SPAMTTG

AMT

BRN

ACCCY

ACC

EXRATE

Contract-Rollover

ROLLTYPE

ROLLAMTTYP

ROLLAMT

LIQDODSCHD

SCHDBASIS

UPDATEUTIL

ROLLMATTYPE

ROLLMATDT

ROLLNOTDAYS

ROLLICCFFROM

ROLLBY

APPCHG

APPROLLTAX

TRESPLAMT

REFRATE

ROLLMATDAYS

ROLLMECH

ROLLMETHD

DRAWDOWNNO

NEWCOMPALL

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the Flexcube has to send a request for Rollover of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	

Description	This Includes LD Contract Input Only Details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,N,C</td></tr></table>

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description
Name	BRKCONFSTAT
Datatype	String
Description	Indicate broker confirmation status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description	
Name	AUTPROVREQD	
Datatype	String	
Description	Indicates Auto Provisioning required N:no Y:yes	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CASCADESCHD

Attribute	Description	
Name	CASCADESCHD	
Datatype	String	
Description	Indicate Cascade Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEDTAXCAP

Attribute	Description	
Name	DEDTAXCAP	
Datatype	String	
Description	Indicates Deduct Tax on Capitalisatio	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DFLTSETTCCY

Attribute	Description	
Name	DFLTSETTCCY	
Datatype	String	
Description	Indicates dafault settlement currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

DRSETLAC

Attribute	Description	
Name	DRSETLAC	
Datatype	String	
Description	Indicate Debit sett Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description	
Name	DRSETLACBR	
Datatype	String	
Description	Indicate Debit sett Account branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description	
Name	DRSETLCCY	
Datatype	String	
Description	Indicate debit settlement surrency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EXPCAT

Attribute	Description	
Name	EXPCAT	
Datatype	String	
Description	Indicate Exposure Category	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOLMTH

Attribute	Description
Name	HOLMTH
Datatype	String
Description	Indicate Holiday Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicate Holiday Month flag Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IGHOL

Attribute	Description
Name	IGHOL
Datatype	String
Description	Indicates ignore holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBVSCH

Attribute	Description
Name	LIQBVSCH
Datatype	String
Description	Indicates Liquid Back Valued Schedules
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description	
Name	LIQODSCH	
Datatype	String	
Description	Indicate Liquidate Od Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LNSTMTCYC

Attribute	Description	
Name	LNSTMTCYC	
Datatype	String	
Description	Indicate Loan Statement Cycle	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicate loan statement type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MVACRMTH

Attribute	Description	
Name	MVACRMTH	
Datatype	String	
Description	Indicate Move Across Months Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description

Name	TRCKRECVALIQ
Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDINT

Attribute	Description
Name	VRFYFUNDINT
Datatype	String
Description	Indicate Verify Funds For Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPLTY

Attribute	Description
Name	VRFYFUNDPLTY
Datatype	String
Description	Indicate Verify Funds For Penalty amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VRFYFUNDPRIN

Attribute	Description
Name	VRFYFUNDPRIN
Datatype	String
Description	Indicate Verify Funds For Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	4
minLength	1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates the Supplement Identification	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PYRIDFR

Attribute	Description	
Name	PYRIDFR	
Datatype	String	
Description	Indicates the Payer Identifier	
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PYMTTYPE

Attribute	Description	
Name	PYMTTYPE	
Datatype	String	
Description	Indicates the Payment type	
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	**Description**	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	**Description**	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	**Description**	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

INTCMPDESC

Attribute	**Description**	
Name	INTCMPDESC	
Datatype	String	
Description	Indicates the interest Component description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicate value date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates the Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,N,C

TOP

ROLLMATDT

Attribute	Description	
Name	ROLLMATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ROLLNOTDAYS

Attribute	Description	
Name	ROLLNOTDAYS	
Datatype	String	
Description	Indicates Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ROLLICCFFROM

Attribute	Description	
Name	ROLLICCFFROM	
Datatype	String	
Description	Indicates ICCF Rollover Product : P Contract : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

2.46.3.LDContract-Rollover-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CONTSTAT*
    - *UREF*
    - *BRN*
    - *CPTYCONFSTAT*
    - *LATEST_VERNO*
    - *REVCONREF*
    - *SRC*
    - *ALLOWPREPAY*
    - *AMT*
    - *ANNLOAN*
    - *AUTPROVREQD*
    - *BAREF*
    - *BILLREFNO*
    - *BOOKDT*
    - *BRK*
    - *CLUSID*

CLUSSIZE
CONDERIVSTAT
CPTY
LINE
CCY
DEALER
DFLT_ACC
DFLT_ACC_BRN
DRSETLAC
DRSETLACBR
EXPCAT
INTPERBAS
INTREFNO
LASTAVLDT
LCYEQINDLN
LNSTMTCYC
MATDT
MULTICIF
NOTC_DAYS
ORGL_STDT
PARFCCREF
PAREXTREFNO
PRD
RELREF
TDESC
RFEXPAMT
ROLLOVRCNT
ROLLOVRIND
STMTDAY
SUBSIDYPER
TAXSCHEME
UDSTAT
USERINPUTMATDT
VALDT
VERNO
PAMTMETHOD
OUTBAL
PROTYPEDESC
PROVAMT
AMTINRPTCCY
RPTCCY
OSBALRPTCCY
IGRHOLDYS
HOLDYCCY

CASCADESCHD
VFYFUNDS
LIQBCKVALSCHD
DEDTAXCAP
HOLMTHFLG
MVACRMTH
NOTCREQD
TRKRECALIQ
TRKRECMLIQ
VERIFUNDPRIN
VERIFUNDINT
VERIFUND
PARTPAYMLIQ
SUBSALLOW
USERDEFSCHED
SGENREQD
DEMANDBASIS
MOVEPAYSCH
MOVEREVSCH
MOVECOMMREDNSCH
MOVEDISSCH
RNDNGREQ
CCYRNDRULE
CCYDECIMALS
CCYRNDUNIT
RVNCONSBRNHOL
MCONSBRNHOL
CONSBRNHOL
APLYFACLTYHOLCCY
APLYCONTHOLCCY
APLYLCLHOLCCY
CHKRATECDCCY
MSCHCCY
MSCHAPLYFACLTYHOLCCY
MSCHAPLYCONTHOLCCY
MSCHAPLYLCLHOLCCY
RVNCASCSCHD
RVNMOVEACROSSMNTH
RVNAPLYFACLTYHOLCCY
RVNAPLYCONTHOLCCY
RVNAPLYLCLHOLCCY
RVNCCY
RVNIGHOL
MAXRATEREVPRD

MSCHINDHOLTREAT
RVNINDHOLTREAT
MSCHMOVEACROSSMNTH
MSCHIGHOL
LNSTMTTYPE
MAT_TYPE
PRCCYTYP
ROLLALLW
AMORTYPE
PRINCLIQ
STACTL
REVCOMM
SCHDMOVE
RVNSCHDMOVE
MSCHSCHDMOVE
PRDSCHTYPE
SUBSYSTEMSTAT
PURPOFSYND
LATINTRAT
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Clearing-Details

- *FCCREF*
- *ESN*
- *AMTTAG*
- *BRNCD*
- *MSGTYPE*
- *CLGNW*
- *CRBNCD*
- *SNDR_CUSNM1*
- *SNDR_CUSNM2*
- *SNDR_CUSNM3*
- *SNDR_CUSNM4*
- *RCVR_CUSNM1*
- *RCVR_CUSNM2*
- *RCVR_CUSNM3*
- *RCVR_CUSNM4*
- *SNDR_RCVR_PRCNT*

- *SNDR_ACC*
- *RCVR_ACC*
- *ULT_BKCD*
- *ADDINFO1*
- *ADDINFO2*
- *ADDINFO3*
- *ADDINFO4*
- *NIPPYR*
- *SUPPID*
- *PYRIDFR*
- *PYMTTYPE*
- *DLCLR*
- *NOFDCLR*
- *NOFCHK*
- *REPRRES1*
- *REPRRES2*
- *REPRRES3*
- *REPRRES4*
- *CDFDOC*
- *ADDIDFR*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN

REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT

LQDSTS

Interest-Main

INTCOMP

VALDT

TXNDT

INTAMT

CHDAMDMNT

INTCCY

EVNT

ESN

PKUPEVSQ

INTBASIS

INTRATE

INTRATECODE

INTSPREAD

AQRDAMT

WAIVER

ACREQD

RTTYPE

MAXRRATE

MINRATE

RETENOR

BORLENIND

RTCALCTYP

CUSTMARG

UNT

NOUNIT

RTCDUSE

CONASDISC

DENOBASIS

BASIS366

NOINTPRD

MINSPREAD

MAXSPREAD

MARGIN

INTDESC

INTCMPDESC

EFFCTIVERATE

Interest-Details

VALDT

TXNDT

INTAMT

INTCCY

ESN

INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
RTTYPE
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
Taxdetails
TAXRULE
BASAMTTAG
COMPEVT
WAIVER
Taxrule-Detail
ESN
TAXAMT
TAXCCY
VALDT
COMPDT
ContractSchedules1
SCOMP
SCHD_TYPE
FREQ
FREQ_UNIT
LCYEQINDLN
STDT
NO_OF_SCHD
AMT
Contract_Linkages
LINK_REF
LINK_TYPE
LINK_CCY
LINK_AMT
XRATE
AVLAMT
CONV_LINK_AMT
LOAN_CCY
LINKBRANCH
LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT

- *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
- *Advice-Details*
  - *MSGTYPE*
  - *PARTYID*
  - *MEDIUM*
  - *SUPPRESS*
  - *PRIORITY*
  - *CHGREQ*
- *Settlement-Split-Master*
  - *SNO*
  - *SPAMTTG*
  - *AMT*
  - *BRN*
  - *ACCCY*
  - *ACC*
  - *EXRATE*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*

- *NO_OF_SCHD*
- *AMT*

Change-Log

- *FLDDESC*
- *OLDISVAL*
- *NWDISVAL*

Contract-Event-Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*
- *REVR_MAKERID*
- *REVR_MAKERSTAMP*
- *REVR_CHECKERID*
- *REVR_CHECKERSTAMP*
- *REVR_AUTHSTAT*
- *REVR_CONTSTAT*

Schedule-Dates

- *ESN*
- *DTOFCHNG*
- *EVNTCD*

Schedule-Summ

- *DUEDT*
- *SUBAMT*
- *CCYAMTDUE*
- *DISAMTDUE*
- *DISAMTSETTL*
- *DISADJAMT*
- *Schedule-Details*
  - *SCOMP*
  - *AMTDUE*
  - *CCYAMTDUE*
  - *AMTSET*
  - *ADJAMT*
  - *Amount-Settle*
    - *PAIDDT*
    - *CCYSETTL*
    - *LCYEQSET*
    - *AMTSETTL*
    - *MAKERDT*

Holiday-Currencies

- *CCY*

CCYDESC

Contract-Rollover

ROLLAMT

ROLLMATDT

ROLLNOTDAYS

UPDATEUTIL

LIQDODSCHD

DRAWDOWNNO

ROLLBY

ROLLINTST

ROLLMECH

ROLLMETHD

ROLLTYPE

ROLLAMTTYP

ROLLMATTYPE

ROLLICCFFROM

SCHDBASIS

TRESPLAMT

APPROLLTAX

NEWCOMPALL

ROLLMATDAYS

APPCHG

REFRATE

Rvrintrates

INTCOMP

DEFFROM

RATETYPE

INTBASIS

INTBAS

INTCOMP

ROLLOIFROM

RATETYPE

RATEUSCD

INTRATE

INTBASIS

RATECD

SPREAD

MARGIN

AMT

ROLSTENOR

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Rollover of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	This Includes Rollover Contract Master Full Details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CPTYCONFSTAT

Attribute	**Description**	
Name	CPTYCONFSTAT	
Datatype	String	
Description	Indicates Counterparty Confirm Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATEST_VERNO

Attribute	**Description**	
Name	LATEST_VERNO	
Datatype	Number	
Description	Indicates Latest Version Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

REVCONREF

Attribute	**Description**	
Name	REVCONREF	
Datatype	String	
Description	Indicates Reverse Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

SRC

Attribute	Description	
Name	SRC	
Datatype	String	
Description	Indicates Source	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ALLOWPREPAY

Attribute	Description	
Name	ALLOWPREPAY	
Datatype	String	
Description	Indicates Allow Prepayment of Interest Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ANNLOAN

Attribute	Description	
Name	ANNLOAN	
Datatype	String	
Description	Indicates Annuity Loan Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates BA Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	Indicates Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRK

Attribute	Description
Name	BRK
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CLUSID

Attribute	Description
Name	CLUSID
Datatype	String
Description	Indicates Cluster Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 1

TOP

CLUSSIZE

Attribute	Description
Name	CLUSSIZE
Datatype	Number
Description	Indicates Cluster Size
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONDERIVSTAT

Attribute	Description
Name	CONDERIVSTAT
Datatype	String
Description	Indicates Contract Derived Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counterparty
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicates Default Settlement Credit Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicates Default Settlement Credit Account Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

DRSETLAC

Attribute	Description
Name	DRSETLAC
Datatype	String
Description	Indicates Debit Settlement Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description
Name	DRSETLACBR
Datatype	String
Description	Indicates Debit Settlement Account Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	Indicates Exposure Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INTPERBAS

Attribute	Description
Name	INTPERBAS
Datatype	String
Description	Indicates Interest Period Basis Include Frm Dt : F Include To Dt : T Include Frm and To Dt : B Exclude Frm and To Dt : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,B,E

TOP

INTREFNO

Attribute	Description
Name	INTREFNO
Datatype	String
Description	Indicates External Interface Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LASTAVLDT

Attribute	Description
Name	LASTAVLDT
Datatype	Date
Description	Indicates Last Available Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LNSTMTCYC

Attribute	Description
Name	LNSTMTCYC
Datatype	String
Description	Indicates Loan Statement Cycle Annual : A Semi Annual : S Quarterly : Q Monthly : M Fortnightly : F Weekly : W Daily : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,Q,M,F,W,D

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MULTICIF

Attribute	Description
Name	MULTICIF
Datatype	String
Description	Indicates Mutiple CIF Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicates Original Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARFCCREF

Attribute	Description
Name	PARFCCREF
Datatype	String
Description	Indicates Parent Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

PAREXTREFNO

Attribute	Description
Name	PAREXTREFNO
Datatype	String
Description	Indicates Parent External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4

TOP

RELREF

Attribute	Description
Name	RELREF
Datatype	String
Description	Indicates Related Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicates Risk Free Exposure Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLOVRCNT

Attribute	Description	
Name	ROLLOVRCNT	
Datatype	Number	
Description	Indicates Rollover Count	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	9999

TOP

ROLLOVRIND

Attribute	Description	
Name	ROLLOVRIND	
Datatype	String	
Description	Indicates Rollover Details Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

STMTDAY

Attribute	Description	
Name	STMTDAY	
Datatype	Number	
Description	Indicates Statement Day	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxInclusive	99

TOP

SUBSIDYPER

Attribute	Description	
Name	SUBSIDYPER	
Datatype	Number	
Description	Indicates Subsidy Percentage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	2
	totalDigits	4

TOP

TAXSCHEME

Attribute	Description	
Name	TAXSCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6
	minLength	1

TOP

UDSTAT

Attribute	Description	
Name	UDSTAT	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

USERINPUTMATDT

Attribute	Description	
Name	USERINPUTMATDT	
Datatype	Date	
Description	Indicates User Input Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

PAMTMETHOD

Attribute	Description
Name	PAMTMETHOD
Datatype	String
Description	Indicates Payment Method Bearing : B Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OUTBAL

Attribute	Description
Name	OUTBAL
Datatype	Number
Description	Indicates Outstanding Principal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	Indicates Provision Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTINRPTCCY

Attribute	Description
Name	AMTINRPTCCY
Datatype	String
Description	Indicates Amount in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RPTCCY

Attribute	Description
Name	RPTCCY
Datatype	String
Description	Indicates Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

OSBALRPTCCY

Attribute	Description
Name	OSBALRPTCCY
Datatype	String
Description	Indicates Outstanding Balance in Report Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

IGRHOLDYS

Attribute	Description
Name	IGRHOLDYS
Datatype	String

Description	Indicates Ignore Holidays Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLDYCCY

Attribute	Description
Name	HOLDYCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicates Cascade Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VFYFUNDS

Attribute	Description
Name	VFYFUNDS
Datatype	String
Description	Indicates Verify Funds For Penalty Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQBCKVALSCHD

Attribute	Description

Name	LIQBCKVALSCHD
Datatype	String
Description	Indicates Liquidate Back Valued Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOLMTHFLG

Attribute	Description
Name	HOLMTHFLG
Datatype	String
Description	Indicates Holiday Month Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVACRMTH

Attribute	Description
Name	MVACRMTH
Datatype	String
Description	Indicates Move Across Months Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTCREQD

Attribute	Description
Name	NOTCREQD
Datatype	String
Description	Indicates Whether Notice is Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECALIQ

Attribute	Description
Name	TRKRECALIQ
Datatype	String
Description	Indicates Automatic Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRKRECMLIQ

Attribute	Description
Name	TRKRECMLIQ
Datatype	String
Description	Indicates Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDPRIN

Attribute	Description
Name	VERIFUNDPRIN
Datatype	String
Description	Indicates Verify Funds For Principal Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUNDINT

Attribute	Description
Name	VERIFUNDINT
Datatype	String
Description	Indicates Verify Funds For Interest Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VERIFUND

Attribute	Description
Name	VERIFUND
Datatype	String
Description	Indicates Verify Funds
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

PARTPAYMLIQ

Attribute	Description
Name	PARTPAYMLIQ
Datatype	String
Description	Indicates Partial Manual Liquidation Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SUBSALLOW

Attribute	Description
Name	SUBSALLOW
Datatype	String
Description	Indicates Subsidy Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 1

TOP

USERDEFSCHED

Attribute	Description
Name	USERDEFSCHED
Datatype	String
Description	Indicates User Defined Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

SGENREQD

Attribute	Description
Name	SGENREQD
Datatype	String
Description	Indicates SGEN Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

DEMANDBASIS

Attribute	Description
Name	DEMANDBASIS
Datatype	String
Description	Indicates Demand Basis SGEN : S Billing Notice : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MOVEPAYSCH

Attribute	Description
Name	MOVEPAYSCH
Datatype	String
Description	Indicates Move Payment Schedule Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEREVSCH

Attribute	**Description**	
Name	MOVEREVSCH	
Datatype	String	
Description	Indicates Move Revision Schedule Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVECOMMREDNSCH

Attribute	**Description**	
Name	MOVECOMMREDNSCH	
Datatype	String	
Description	Indicates Move Comm Redn Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MOVEDISSCH

Attribute	**Description**	
Name	MOVEDISSCH	
Datatype	String	
Description	Indicates Move Disburse Schedules Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RNDNGREQ

Attribute	**Description**
Name	RNDNGREQ
Datatype	String

Description	Indicates Rounding Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYRNDRULE

Attribute	Description
Name	CCYRNDRULE
Datatype	String
Description	Indicates Rounding Rule Truncate : T Up : U Down : D Round Near : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CCYDECIMALS

Attribute	Description
Name	CCYDECIMALS
Datatype	Number
Description	Indicates Currency Decimals
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CCYRNDUNIT

Attribute	Description
Name	CCYRNDUNIT
Datatype	Number
Description	Indicates Currency Round Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 7

TOP

RVNCONSBRNHOL

Attribute	Description
Name	RVNCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MCONSBRNHOL

Attribute	Description
Name	MCONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CONSBRNHOL

Attribute	Description
Name	CONSBRNHOL
Datatype	String
Description	Indicates Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYFACLTYHOLCCY

Attribute	Description
Name	APLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Currency Holiday Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYCONTHOLCCY

Attribute	Description
Name	APLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Consider Branch Holiday
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

APLYLCLHOLCCY

Attribute	Description
Name	APLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

CHKRATECDCCY

Attribute	Description
Name	CHKRATECDCCY
Datatype	String
Description	Indicates Rate Code Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHCCY

Attribute	Description
Name	MSCHCCY
Datatype	String
Description	Indicates Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYFACLTYHOLCCY

Attribute	Description
Name	MSCHAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYCONTHOLCCY

Attribute	Description
Name	MSCHAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHAPLYLCLHOLCCY

Attribute	Description
Name	MSCHAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNCASCSCHD

Attribute	Description
Name	RVNCASCSCHD
Datatype	String
Description	Indicates Cascade Schedules on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNMOVEACROSSMNTH

Attribute	Description
Name	RVNMOVEACROSSMNTH

Datatype	String
Description	Indicates Move Across Month on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNAPLYFACLTYHOLCCY

Attribute	Description
Name	RVNAPLYFACLTYHOLCCY
Datatype	String
Description	Indicates Apply Facility Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYCONTHOLCCY

Attribute	Description
Name	RVNAPLYCONTHOLCCY
Datatype	String
Description	Indicates Apply Contract Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNAPLYLCLHOLCCY

Attribute	Description
Name	RVNAPLYLCLHOLCCY
Datatype	String
Description	Indicates Apply Local Holiday Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RVNCCY

Attribute	Description
Name	RVNCCY
Datatype	String

Description	Indicates Currency on Rate Revision Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNIGHOL

Attribute	Description
Name	RVNIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Rate Revision Schedule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MAXRATEREVPRD

Attribute	Description
Name	MAXRATEREVPRD
Datatype	Number
Description	Indicates Maximum Rate Rev Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

MSCHINDHOLTREAT

Attribute	Description
Name	MSCHINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

RVNINDHOLTREAT

Attribute	Description
Name	RVNINDHOLTREAT
Datatype	String
Description	Indicates Independent Holiday on Rate Revision Schedule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHMOVEACROSSMNTH

Attribute	Description
Name	MSCHMOVEACROSSMNTH
Datatype	String
Description	Indicates Move Across Month on Maturity Date Schedule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

MSCHIGHOL

Attribute	Description
Name	MSCHIGHOL
Datatype	String
Description	Indicates Ignore Holidays on Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LNSTMTTYPE

Attribute	Description
Name	LNSTMTTYPE
Datatype	String
Description	Indicates Type None : N Detailed : D Summary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,D,S

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String

Description	Indicates Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

PRCCYTYP

Attribute	Description
Name	PRCCYTYP
Datatype	String
Description	Indicates Provisioning Currency Type Contract : C Local : L
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,L

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicates Rollover Yes : Y No : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMORTYPE

Attribute	Description
Name	AMORTYPE
Datatype	String
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,O

TOP

PRINCLIQ

Attribute	Description
Name	PRINCLIQ
Datatype	String
Description	Indicates Liquidation Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STACTL

Attribute	Description
Name	STACTL
Datatype	String
Description	Indicates Status Control Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

REVCOMM

Attribute	Description
Name	REVCOMM
Datatype	String
Description	Indicates Revolving Commitment Revolving : Y Non Revolving : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCHDMOVE

Attribute	Description
Name	SCHDMOVE
Datatype	String
Description	Indicates Schedule Movement Move Forward : F Move Backward : B

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

RVNSCHDMOVE

Attribute	**Description**	
Name	RVNSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Rate Revision Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

MSCHSCHDMOVE

Attribute	**Description**	
Name	MSCHSCHDMOVE	
Datatype	String	
Description	Indicates Schedule Movement on Maturity Date Schedule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

PRDSCHTYPE

Attribute	**Description**	
Name	PRDSCHTYPE	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsytem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PURPOFSYND

Attribute	Description	
Name	PURPOFSYND	
Datatype	String	
Description	Indicates Purpose Of Syndication	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LATINTRAT

Attribute	Description	
Name	LATINTRAT	
Datatype	Number	
Description	Indicates Latest Interest effective rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5

Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO

Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String

Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST5

Attribute	Description	
Name	INT_REIM_INST5	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST6

Attribute	Description	
Name	INT_REIM_INST6	
Datatype	String	
Description	Country to which the Intermediary remitter institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INTMEDRY1

Attribute	Description	
Name	INTMEDRY1	
Datatype	String	
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	**Description**	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	**Description**	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	**Description**

Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description

Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	**Description**	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	**Description**	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**
Name	AMTTAGDESC

Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG

Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String

Description	Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Includes Clearing details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description

Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Includes Balance Transfer Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS

Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR

Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS Amendment details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description

Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Includes Refinance details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	**Description**	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	Description	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	Description	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	Description	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Includes Interest Main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHDAMDMNT

Attribute	**Description**	
Name	CHDAMDMNT	
Datatype	String	
Description	Indicates whether the Interest can be Changed during Amendment or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description

Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EFFCTIVERATE

Attribute	**Description**	
Name	EFFCTIVERATE	
Datatype	Number	
Description	Indicates the Effective rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Interest-Details

Attribute	**Description**	
Name	Interest-Details	
Datatype		
Description	Indicates Interest details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC

Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPEVT

Attribute	Description
Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxrule-Detail

Attribute	Description	
Name	Taxrule-Detail	
Datatype		
Description	Specifies Tax Rule Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXAMT

Attribute	Description	
Name	TAXAMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

ContractSchedules1

Attribute	Description
Name	ContractSchedules1
Datatype	
Description	Includes Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Includes Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Includes Relationship Linkages details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Includes Brokerage Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	**Description**	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes Advice details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Includes Settlement Split Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNO

Attribute	**Description**	
Name	SNO	
Datatype	Number	
Description	Indicates the serial No.	
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

SPAMTTG

Attribute	**Description**	
Name	SPAMTTG	
Datatype	String	
Description	Indicates the Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Includes Contract Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN

Datatype	Number
Description	Indicates Local Currency Equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Includes Change Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OLDISVAL

Attribute	**Description**	
Name	OLDISVAL	
Datatype	String	
Description	Indicates Old Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

NWDISVAL

Attribute	**Description**	
Name	NWDISVAL	
Datatype	String	
Description	Indicates New Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Contract-Event-Log

Attribute	**Description**	
Name	Contract-Event-Log	
Datatype		
Description	Indicates Contract Event log	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Auth Status A for Authorized; U for Unauthorized
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indciates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_MAKERID

Attribute	Description
Name	REVR_MAKERID
Datatype	String
Description	Indicates the Maker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_MAKERSTAMP

Attribute	Description
Name	REVR_MAKERSTAMP
Datatype	String
Description	Indicates the makerstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_CHECKERID

Attribute	Description
Name	REVR_CHECKERID
Datatype	String
Description	Indicates the checker id who has done the reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REVR_CHECKERSTAMP

Attribute	Description
Name	REVR_CHECKERSTAMP
Datatype	String

Description	Indicates the checkrstamp of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVR_AUTHSTAT

Attribute	Description
Name	REVR_AUTHSTAT
Datatype	String
Description	Indicates the Auth status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVR_CONTSTAT

Attribute	Description
Name	REVR_CONTSTAT
Datatype	String
Description	Indicates the Contract status of reversal of contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Schedule-Dates

Attribute	Description
Name	Schedule-Dates
Datatype	
Description	Includes Schedule Dates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DTOFCHNG

Attribute	Description
Name	DTOFCHNG
Datatype	Date
Description	Indicates Date Of Change
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Schedule-Summ

Attribute	Description
Name	Schedule-Summ
Datatype	
Description	Includes Scedules Summary details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBAMT

Attribute	Description
Name	SUBAMT
Datatype	Number
Description	Indicates Subsidy Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

DISAMTDUE

Attribute	Description
Name	DISAMTDUE
Datatype	Number
Description	Indicates Total Amount Due From Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISAMTSETTL

Attribute	Description
Name	DISAMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled By Customer
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DISADJAMT

Attribute	Description
Name	DISADJAMT
Datatype	Number
Description	Indicates Total Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Schedule-Details

Attribute	Description
Name	Schedule-Details
Datatype	
Description	Includes Schedule details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CCYAMTDUE

Attribute	Description
Name	CCYAMTDUE
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTSET

Attribute	Description
Name	AMTSET
Datatype	Number
Description	Indicates Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicates Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Amount-Settle

Attribute	Description
Name	Amount-Settle
Datatype	
Description	Includes Amount Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAIDDT

Attribute	Description
Name	PAIDDT
Datatype	Date
Description	Indicates Paid Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYSETTL

Attribute	Description

Name	CCYSETTL
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LCYEQSET

Attribute	Description
Name	LCYEQSET
Datatype	Number
Description	Indicates Local Equivalent Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

AMTSETTL

Attribute	Description
Name	AMTSETTL
Datatype	Number
Description	Indicates Total Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERDT

Attribute	Description
Name	MAKERDT
Datatype	Date
Description	Indicates Maker Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Includes Holiday Currency details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

CCYDESC

Attribute	**Description**	
Name	CCYDESC	
Datatype	String	
Description	Indicates Currency Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Rollover

Attribute	**Description**	
Name	Contract-Rollover	
Datatype		
Description	Includes Contract Rollover details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ROLLAMT

Attribute	**Description**	
Name	ROLLAMT	
Datatype	Number	
Description	Indicates Rollover Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Rollover Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Rollover Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Utilisation On Rollover Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRAWDOWNNO

Attribute	Description
Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,S,Q,Y

TOP

ROLLINTST

Attribute	Description
Name	ROLLINTST
Datatype	String
Description	Indicates Roll Inst. Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicates Mechanism New Version : V Spawn Contract : C Linked Contract : L
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates rollover type Auto : A Manual : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,I,T

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String

Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

TRESPLAMT

Attribute	Description
Name	TRESPLAMT
Datatype	String
Description	Indicates Treat Special Amount As Rollover Amount : A Liquidation Amount : L Maximum Rollover Amt : M Ignore : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,L,M,I

TOP

APPROLLTAX

Attribute	Description
Name	APPROLLTAX
Datatype	String
Description	Indicates Apply Tax On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

APPCHG

Attribute	Description
Name	APPCHG
Datatype	String
Description	Indicates Apply Charge On Rollover Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Number
Description	Indicates Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

Rvrintrates

Attribute	Description
Name	Rvrintrates
Datatype	
Description	Includes Rollover Interest Rates details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DEFFROM

Attribute	Description
Name	DEFFROM
Datatype	String
Description	Indicates Basis Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type Fixed : X Floating : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F

TOP

INTBASIS

Attribute	Description	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTBAS

Attribute	Description	
Name	INTBAS	
Datatype		
Description	Includes Interest basis details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String
Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Rate Code Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
fractionDigits	5
totalDigits	10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxInclusive	99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS Error Response type details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.4.LDContract-Rollover-Res-IOPK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-PK*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *BRN*
      - *PRD*
      - *CPTY*
      - *CPTYCONFSTAT*
      - *AMT*
      - *CCY*
      - *ORGL_STDT*
      - *TRNDT*
      - *VALDT*
      - *MAT_TYPE*
      - *NOTC_DAYS*
      - *DFLT_ACC*

DFLT_ACC_BRN
LINE
DEALER
BRK
BRKCONFSTAT
TDESC
AMORTYPE
AUTPROVREQD
CASCADESCHD
DEDTAXCAP
DFLTSETTCCY
DRSETLAC
DRSETLACBR
DRSETLCCY
EXPCAT
HOLMTH
HOLMTHFLG
IGHOL
LIQBVSCH
LIQODSCH
LNSTMTCYC
LNSTMTTYPE
MVACRMTH
NEWCOMP
PARPYMTMLIQ
PRINLIQN
RFEXPAMT
ROLLALLW
ROLLMETH
ROLLMECH
MATDT
SCHDDEFNBAS
SCHDMVMT
STMTDAY
STATCONT
TRCKRECVALIQ
TRCKRECVMLIQ
UPDUTLROLL
UDSTAT
VRFYFUND
VRFYFUNDINT
VRFYFUNDPLTY
VRFYFUNDPRIN
INTPERBAS

PRCCYTYP
UREF
PCREF
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*

COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5

RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT

INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2

REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT

- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

Contract_Schedules

- *SCOMP*
- *SCHD_TYPE*
- *FREQ*
- *FREQ_UNIT*
- *LCYEQINDLN*

- STDT
- NO_OF_SCHD
- AMT

Contract_Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Holiday-Currencies

- CCY
- CCYDESC

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY
  - BKMTHD
  - BOOKAMT
  - LIQSTAT
  - LREFNO

Advice-Details

- MSGTYPE

- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Contract-Rollover

- *ROLLTYPE*
- *ROLLAMTTYP*
- *ROLLAMT*
- *LIQDODSCHD*
- *SCHDBASIS*
- *UPDATEUTIL*
- *ROLLMATTYPE*
- *ROLLMATDT*
- *ROLLNOTDAYS*
- *ROLLICCFFROM*
- *ROLLBY*
- *APPCHG*
- *APPROLLTAX*
- *TRESPLAMT*
- *REFRATE*
- *ROLLMATDAYS*
- *ROLLMECH*
- *ROLLMETHD*
- *DRAWDOWNNO*
- *NEWCOMPALL*
- *INTBAS*
  - *INTCOMP*
  - *ROLLOIFROM*
  - *RATETYPE*
  - *RATEUSCD*
  - *INTRATE*
  - *INTBASIS*
  - *RATECD*
  - *SPREAD*
  - *MARGIN*

AMT

ROLSTENOR

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for Rollover the primary information relating the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-PK

Attribute	Description
Name	Contract-Master-PK
Datatype	
Description	Include Loans and deposits contract master PK type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Include Loans and deposits contract master IO type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	A unique reference number for the deal assigned by the external system. This reference can be used for any subsequent operations related to this deal with Flexcube.
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions**: pattern; **Description**: [a-zA-Z0-9]{16}

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: length; **Description**: 3 **Restrictions**: pattern; **Description**: [a-zA-Z_0-9]{3}

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the product
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: length; **Description**: 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	Indicates counter party.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYCONFSTAT

Attribute	Description
Name	CPTYCONFSTAT
Datatype	String
Description	Indicates Counterparty Confirm Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ORGL_STDT

Attribute	Description
Name	ORGL_STDT
Datatype	Date
Description	Indicate Original Start Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNDT

Attribute	Description
Name	TRNDT
Datatype	Date
Description	Indicate Transfer Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAT_TYPE

Attribute	Description
Name	MAT_TYPE
Datatype	String
Description	Indicate maturity type C Call N Notice F Fixed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

NOTC_DAYS

Attribute	Description
Name	NOTC_DAYS
Datatype	String
Description	Indicate Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DFLT_ACC

Attribute	Description
Name	DFLT_ACC
Datatype	String
Description	Indicate default credit account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

DFLT_ACC_BRN

Attribute	Description
Name	DFLT_ACC_BRN
Datatype	String
Description	Indicate default account branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

LINE

Attribute	Description
Name	LINE
Datatype	String
Description	Indicates Line Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRK

Attribute	Description	
Name	BRK	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BRKCONFSTAT

Attribute	Description	
Name	BRKCONFSTAT	
Datatype	String	
Description	Indicate broker confirmation status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TDESC

Attribute	Description	
Name	TDESC	
Datatype	String	
Description	Indicates description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

AMORTYPE

Attribute	Description	
Name	AMORTYPE	
Datatype	String	
Description	Indicates Amortisation Type Reducing Balance : R Rule 78 : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,O

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	Indicates Auto Provisioning required N:no Y:yes
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASCADESCHD

Attribute	Description
Name	CASCADESCHD
Datatype	String
Description	Indicate Cascade Schedules
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEDTAXCAP

Attribute	Description
Name	DEDTAXCAP
Datatype	String
Description	Indicates Deduct Tax on Capitalisatio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFLTSETTCCY

Attribute	Description
Name	DFLTSETTCCY
Datatype	String
Description	Indicates dafault settlement currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

DRSETLAC

Attribute	Description	
Name	DRSETLAC	
Datatype	String	
Description	Indicate Debit sett Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

DRSETLACBR

Attribute	Description	
Name	DRSETLACBR	
Datatype	String	
Description	Indicate Debit sett Account branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRSETLCCY

Attribute	Description	
Name	DRSETLCCY	
Datatype	String	
Description	Indicate debit settlement surrency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

EXPCAT

Attribute	Description	
Name	EXPCAT	
Datatype	String	
Description	Indicate Exposure Category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

HOLMTH

Attribute	Description	
Name	HOLMTH	
Datatype	String	
Description	Indicate Holiday Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

HOLMTHFLG

Attribute	Description	
Name	HOLMTHFLG	
Datatype	String	
Description	Indicate Holiday Month flag Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

IGHOL

Attribute	Description	
Name	IGHOL	
Datatype	String	
Description	Indicates ignore holidays Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQBVSCH

Attribute	Description	
Name	LIQBVSCH	
Datatype	String	
Description	Indicates Liquid Back Valued Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQODSCH

Attribute	Description	
Name	LIQODSCH	
Datatype	String	
Description	Indicate Liquidate Od Schedules	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LNSTMTCYC

Attribute	Description	
Name	LNSTMTCYC	
Datatype	String	
Description	Indicate Loan Statement Cycle	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,Q,M,F,W,D

TOP

LNSTMTTYPE

Attribute	Description	
Name	LNSTMTTYPE	
Datatype	String	
Description	Indicate loan statement type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,D,S

TOP

MVACRMTH

Attribute	Description	
Name	MVACRMTH	
Datatype	String	
Description	Indicate Move Across Months Y:yes N:no	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEWCOMP

Attribute	Description
Name	NEWCOMP
Datatype	String
Description	Indicates New Components Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARPYMTMLIQ

Attribute	Description
Name	PARPYMTMLIQ
Datatype	String
Description	Indicate Partial Payment Mliq
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRINLIQN

Attribute	Description
Name	PRINLIQN
Datatype	String
Description	Indicate Principal Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

RFEXPAMT

Attribute	Description
Name	RFEXPAMT
Datatype	Number
Description	Indicate Risk Free Exp Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLLALLW

Attribute	Description
Name	ROLLALLW
Datatype	String
Description	Indicate Rollover Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROLLMETH

Attribute	Description
Name	ROLLMETH
Datatype	String
Description	Indicate rollover method N Normal S Split C Consolidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,C

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDDEFNBAS

Attribute	Description
Name	SCHDDEFNBAS
Datatype	String
Description	Indicate Schedule Definition Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

SCHDMVMT

Attribute	Description
Name	SCHDMVMT
Datatype	String
Description	Indicate Schedule Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,B

TOP

STMTDAY

Attribute	Description
Name	STMTDAY
Datatype	Number
Description	Indicate Statement Day
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99

TOP

STATCONT

Attribute	Description
Name	STATCONT
Datatype	String
Description	Indicate Status Control
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

TRCKRECVALIQ

Attribute	Description
Name	TRCKRECVALIQ

Datatype	String
Description	Indicate Track Receivable Aliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECVMLIQ

Attribute	Description
Name	TRCKRECVMLIQ
Datatype	String
Description	Indicate Track Receivable Mliq
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPDUTLROLL

Attribute	Description
Name	UPDUTLROLL
Datatype	String
Description	Indicate Update Utilisation On Rollover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	Indicate User Defined Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VRFYFUND

Attribute	Description
Name	VRFYFUND
Datatype	String
Description	Indicate verify funds

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDINT

Attribute	**Description**	
Name	VRFYFUNDINT	
Datatype	String	
Description	Indicate Verify Funds For Interest	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPLTY

Attribute	**Description**	
Name	VRFYFUNDPLTY	
Datatype	String	
Description	Indicate Verify Funds For Penalty amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFUNDPRIN

Attribute	**Description**	
Name	VRFYFUNDPRIN	
Datatype	String	
Description	Indicate Verify Funds For Principal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTPERBAS

Attribute	**Description**
Name	INTPERBAS
Datatype	String
Description	Indicate Interest Period Basis F Include Frm Dt T Include To Dt B Include Frm & To Dt E Exclude Frm & To Dt

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,B,E

TOP

PRCCYTYP

Attribute	**Description**	
Name	PRCCYTYP	
Datatype	String	
Description	Indicate Prov Currency Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,L

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description	Indicate User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PCREF

Attribute	**Description**	
Name	PCREF	
Datatype	String	
Description	Indicate PC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Include Settlement type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3

Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC

Datatype	String
Description	Indicates the Sender Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number
Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String

Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3LBL3

Attribute	**Description**	
Name	FUNDMIS3LBL3	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4LBL4

Attribute	**Description**	
Name	FUNDMIS4LBL4	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS5LBL5

Attribute	**Description**	
Name	FUNDMIS5LBL5	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS6LBL6

Attribute	**Description**
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS7LBL7

Attribute	**Description**	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	**Description**	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS9LBL9

Attribute	**Description**	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	**Description**
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS1LBL1

Attribute	**Description**	
Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS2LBL2

Attribute	**Description**	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS3LBL3

Attribute	**Description**	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**

Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS balance transfer log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD
Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS chnage log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS refine rate Details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details

Datatype	
Description	Include UDF type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges application type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include charge association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ

Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include charge liquidation type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include interest main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description

Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indiactes the Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indiactes the Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MARGIN

Attribute	**Description**	
Name	MARGIN	
Datatype	Number	
Description	Indicates the margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	totalDigits	10

TOP

INTDESC

Attribute	**Description**
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	Description	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	Description	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax main type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract_Schedules

Attribute	Description
Name	Contract_Schedules
Datatype	
Description	Include contract schedule type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract_Linkages

Attribute	Description
Name	Contract_Linkages
Datatype	
Description	Include contract linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,A,B

TOP

LINK_CCY

Attribute	**Description**	
Name	LINK_CCY	
Datatype	String	
Description	Indicates the link currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINK_AMT

Attribute	**Description**	
Name	LINK_AMT	
Datatype	Number	
Description	Indicates the link amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

AVLAMT

Attribute	**Description**
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONV_LINK_AMT

Attribute	**Description**	
Name	CONV_LINK_AMT	
Datatype	Number	
Description	Indicates the converted linked amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LOAN_CCY

Attribute	**Description**	
Name	LOAN_CCY	
Datatype	String	
Description	Indicates the loan currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKBRANCH

Attribute	**Description**	
Name	LINKBRANCH	
Datatype	String	
Description	Indicates the Link branch.	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

LINKVALID

Attribute	**Description**	
Name	LINKVALID	
Datatype	String	
Description	Indicates the valid Link	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkages type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String

Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday-Currencies

Attribute	Description
Name	Holiday-Currencies
Datatype	
Description	Include holiday currencies type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	Indicates Currency Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include brokerage master type Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String

Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Include Settlement split master type Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

Contract-Rollover

Attribute	Description
Name	Contract-Rollover
Datatype	
Description	Include contract rollover type Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ROLLTYPE

Attribute	Description
Name	ROLLTYPE
Datatype	String
Description	Indicates Roll Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,M

TOP

ROLLAMTTYP

Attribute	Description
Name	ROLLAMTTYP
Datatype	String
Description	Indicates Rollover Amount Type Principal : P Principal + Interest : I Principal + (Interest - Tax) : T
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,I,T

TOP

ROLLAMT

Attribute	Description
Name	ROLLAMT
Datatype	Number
Description	Indicates Special Rollover Amount
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQDODSCHD

Attribute	Description
Name	LIQDODSCHD
Datatype	String
Description	Indicates Liquidate Overdue Schedules Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SCHDBASIS

Attribute	Description
Name	SCHDBASIS
Datatype	String
Description	Indicates Schedule Basis Product : P Contract : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

TOP

UPDATEUTIL

Attribute	Description
Name	UPDATEUTIL
Datatype	String
Description	Indicates Update Limits Utilisation Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ROLLMATTYPE

Attribute	Description
Name	ROLLMATTYPE
Datatype	String
Description	Indicates Rollover Maturity Type Fixed : F Notice : N Call : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,N,C

TOP

ROLLMATDT

Attribute	Description
Name	ROLLMATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ROLLNOTDAYS

Attribute	Description
Name	ROLLNOTDAYS
Datatype	String
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ROLLICCFFROM

Attribute	Description
Name	ROLLICCFFROM
Datatype	String
Description	Indicates ICCF Rollover Product : P Contract : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

ROLLBY

Attribute	Description
Name	ROLLBY
Datatype	String
Description	Indicates Roll By Days : D Months : M Quarters : Q SemiAnnuals : S Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,S,Q,Y

TOP

APPCHG

Attribute	**Description**	
Name	APPCHG	
Datatype	String	
Description	Indicates Apply charge on Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

APPROLLTAX

Attribute	**Description**	
Name	APPROLLTAX	
Datatype	String	
Description	Indicates Apply Tax On Rollover Amount Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRESPLAMT

Attribute	**Description**	
Name	TRESPLAMT	
Datatype	String	
Description	Indicates Treat Special Amount As Rollover Amount :A Liquidation Amount : L Maximum Rollover Amount : M Ignore : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,L,M,I

TOP

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Number

Description	Indicates Daily Refinance Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 11

TOP

ROLLMATDAYS

Attribute	Description
Name	ROLLMATDAYS
Datatype	Number
Description	Indicates Maturity Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 9999

TOP

ROLLMECH

Attribute	Description
Name	ROLLMECH
Datatype	String
Description	Indicate rollover mechanism V New Version C Spawn Contract L Linked Contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,C

TOP

ROLLMETHD

Attribute	Description
Name	ROLLMETHD
Datatype	String
Description	Indicates Rollover Method Normal : N Split : S Consolidated : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

DRAWDOWNNO

Attribute	Description

Name	DRAWDOWNNO
Datatype	Number
Description	Indicates Drawdown Sch No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999999999999

TOP

NEWCOMPALL

Attribute	Description
Name	NEWCOMPALL
Datatype	String
Description	Indicates New Components Allowed Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minLength / 1

TOP

INTBAS

Attribute	Description
Name	INTBAS
Datatype	
Description	Intereset Basis Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLLOIFROM

Attribute	Description
Name	ROLLOIFROM
Datatype	String

Description	Indicates Rollover ICCF From (Basis) Product : P Contract : C User Rate : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C,U

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

RATEUSCD

Attribute	Description
Name	RATEUSCD
Datatype	String
Description	Indicates Code Usage AUTO : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	Indicates Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ROLSTENOR

Attribute	Description
Name	ROLSTENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxInclusive / 99999

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include FCUBS error response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include FCUBS warning response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.LDVamiAuthorize

Authorization of Loans and Deposits Value Dated Amendment

2.47.1.LDContractVAMI-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Valuedated-Details*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*

VALDT
PRD
PROTYPEDESC
LATVERNO
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*

CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4

RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3

INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1

REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6

COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Interest-Main

- *INTCOMP*
- *VALDT*
- *TXNDT*
- *INTAMT*
- *CHDAMDMNT*
- *INTCCY*
- *EVNT*
- *ESN*
- *PKUPEVSQ*
- *INTBASIS*
- *INTRATE*
- *INTRATECODE*
- *INTSPREAD*

- *AQRDAMT*
- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*

- *Taxrule-Detail*
  - *ESN*
  - *TAXAMT*
  - *TAXCCY*
  - *VALDT*
  - *COMPDT*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*
  - *LINKVALID*
  - *LINK_SRNO*
  - *AMTBLKNO*
  - *LINKEFFDT*
  - *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*

- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Amountdue

- *FCCREF*
- *COMP*
- *DUEDT*
- *AMTDUE*
- *AMTSTD*
- *ADJAMT*

Change-Log

- *FCCREF*
- *FLDDESC*
- *OLDDISPVAL*
- *NEWDISPVAL*

Overrides

- *FCCREF*
- *OVDSN*
- *MODULE*
- *ERRCODE*
- *PARAM*
- *ONLAUTHID*
- *REMARKS*
- *AUTHBY*
- *AUTHDTSTAMP*

TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a request for Creation of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Valuedated-Details

Attribute	Description
Name	Valuedated-Details
Datatype	
Description	Includes Loans and Deposits Value Date Amendment Contract Authorize full details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROTYPEDESC

Attribute	**Description**	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description**: maxLength / 25; minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	Description	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates the Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	Description	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

UNT

Attribute	Description	
Name	UNT	
Datatype	String	
Description	Indicates the Unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y

TOP

NOUNIT

Attribute	Description	
Name	NOUNIT	
Datatype	Number	
Description	Indicates the No Of Units.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	5

TOP

RTCDUSE

Attribute	Description	
Name	RTCDUSE	
Datatype	String	
Description	Indicates the Interest rate code usage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	**Description**	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	**Description**	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	**Description**	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	**Description**	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Include Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	**Description**	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	**Description**	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	**Description**	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	**Description**	
Name	RELATIONSHIP	
Datatype	String	
Description	Relation element, It can be of alpha numerical with special characters.	
Restrictions	**Restrictions**	**Description**
	maxLength	10
	pattern	[a-zA-Z0-9]*

TOP

INHERIT

Attribute	**Description**	
Name	INHERIT	
Datatype	String	
Description	Indicates the Include Relationship.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Brokerage-Master

Attribute	**Description**	
Name	Brokerage-Master	
Datatype		
Description	Include Brokerage Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates flexcube Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.47.2.LDContractVAMI-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Valuedated-Details*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*
    - *VALDT*
    - *PRD*
    - *PROTYPEDESC*

LATVERNO

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*
  - *XPTACC*

XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER

RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4

- *CDFDOC*
- *ADDIDFR*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9

COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD

- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*

- TAXCCY
- VALDT
- COMPDT

Contract-Schedules

- SCOMP
- SCHD_TYPE
- FREQ
- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Contract-Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY

BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
Amountdue
FCCREF
COMP
DUEDT
AMTDUE
AMTSTD
ADJAMT
Change-Log
FCCREF
FLDDESC
OLDDISPVAL
NEWDISPVAL
Overrides
FCCREF
OVDSN
MODULE
ERRCODE
PARAM
ONLAUTHID
REMARKS
AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED

OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Valuedated-Details

Attribute	Description
Name	Valuedated-Details
Datatype	
Description	Includes Loans and Deposits Value Date Amendment Contract Authorize details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String

Description	Indicate product code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicate product type description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	Indicate Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Include Settlement Additional Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS8LBL8

Attribute	Description	
Name	TXNMIS8LBL8	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Include Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	**Description**	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	**Description**	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	**Description**	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description**
	maxLength / 10
	pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 1

TOP

Brokerage-Master

Attribute	**Description**
Name	Brokerage-Master
Datatype	
Description	Include Brokerage Master details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description**
	pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.LDDeleteVami

Deletion of Loans and Deposits Value dated amendment

2.48.1.LDContractVAMI-Delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*

VALDT
PRD
PROTYPEDESC
LATVERNO
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*

CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4

RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3

INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1

REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6

COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Interest-Main

- *INTCOMP*
- *VALDT*
- *TXNDT*
- *INTAMT*
- *CHDAMDMNT*
- *INTCCY*
- *EVNT*
- *ESN*
- *PKUPEVSQ*
- *INTBASIS*
- *INTRATE*
- *INTRATECODE*
- *INTSPREAD*

- *AQRDAMT*
- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*

- *Taxrule-Detail*
  - *ESN*
  - *TAXAMT*
  - *TAXCCY*
  - *VALDT*
  - *COMPDT*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*
  - *LINKVALID*
  - *LINK_SRNO*
  - *AMTBLKNO*
  - *LINKEFFDT*
  - *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*

- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*
- *EXRATE*

Amountdue

- *FCCREF*
- *COMP*
- *DUEDT*
- *AMTDUE*
- *AMTSTD*
- *ADJAMT*

Change-Log

- *FCCREF*
- *FLDDESC*
- *OLDDISPVAL*
- *NEWDISPVAL*

Overrides

- *FCCREF*
- *OVDSN*
- *MODULE*
- *ERRCODE*
- *PARAM*
- *ONLAUTHID*
- *REMARKS*
- *AUTHBY*
- *AUTHDTSTAMP*

TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a request for Creation of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Includes Loans and Deposits Value Date Amendment Contract Delete Master details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROTYPEDESC

Attribute	**Description**	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description	
Name	BNKPRIO	
Datatype	String	
Description	Indicates Banking Priority	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

BNFINSTCVR1

Attribute	Description	
Name	BNFINSTCVR1	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	Description	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	Description	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Taxdetails

Attribute	Description
Name	Taxdetails
Datatype	
Description	Include Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRULE

Attribute	Description
Name	TAXRULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	**Description**	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	**Description**	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	**Description**	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	**Description**	
Name	RELATIONSHIP	
Datatype	String	
Description	Relation element, It can be of alpha numerical with special characters.	
Restrictions	**Restrictions**	**Description**
	maxLength	10
	pattern	[a-zA-Z0-9]*

TOP

INHERIT

Attribute	**Description**	
Name	INHERIT	
Datatype	String	
Description	Indicates the Include Relationship.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Brokerage-Master

Attribute	**Description**	
Name	Brokerage-Master	
Datatype		
Description	Include Brokerage Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates flexcube Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.48.2.LDContractVAMI-Delete-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *XREF*
    - *FCCREF*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *MATDT*
    - *VALDT*
    - *Settlement-Addl-Details*
      - *ACCBRN*
      - *ACC_CCY*
      - *ACC*
      - *AMTTAG*
      - *CUSTSPRD*
      - *ERIAMT*
      - *ERICCY*
      - *XRATE*
      - *GENMSG*

NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF

ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2

FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5

LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*
- *PERIOD*
- *FINYR*
- *GLCODE*
- *CCY*
- *AMT*
- *EXRATE*

Mis-Change-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*

Mis-Amend

- *CONTREF*
- *RTYPE*
- *RCODE*
- *SPD*

Refinance-Rate

- *UNITREF*
- *BKDATE*
- *EFFDT*
- *REFRT*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*

LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC

- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*

LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT
CONVPAIDAMT
Relationship-Linkage
DESCP
CUSTOMER
RELATIONSHIP
INHERIT
Brokerage-Master
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a request for Creation of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Includes Loans and Deposits Value Date Amendment Contract Delete Master details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String

Description	Indicates the Reference Number of the External System.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicates the Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description

Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Indicates MIS Amendment Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String

Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	**Description**	
Name	LQDSTS	
Datatype	String	
Description	Indicates the Liquidation Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Interest-Main

Attribute	**Description**	
Name	Interest-Main	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Indicates Tax Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Indicates Contract Schedules Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description

Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

2.48.3.LDContractVAMI-Delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*
    - *VALDT*
    - *PRD*
    - *PROTYPEDESC*

LATVERNO

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*
  - *XPTACC*

XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER

RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4

- *CDFDOC*
- *ADDIDFR*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9

COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD

- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*

- TAXCCY
- VALDT
- COMPDT

Contract-Schedules

- SCOMP
- SCHD_TYPE
- FREQ
- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Contract-Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY

BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
Amountdue
FCCREF
COMP
DUEDT
AMTDUE
AMTSTD
ADJAMT
Change-Log
FCCREF
FLDDESC
OLDDISPVAL
NEWDISPVAL
Overrides
FCCREF
OVDSN
MODULE
ERRCODE
PARAM
ONLAUTHID
REMARKS
AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED

OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Includes Loans and Deposits Value Date Amendment Contract Delete Master details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String

Description	Indicate product code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PROTYPEDESC

Attribute	Description
Name	PROTYPEDESC
Datatype	String
Description	Indicate product type description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	Indicate Latest Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Include Settlement Additional Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	Description	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	Description	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	Description	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	Description	
Name	COMPMIS7LBL7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Mis-Amend

Attribute	**Description**	
Name	Mis-Amend	
Datatype		
Description	Include MIS amend Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONTREF

Attribute	**Description**
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	enumeration	U,D,I,R

TOP

CUSTMARG

Attribute	Description	
Name	CUSTMARG	
Datatype	Number	
Description	Indicates the Customer margin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

UNT

Attribute	Description	
Name	UNT	
Datatype	String	
Description	Indicates the Unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y

TOP

NOUNIT

Attribute	Description	
Name	NOUNIT	
Datatype	Number	
Description	Indicates the No Of Units.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	5

TOP

RTCDUSE

Attribute	Description	
Name	RTCDUSE	
Datatype	String	
Description	Indicates the Interest rate code usage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Taxdetails

Attribute	Description	
Name	Taxdetails	
Datatype		
Description	Include Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TAXRULE

Attribute	Description	
Name	TAXRULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

BASAMTTAG

Attribute	Description	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	**Description**	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	**Description**	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	**Description**	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description	
Name	RELATIONSHIP	
Datatype	String	
Description	Relation element, It can be of alpha numerical with special characters.	
Restrictions	**Restrictions**	**Description**
	maxLength	10
	pattern	[a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description	
Name	INHERIT	
Datatype	String	
Description	Indicates the Include Relationship.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Brokerage-Master

Attribute	Description	
Name	Brokerage-Master	
Datatype		
Description	Include Brokerage Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates flexcube Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.4.LDContractVAMI-Delete-Res-IOPK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-Pk*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *EVNT*
      - *EVNTDT*
      - *MAKERID*
      - *AMT*
      - *MATDT*
      - *VALDT*
      - *Settlement-Addl-Details*
        - *ACCBRN*
        - *ACC_CCY*
        - *ACC*
        - *AMTTAG*
        - *CUSTSPRD*

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*
- *COSTCOD1*

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*

- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY
  - BKMTHD
  - BOOKAMT
  - LIQSTAT
  - LREFNO

Advice-Details

- MSGTYPE
- PARTYID
- MEDIUM
- SUPPRESS
- PRIORITY
- CHGREQ

Settlement-Split-Master

- SNO
- SPAMTTG
- AMT
- BRN
- ACCCY
- ACC

EXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for detailing the primary information relating the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-Pk

Attribute	Description
Name	Contract-Master-Pk
Datatype	
Description	Includes Loans and Deposits Value Date Amendment Contract Delete Primary Key Master details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Includes Loans and Deposits Value Date Amendment Contract Delete Input Only Master details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String

Description	Indicates the Reference Number of the External System.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicates the Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	**Description**	
Name	ACC_INST3	
Datatype	String	
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST4

Attribute	**Description**	
Name	ACC_INST4	
Datatype	String	
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	

Restrictions	Description
maxLength	3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	

Restrictions	Description
maxLength	3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	

Restrictions	Description
maxLength	15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	

Restrictions	Description
maxLength	20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description

Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Indicates MIS Amendment Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String

Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
fractionDigits	8
totalDigits	13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	8
totalDigits	13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description**: enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Indicates Tax Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Contract-Schedules

Attribute	Description	
Name	Contract-Schedules	
Datatype		
Description	Indicates Contract Schedules Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCOMP

Attribute	Description	
Name	SCOMP	
Datatype	String	
Description	Indicates the component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	Description	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	Description

Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.LDVamiContract

Modification of Loans and Deposits Value Dated Amendment

2.49.1.LDContractVAMI-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*

VALDT
PRD
PROTYPEDESC
LATVERNO
Settlement-Addl-Details
- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*

CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4

RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3

INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1

REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6

COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Interest-Main

- *INTCOMP*
- *VALDT*
- *TXNDT*
- *INTAMT*
- *CHDAMDMNT*
- *INTCCY*
- *EVNT*
- *ESN*
- *PKUPEVSQ*
- *INTBASIS*
- *INTRATE*
- *INTRATECODE*
- *INTSPREAD*

- *AQRDAMT*
- *WAIVER*
- *ACREQD*
- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*

- *Taxrule-Detail*
  - *ESN*
  - *TAXAMT*
  - *TAXCCY*
  - *VALDT*
  - *COMPDT*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*
  - *LINKVALID*
  - *LINK_SRNO*
  - *AMTBLKNO*
  - *LINKEFFDT*
  - *CONVPAIDAMT*
- *Relationship-Linkage*
  - *DESCP*
  - *CUSTOMER*
  - *RELATIONSHIP*
  - *INHERIT*
- *Brokerage-Master*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*

- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *Advice-Details*
  - *MSGTYPE*
  - *PARTYID*
  - *MEDIUM*
  - *SUPPRESS*
  - *PRIORITY*
  - *CHGREQ*
- *Settlement-Split-Master*
  - *SNO*
  - *SPAMTTG*
  - *AMT*
  - *BRN*
  - *ACCCY*
  - *ACC*
  - *EXRATE*
- *Amountdue*
  - *FCCREF*
  - *COMP*
  - *DUEDT*
  - *AMTDUE*
  - *AMTSTD*
  - *ADJAMT*
- *Change-Log*
  - *FCCREF*
  - *FLDDESC*
  - *OLDDISPVAL*
  - *NEWDISPVAL*
- *Overrides*
  - *FCCREF*
  - *OVDSN*
  - *MODULE*
  - *ERRCODE*
  - *PARAM*
  - *ONLAUTHID*
  - *REMARKS*
  - *AUTHBY*
  - *AUTHDTSTAMP*

TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a request for Creation of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Includes Loans and Deposits Contract Value Date Amendment Input Only Master details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROTYPEDESC

Attribute	**Description**	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

CUSTSPRD

Attribute	Description	
Name	CUSTSPRD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	2000
minLength	1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

ULT_BKCD

Attribute	Description
Name	ULT_BKCD
Datatype	String
Description	Indicates the Ultimate bank code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDINFO1

Attribute	Description
Name	ADDINFO1
Datatype	String
Description	Indicates Additional information-1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO2

Attribute	Description
Name	ADDINFO2
Datatype	String
Description	Indicates Additional information-2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO3

Attribute	Description
Name	ADDINFO3
Datatype	String
Description	Indicates Additional information-3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDINFO4

Attribute	Description
Name	ADDINFO4
Datatype	String
Description	Indicates Additional information-4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTAMT

Attribute	**Description**	
Name	INTAMT	
Datatype	Number	
Description	Indicates the interest amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

INTCCY

Attribute	**Description**	
Name	INTCCY	
Datatype	String	
Description	Indicates the interest Component currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	String	
Description	Indicates the interest basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Taxdetails

Attribute	Description	
Name	Taxdetails	
Datatype		
Description	Include Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TAXRULE

Attribute	Description	
Name	TAXRULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

BASAMTTAG

Attribute	Description	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	**Description**	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	**Description**	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	**Description**	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions** / **Description** maxLength: 9 pattern: [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength: 10 pattern: [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Include Brokerage Master details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description	
Name	LREFNO	
Datatype	String	
Description	Indicates Latest Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

Advice-Details

Attribute	Description	
Name	Advice-Details	
Datatype		
Description	Include Advice Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description	Indicates the Message Type.	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description	Specify The Customer To Whom The Advice Is Being Despatched	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.49.2.LDContractVAMI-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-IO*
    - *XREF*
    - *FCCREF*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *MATDT*
    - *VALDT*
    - *Settlement-Addl-Details*
      - *ACCBRN*
      - *ACC_CCY*
      - *ACC*
      - *AMTTAG*
      - *CUSTSPRD*
      - *ERIAMT*
      - *ERICCY*
      - *XRATE*
      - *GENMSG*

NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF

ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2

FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5

LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*
- *PERIOD*
- *FINYR*
- *GLCODE*
- *CCY*
- *AMT*
- *EXRATE*

Mis-Change-Log

- *BRN*
- *REFNO*
- *MIS*
- *TXNDT*
- *OLDMIS*
- *NEWMIS*

Mis-Amend

- *CONTREF*
- *RTYPE*
- *RCODE*
- *SPD*

Refinance-Rate

- *UNITREF*
- *BKDATE*
- *EFFDT*
- *REFRT*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*

LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG
UNT
NOUNIT
RTCDUSE
CONASDISC

- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*
  - *AVLAMT*
  - *CONV_LINK_AMT*
  - *LOAN_CCY*
  - *LINKBRANCH*

LINKVALID
LINK_SRNO
AMTBLKNO
LINKEFFDT
CONVPAIDAMT
Relationship-Linkage
DESCP
CUSTOMER
RELATIONSHIP
INHERIT
Brokerage-Master
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the format in which the external system has to send a request for Creation of LDContract. This request is a full screen request which includes even input only fields and the display fields

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Includes Loans and Deposits Contract Value Date Amendment Input Only Master details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String

Description	Indicates the Reference Number of the External System.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicates the Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description

Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PERIOD

Attribute	Description
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Mis-Amend

Attribute	**Description**	
Name	Mis-Amend	
Datatype		
Description	Indicates MIS Amendment Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREF

Attribute	**Description**
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String

Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACREQD

Attribute	Description
Name	ACREQD
Datatype	String
Description	Indicates the accrual required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

MAXRRATE

Attribute	Description
Name	MAXRRATE
Datatype	Number
Description	Indicates the Maximum rate.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Indicates Tax Details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Contract-Schedules

Attribute	Description	
Name	Contract-Schedules	
Datatype		
Description	Indicates Contract Schedules Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCOMP

Attribute	Description	
Name	SCOMP	
Datatype	String	
Description	Indicates the component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	Description	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	Description

Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

2.49.3.LDContractVAMI-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master*
    - *FCCREF*
    - *XREF*
    - *CPTY*
    - *NAME*
    - *EVNT*
    - *EVNTDT*
    - *MAKERID*
    - *AMT*
    - *ORIG*
    - *CALCDT*
    - *AMTDT*
    - *MATDT*
    - *MDATE*
    - *DAMNT*
    - *CONTCCY*
    - *VALDT*
    - *PRD*
    - *PROTYPEDESC*

LATVERNO

Settlement-Addl-Details

- *ACCBRN*
- *ACC_CCY*
- *ACC*
- *AMTTAG*
- *CUSTSPRD*
- *ERIAMT*
- *ERICCY*
- *XRATE*
- *GENMSG*
- *NETACRSMOD*
- *PAYRCV*
- *RATECDDEFRD*
- *SPRDDFN*
- *TAG_CCY*
- *DRCRIND*
- *Settlement-Addl-Main*
  - *ACC_INST1*
  - *ACC_INST2*
  - *ACC_INST3*
  - *ACC_INST4*
  - *ACC_INST5*
  - *ACC_INST6*
  - *AGRID*
  - *AMTTAG*
  - *BNKPRIO*
  - *BNFINSTCVR1*
  - *BNFINSTCVR2*
  - *BNFINSTCVR3*
  - *BNFINSTCVR4*
  - *BNFINSTCVR5*
  - *BNFINSTCVR6*
  - *BENEF_INST1*
  - *BENEF_INST2*
  - *BENEF_INST3*
  - *BENEF_INST4*
  - *BENEF_INST5*
  - *BENEF_INST6*
  - *CHGDET*
  - *CLGNTW*
  - *CVRBY*
  - *COVER_REQ*
  - *XPTACC*

XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER

RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

Clearing-Details

FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4

CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
GENRT
FRETXT1
FRETXT2
FRETXT3
PMTCD
ADDINFOSBR
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9

COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE

Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS

Mis-Amend
CONTREF
RTYPE
RCODE
SPD

Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT

Udf-Details
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD

- *RTTYPE*
- *MAXRRATE*
- *MINRATE*
- *RETENOR*
- *BORLENIND*
- *RTCALCTYP*
- *CUSTMARG*
- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Taxdetails*
  - *TAXRULE*
  - *BASAMTTAG*
  - *COMPEVT*
  - *WAIVER*
  - *Taxrule-Detail*
    - *ESN*
    - *TAXAMT*

- TAXCCY
- VALDT
- COMPDT

Contract-Schedules

- SCOMP
- SCHD_TYPE
- FREQ
- FREQ_UNIT
- LCYEQINDLN
- STDT
- NO_OF_SCHD
- AMT

Contract-Linkages

- LINK_REF
- LINK_TYPE
- LINK_CCY
- LINK_AMT
- XRATE
- AVLAMT
- CONV_LINK_AMT
- LOAN_CCY
- LINKBRANCH
- LINKVALID
- LINK_SRNO
- AMTBLKNO
- LINKEFFDT
- CONVPAIDAMT

Relationship-Linkage

- DESCP
- CUSTOMER
- RELATIONSHIP
- INHERIT

Brokerage-Master

- FCCREF
- ESN
- BROKER
- BRKAMT
- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY

BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Settlement-Split-Master
SNO
SPAMTTG
AMT
BRN
ACCCY
ACC
EXRATE
Amountdue
FCCREF
COMP
DUEDT
AMTDUE
AMTSTD
ADJAMT
Change-Log
FCCREF
FLDDESC
OLDDISPVAL
NEWDISPVAL
Overrides
FCCREF
OVDSN
MODULE
ERRCODE
PARAM
ONLAUTHID
REMARKS
AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED

OVDREMARKS
OVDTXT
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for providing Full information of the LDContract details that are successfully defined in FLEXCUBE UBS

TOP

Contract-Master

Attribute	Description
Name	Contract-Master
Datatype	
Description	Includes Loans and Deposits Contract Value Date Amendment Master details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the reference number of the external system
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates counter party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicate event date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ORIG

Attribute	Description
Name	ORIG
Datatype	Number
Description	Indicate Rate
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

CALCDT

Attribute	Description
Name	CALCDT
Datatype	String
Description	Indicate calc date
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

TOP

AMTDT

Attribute	Description
Name	AMTDT
Datatype	Date
Description	Indicate Amendment Date
Attributes	

Attribute	Description
minOccurs	0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicate maturity date
Attributes	

Attribute	Description
minOccurs	0

TOP

MDATE

Attribute	Description
Name	MDATE
Datatype	Date
Description	Indicate Maturity Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DAMNT

Attribute	Description
Name	DAMNT
Datatype	Number
Description	Indicate Change in principal amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicate Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicate product code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROTYPEDESC

Attribute	**Description**	
Name	PROTYPEDESC	
Datatype	String	
Description	Indicate product type description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	String	
Description	Indicate Latest Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Addl-Details

Attribute	**Description**	
Name	Settlement-Addl-Details	
Datatype		
Description	Include Settlement Additional Type Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Include Settlement Type Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35
minLength	1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	2000
minLength	1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Include Settlement clearing Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	

Restrictions	Description
maxLength	3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	

Restrictions	Description
maxLength	3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	

Restrictions	Description
maxLength	15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	

Restrictions	Description
maxLength	20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

GENRT

Attribute	**Description**
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Include MIS Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Include MIS Balance Transfer LOG Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Include MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Include MIS amend Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Include MIS Refine Rate Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF

Datatype	String
Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Include UDFType Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Include charges Application Type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Include Charge Association type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Include Charge Liquidation type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String

Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Interest-Main

Attribute	Description
Name	Interest-Main
Datatype	
Description	Include Interest Main type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicate event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

CONASDISC

Attribute	Description	
Name	CONASDISC	
Datatype	String	
Description	Indicates whether to consider discount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DENOBASIS

Attribute	Description	
Name	DENOBASIS	
Datatype	String	
Description	Indicates the Denominator basis.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description	Indicates the BASIS_366	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOINTPRD

Attribute	Description	
Name	NOINTPRD	
Datatype	Number	
Description	Indicates the No of Interest Period.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Include Tax Main type details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Taxdetails

Attribute	Description	
Name	Taxdetails	
Datatype		
Description	Include Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TAXRULE

Attribute	Description	
Name	TAXRULE	
Datatype	String	
Description	Indicates tax rule that should be applied to the contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

BASAMTTAG

Attribute	Description	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPEVT

Attribute	Description

Name	COMPEVT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxrule-Detail

Attribute	Description
Name	Taxrule-Detail
Datatype	
Description	Specifies Tax Rule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXAMT

Attribute	Description
Name	TAXAMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicate value date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDT

Attribute	Description
Name	COMPDT
Datatype	Date
Description	Indicates Transaction Date

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Include Contract Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SCHD_TYPE

Attribute	**Description**	
Name	SCHD_TYPE	
Datatype	String	
Description	Indicates the schedule type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R,C,D

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates the frequency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	**Description**	
Name	FREQ_UNIT	
Datatype	Number	
Description	Indicates the frequency unit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	14

TOP

LCYEQINDLN

Attribute	**Description**	
Name	LCYEQINDLN	
Datatype	Number	
Description	Local Currency equivalent	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Include Contract Linkages details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3 pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description

Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

LINKEFFDT

Attribute	Description

Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include Relationship Linkage details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	**Description**	
Name	RELATIONSHIP	
Datatype	String	
Description	Relation element, It can be of alpha numerical with special characters.	
Restrictions	**Restrictions**	**Description**
	maxLength	10
	pattern	[a-zA-Z0-9]*

TOP

INHERIT

Attribute	**Description**	
Name	INHERIT	
Datatype	String	
Description	Indicates the Include Relationship.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Brokerage-Master

Attribute	**Description**	
Name	Brokerage-Master	
Datatype		
Description	Include Brokerage Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates flexcube Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**

Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Include Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description

Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master

Datatype	
Description	Include Settlement Split Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicate amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates the account currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Amountdue

Attribute	Description
Name	Amountdue
Datatype	
Description	Include Loans and Deposits AmountDue type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicate due date

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicate amount due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

AMTSTD

Attribute	Description
Name	AMTSTD
Datatype	Number
Description	Indicate Amount Settled
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

ADJAMT

Attribute	Description
Name	ADJAMT
Datatype	Number
Description	Indicate Amount Adjusted
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

Change-Log

Attribute	Description
Name	Change-Log
Datatype	
Description	Include Change Log details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	

Restrictions	Description
pattern	[a-zA-Z0-9]{16}

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicate Field Description
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicate old value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicate New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Include override type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates the User ID of the person who is Authorising the override online.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicate the Remarks provided by the online authorizer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHBY

Attribute	**Description**	
Name	AUTHBY	
Datatype	String	
Description	Indicates the User id who has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHDTSTAMP

Attribute	**Description**	
Name	AUTHDTSTAMP	
Datatype	String	
Description	Indicates date stamp when the user has authorized	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTSTATUS

Attribute	**Description**	
Name	TXTSTATUS	
Datatype	String	
Description	Indicates the Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDSTATUS

Attribute	**Description**	
Name	OVDSTATUS	
Datatype	String	
Description	Indicates the Overridden status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates whether the override is confirmed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates the override remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates the Override text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Include contract event details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicate maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicate maker stamp

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicate checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicate checker stamp
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicate authorisation status A:authorised U:unauthorised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicate Contract Status A Active H Hold V Reversed S Closed K Cancelled
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.4.LDContractVAMI-Res-IOPK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-Pk*
      - *XREF*
      - *FCCREF*
    - *Contract-Master-IO*
      - *XREF*
      - *FCCREF*
      - *EVNT*
      - *EVNTDT*
      - *MAKERID*
      - *AMT*
      - *MATDT*
      - *VALDT*
      - *Settlement-Addl-Details*
        - *ACCBRN*
        - *ACC_CCY*
        - *ACC*
        - *AMTTAG*
        - *CUSTSPRD*

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Settlement-Details

AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3

INSTRCDTXT4
INSTRCDTXT5
Clearing-Details
FCCREF
ESN
AMTTAG
BRNCD
MSGTYPE
CLGNW
CRBNCD
SNDR_CUSNM1
SNDR_CUSNM2
SNDR_CUSNM3
SNDR_CUSNM4
RCVR_CUSNM1
RCVR_CUSNM2
RCVR_CUSNM3
RCVR_CUSNM4
SNDR_RCVR_PRCNT
SNDR_ACC
RCVR_ACC
ULT_BKCD
ADDINFO1
ADDINFO2
ADDINFO3
ADDINFO4
NIPPYR
SUPPID
PYRIDFR
PYMTTYPE
DLCLR
NOFDCLR
NOFCHK
REPRRES1
REPRRES2
REPRRES3
REPRRES4
CDFDOC
ADDIDFR
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

- *SNDR_INFO6*
- *GENRT*
- *FRETXT1*
- *FRETXT2*
- *FRETXT3*
- *PMTCD*
- *ADDINFOSBR*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*
- *COSTCOD1*

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Balance-Trnsfer-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
PERIOD
FINYR
GLCODE
CCY
AMT
EXRATE
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
Refinance-Rate
UNITREF
BKDATE
EFFDT
REFRT
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Application
CHGCOMP
CRNESN
TGCCY

TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Interest-Main
INTCOMP
VALDT
TXNDT
INTAMT
CHDAMDMNT
INTCCY
EVNT
ESN
PKUPEVSQ
INTBASIS
INTRATE
INTRATECODE
INTSPREAD
AQRDAMT
WAIVER
ACREQD
RTTYPE
MAXRRATE
MINRATE
RETENOR
BORLENIND
RTCALCTYP
CUSTMARG

- *UNT*
- *NOUNIT*
- *RTCDUSE*
- *CONASDISC*
- *DENOBASIS*
- *BASIS366*
- *NOINTPRD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *INTDESC*
- *INTCMPDESC*
- *EFFCTIVERATE*
- *Interest-Details*
  - *VALDT*
  - *TXNDT*
  - *INTAMT*
  - *INTCCY*
  - *ESN*
  - *INTBASIS*
  - *INTRATE*
  - *INTRATECODE*
  - *INTSPREAD*
  - *AQRDAMT*
  - *RTTYPE*
- *Taxdetails-Main*
  - *SCHEME*
  - *WAIVER*
  - *SCHEMEDESC*
- *Contract-Schedules*
  - *SCOMP*
  - *SCHD_TYPE*
  - *FREQ*
  - *FREQ_UNIT*
  - *LCYEQINDLN*
  - *STDT*
  - *NO_OF_SCHD*
  - *AMT*
- *Contract-Linkages*
  - *LINK_REF*
  - *LINK_TYPE*
  - *LINK_CCY*
  - *LINK_AMT*
  - *XRATE*

- *AVLAMT*
- *CONV_LINK_AMT*
- *LOAN_CCY*
- *LINKBRANCH*
- *LINKVALID*
- *LINK_SRNO*
- *AMTBLKNO*
- *LINKEFFDT*
- *CONVPAIDAMT*

Relationship-Linkage

- *DESCP*
- *CUSTOMER*
- *RELATIONSHIP*
- *INHERIT*

Brokerage-Master

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Advice-Details

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Settlement-Split-Master

- *SNO*
- *SPAMTTG*
- *AMT*
- *BRN*
- *ACCCY*
- *ACC*

EXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for detailing the primary information relating the LD Contract that has been successfully created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-Pk

Attribute	Description
Name	Contract-Master-Pk
Datatype	
Description	Includes Loans and Deposits Contract Value Date Amendment Primary Key Master details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

Contract-Master-IO

Attribute	Description
Name	Contract-Master-IO
Datatype	
Description	Includes Loans and Deposits Contract Value Date Amendment Input Only Master details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String

Description	Indicates the Reference Number of the External System.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTDT

Attribute	Description
Name	EVNTDT
Datatype	Date
Description	Indicates the Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Indicates Settlement Additional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**	
Name	Settlement-Addl-Main	
Datatype		
Description	Indicates Settlement Additional Main details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	Description	
Name	SNDR_INFO3	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	Description	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	Description	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Settlement-Details

Attribute	**Description**
Name	Settlement-Details
Datatype	
Description	Indicates Settlement Details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	Indicates Settlement Clearing Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CLGNW

Attribute	Description
Name	CLGNW
Datatype	String
Description	Indicates the Clearing Network code
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

CRBNCD

Attribute	Description
Name	CRBNCD
Datatype	String
Description	Indicates the Credit Branch code
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

SNDR_CUSNM1

Attribute	Description
Name	SNDR_CUSNM1
Datatype	String
Description	Indicates the Sender Information 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM2

Attribute	Description
Name	SNDR_CUSNM2
Datatype	String
Description	Indicates the Sender Information 2
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM3

Attribute	Description
Name	SNDR_CUSNM3
Datatype	String
Description	Indicates the Sender Information 3
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDR_CUSNM4

Attribute	Description
Name	SNDR_CUSNM4
Datatype	String
Description	Indicates the Sender Information 4
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM1

Attribute	Description
Name	RCVR_CUSNM1
Datatype	String
Description	Indicates the Receiver Name 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVR_CUSNM2

Attribute	Description
Name	RCVR_CUSNM2
Datatype	String
Description	Indicates the Receiver Name 2
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM3

Attribute	Description
Name	RCVR_CUSNM3
Datatype	String
Description	Indicates the Receiver Name 3
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVR_CUSNM4

Attribute	Description
Name	RCVR_CUSNM4
Datatype	String
Description	Indicates the Receiver Name 4
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDR_RCVR_PRCNT

Attribute	Description
Name	SNDR_RCVR_PRCNT
Datatype	Number
Description	Indicates the Sender - Receiver participant

TOP

SNDR_ACC

Attribute	Description
Name	SNDR_ACC
Datatype	String
Description	Indicates the Sender Account
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

RCVR_ACC

Attribute	Description
Name	RCVR_ACC
Datatype	String
Description	Indicates the Receiver Account

Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

ULT_BKCD

Attribute	Description	
Name	ULT_BKCD	
Datatype	String	
Description	Indicates the Ultimate bank code	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDINFO1

Attribute	Description	
Name	ADDINFO1	
Datatype	String	
Description	Indicates Additional information-1	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO2

Attribute	Description	
Name	ADDINFO2	
Datatype	String	
Description	Indicates Additional information-2	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO3

Attribute	Description	
Name	ADDINFO3	
Datatype	String	
Description	Indicates Additional information-3	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDINFO4

Attribute	Description	
Name	ADDINFO4	
Datatype	String	
Description	Indicates Additional information-4	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPYR

Attribute	Description
Name	NIPPYR
Datatype	Number
Description	Indicates the NIP Payer

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates the Supplement Identification
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PYRIDFR

Attribute	Description
Name	PYRIDFR
Datatype	String
Description	Indicates the Payer Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>14</td></tr></table>

TOP

PYMTTYPE

Attribute	Description
Name	PYMTTYPE
Datatype	String
Description	Indicates the Payment type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DLCLR

Attribute	Description
Name	DLCLR
Datatype	Number
Description	Indicates the Declaration

TOP

NOFDCLR

Attribute	Description
Name	NOFDCLR
Datatype	Number

Description	Indicates the No. of Declaration

TOP

NOFCHK

Attribute	Description
Name	NOFCHK
Datatype	String
Description	Indicates the No. of checks required in the settlement
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REPRRES1

Attribute	Description
Name	REPRRES1
Datatype	String
Description	Indicates the Repair Reason 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES2

Attribute	Description
Name	REPRRES2
Datatype	String
Description	Indicates the Repair Reason 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES3

Attribute	Description
Name	REPRRES3
Datatype	String
Description	Indicates the Repair Reason 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRRES4

Attribute	Description
Name	REPRRES4
Datatype	String
Description	Indicates the Repair Reason 4
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CDFDOC

Attribute	Description
Name	CDFDOC
Datatype	Number
Description	Indicates the Code of Documents

TOP

ADDIDFR

Attribute	Description
Name	ADDIDFR
Datatype	String
Description	Indicates the Additional Identifier
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

GENRT

Attribute	Description
Name	GENRT
Datatype	String
Description	Indicates to Generate Data

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRETXT1

Attribute	Description
Name	FRETXT1
Datatype	String
Description	Indicates Free text 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT2

Attribute	Description
Name	FRETXT2
Datatype	String
Description	Indicates Free text 2
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRETXT3

Attribute	Description
Name	FRETXT3
Datatype	String
Description	Indicates Free text 3
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMTCD

Attribute	Description
Name	PMTCD
Datatype	String
Description	Indicates the Payment code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSBR

Attribute	Description
Name	ADDINFOSBR
Datatype	String
Description	Indicates Additional information
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Indicates MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description

Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Balance-Trnsfer-Log

Attribute	Description
Name	Balance-Trnsfer-Log
Datatype	
Description	Indicates Balance Transfer Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	**Description**	
Name	NEWMIS	
Datatype	String	
Description	Indicates New MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PERIOD

Attribute	**Description**
Name	PERIOD

Datatype	String
Description	Indicates Period
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates Financial Year
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates GL Code
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Indicates MIS Change Log Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Indicates MIS Amendment Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Refinance-Rate

Attribute	Description
Name	Refinance-Rate
Datatype	
Description	Indicates MIS Refinance Rate Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITREF

Attribute	Description
Name	UNITREF
Datatype	String

Description	Indicates the Unit Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BKDATE

Attribute	Description
Name	BKDATE
Datatype	Date
Description	Indicates the Booking date

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Indicates User Defined Fields Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Indicates Charge Application Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Indicates Charge Association Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Indicates Charge Liquidation Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	**Description**	
Name	LQDSTS	
Datatype	String	
Description	Indicates the Liquidation Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Interest-Main

Attribute	**Description**	
Name	Interest-Main	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates the interest Component.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHDAMDMNT

Attribute	Description
Name	CHDAMDMNT
Datatype	String
Description	Indicates whether the Interest can be Changed during Amendment or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates the Event.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PKUPEVSQ

Attribute	Description
Name	PKUPEVSQ
Datatype	Number
Description	Indicates the Pick Up Event Sequence of the Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

INTBASIS

Attribute	Description
Name	INTBASIS

Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates the interest rate.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

INTRATECODE

Attribute	Description
Name	INTRATECODE
Datatype	String
Description	Indicates the interest rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSPREAD

Attribute	Description
Name	INTSPREAD
Datatype	Number
Description	Indicates the interest spread.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

AQRDAMT

Attribute	Description
Name	AQRDAMT
Datatype	Number
Description	Indicates the Acquired amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACREQD

Attribute	**Description**	
Name	ACREQD	
Datatype	String	
Description	Indicates the accrual required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RTTYPE

Attribute	**Description**	
Name	RTTYPE	
Datatype	String	
Description	Indicates the Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

MAXRRATE

Attribute	**Description**	
Name	MAXRRATE	
Datatype	Number	
Description	Indicates the Maximum rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates the Minimum rate.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 8 totalDigits: 13

TOP

RETENOR

Attribute	Description
Name	RETENOR
Datatype	Number
Description	Indicates the Tenor
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 5

TOP

BORLENIND

Attribute	Description
Name	BORLENIND
Datatype	String
Description	Indicates the Borrow \ Lend Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	Indicates the Interest Rate Calculation type
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description**: enumeration / U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	Indicates the Customer margin.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 8; totalDigits / 13

TOP

UNT

Attribute	Description
Name	UNT
Datatype	String
Description	Indicates the Unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates the No Of Units.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

RTCDUSE

Attribute	Description
Name	RTCDUSE
Datatype	String
Description	Indicates the Interest rate code usage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CONASDISC

Attribute	Description
Name	CONASDISC
Datatype	String
Description	Indicates whether to consider discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOBASIS

Attribute	Description
Name	DENOBASIS
Datatype	String
Description	Indicates the Denominator basis.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	Indicates the BASIS_366
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOINTPRD

Attribute	Description
Name	NOINTPRD
Datatype	Number
Description	Indicates the No of Interest Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indiactes the Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indiactes the Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	Indicates the margin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 totalDigits / 10

TOP

INTDESC

Attribute	Description
Name	INTDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INTCMPDESC

Attribute	Description
Name	INTCMPDESC
Datatype	String
Description	Indicates the interest Component description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EFFCTIVERATE

Attribute	Description
Name	EFFCTIVERATE
Datatype	Number
Description	Indicates the Effective rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Interest-Details

Attribute	Description
Name	Interest-Details
Datatype	
Description	Indicates Interest details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates the Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	Indicates the interest amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INTCCY

Attribute	Description
Name	INTCCY
Datatype	String
Description	Indicates the interest Component currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	String
Description	Indicates the interest basis.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	0,1,2,3,4,5,6,7,8,9,-1,-2

TOP

INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Indicates the interest rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

INTRATECODE

Attribute	Description	
Name	INTRATECODE	
Datatype	String	
Description	Indicates the interest rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTSPREAD

Attribute	Description	
Name	INTSPREAD	
Datatype	Number	
Description	Indicates the interest spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

AQRDAMT

Attribute	Description	
Name	AQRDAMT	
Datatype	Number	
Description	Indicates the Acquired amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

RTTYPE

Attribute	Description
Name	RTTYPE
Datatype	String
Description	Indicates the Rate type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: X,F,S

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Indicates Tax Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Contract-Schedules

Attribute	Description
Name	Contract-Schedules
Datatype	
Description	Indicates Contract Schedules Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCOMP

Attribute	Description
Name	SCOMP
Datatype	String
Description	Indicates the component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SCHD_TYPE

Attribute	Description
Name	SCHD_TYPE
Datatype	String
Description	Indicates the schedule type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,C,D

TOP

FREQ

Attribute	Description

Name	FREQ
Datatype	String
Description	Indicates the frequency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,B

TOP

FREQ_UNIT

Attribute	Description
Name	FREQ_UNIT
Datatype	Number
Description	Indicates the frequency unit.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

TOP

LCYEQINDLN

Attribute	Description
Name	LCYEQINDLN
Datatype	Number
Description	Local Currency equivalent
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

STDT

Attribute	Description
Name	STDT
Datatype	Date
Description	Indicates the Start Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_OF_SCHD

Attribute	Description
Name	NO_OF_SCHD
Datatype	Number
Description	Indicates the No of Schedules.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 14

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Linkages

Attribute	Description
Name	Contract-Linkages
Datatype	
Description	Indicates Contract Linkages Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINK_REF

Attribute	Description
Name	LINK_REF
Datatype	String
Description	Indicates the Link Reference No.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINK_TYPE

Attribute	Description
Name	LINK_TYPE
Datatype	String
Description	Indicates the link type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,A,B

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	Indicates the link currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

LINK_AMT

Attribute	Description
Name	LINK_AMT
Datatype	Number
Description	Indicates the link amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

AVLAMT

Attribute	Description
Name	AVLAMT
Datatype	Number
Description	Indicates the Available amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONV_LINK_AMT

Attribute	Description
Name	CONV_LINK_AMT
Datatype	Number
Description	Indicates the converted linked amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LOAN_CCY

Attribute	Description
Name	LOAN_CCY
Datatype	String
Description	Indicates the loan currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKBRANCH

Attribute	Description
Name	LINKBRANCH
Datatype	String
Description	Indicates the Link branch.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKVALID

Attribute	Description
Name	LINKVALID
Datatype	String
Description	Indicates the valid Link
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

LINK_SRNO

Attribute	Description
Name	LINK_SRNO
Datatype	String
Description	Indicates the Link-serial Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the amount block number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LINKEFFDT

Attribute	Description
Name	LINKEFFDT
Datatype	String
Description	Indicates the link effective date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CONVPAIDAMT

Attribute	Description
Name	CONVPAIDAMT
Datatype	String
Description	Indicates the converted amount paid.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Indicates Relationship Linkage Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	It gives the description about Relationship Linkage.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Customer number element.
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Relation element, It can be of alpha numerical with special characters.
Restrictions	**Restrictions** / **Description** maxLength / 10 pattern / [a-zA-Z0-9]*

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicates the Include Relationship.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Brokerage-Master

Attribute	Description
Name	Brokerage-Master
Datatype	
Description	Indicates Brokerage Master Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT

Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates tax rule that should be applied to the contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Indicates Advice Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Settlement-Split-Master

Attribute	Description
Name	Settlement-Split-Master
Datatype	
Description	Indicates Settlement Split Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNO

Attribute	Description
Name	SNO
Datatype	Number
Description	Indicates the serial No.
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

SPAMTTG

Attribute	Description
Name	SPAMTTG
Datatype	String
Description	Indicates the Amount Tag.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCY

Attribute	**Description**	
Name	ACCCY	
Datatype	String	
Description	Indicates the account currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.50.AuthLDPayment

Authorization of Loans and Deposits Payments

2.50.1.LDPayment-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Paymentauth-Details*
    - *XREF*
    - *FCCREF*
    - *OSAMT*
    - *AMT*
    - *CPTY*
    - *CCY*
    - *USRDEFSTAT*
    - *PAYSTAT*
    - *VALDT*
    - *TOTPAID*
    - *PREPAYPENRATE*
    - *PREPAYPENAMT*
    - *PAYREM*
    - *Payment-BreakUp*
      - *FCCREF*

AMTDUE
OVERDUE
AMTPAID
TAXPAID
Overrides
OVDSN
MODULE
ERRCODE
PARAM
ONLAUTHID
REMARKS
AUTHBY
AUTHDTSTAMP
TXTSTATUS
OVDSTATUS
CONFIRMED
OVDREMARKS
OVDTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	FCUBS Header details

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	FCUBS Body details

TOP

Paymentauth-Details

Attribute	Description
Name	Paymentauth-Details
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates FCC Contract Reference Number.

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT

Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	It indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRDEFSTAT

Attribute	Description
Name	USRDEFSTAT
Datatype	String
Description	Indicates User Defined Status
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYSTAT

Attribute	Description
Name	PAYSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOTPAID

Attribute	**Description**	
Name	TOTPAID	
Datatype	Number	
Description	Indicates Total Paid	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREPAYPENRATE

Attribute	**Description**	
Name	PREPAYPENRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREPAYPENAMT

Attribute	**Description**	
Name	PREPAYPENAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYREM

Attribute	**Description**	
Name	PAYREM	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Payment-BreakUp

Attribute	**Description**
Name	Payment-BreakUp
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates FCC Contract Reference Number.

TOP

AMTDUE

Attribute	Description	
Name	AMTDUE	
Datatype	Number	
Description	Indicates Amount Due	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVERDUE

Attribute	Description	
Name	OVERDUE	
Datatype	Number	
Description	Indicates Over Due.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description	Indicates the Amount Paid.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXPAID

Attribute	Description	
Name	TAXPAID	
Datatype	Number	
Description	Indicates the Tax Paid.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Overrides

Attribute	Description
Name	Overrides
Datatype	
Description	Overrides
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Event Sequence NUmber.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates The Module
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID
Datatype	String
Description	Indicates Onlie Authorizer Id.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHBY

Attribute	Description
Name	AUTHBY
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHDTSTAMP

Attribute	Description
Name	AUTHDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTSTATUS

Attribute	Description
Name	TXTSTATUS
Datatype	String
Description	Indicates Transaction Status A Authorised; U Unauthorised; R Rejected.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDSTATUS

Attribute	Description
Name	OVDSTATUS
Datatype	String
Description	Indicates Override Status.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates Override Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates Override Text.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.50.2.LDPayment-Auth-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Paymentauth-Details*
    - *XREF*
    - *FCCREF*
    - *OSAMT*
    - *AMT*
    - *CPTY*
    - *CCY*
    - *USRDEFSTAT*
    - *PAYSTAT*
    - *VALDT*
    - *TOTPAID*
    - *PREPAYPENRATE*
    - *PREPAYPENAMT*
    - *PAYREM*
    - *Payment-BreakUp*
      - *FCCREF*
      - *AMTDUE*
      - *OVERDUE*
      - *AMTPAID*

TAXPAID

Overrides

OVDSN

MODULE

ERRCODE

PARAM

ONLAUTHID

REMARKS

AUTHBY

AUTHDTSTAMP

TXTSTATUS

OVDSTATUS

CONFIRMED

OVDREMARKS

OVDTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	FCUBS Header details

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	FCUBS Body details

TOP

Paymentauth-Details

Attribute	Description
Name	Paymentauth-Details
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates FCC Contract Reference Number.

TOP

OSAMT

Attribute	Description
Name	OSAMT
Datatype	Number
Description	Indicates Outstanding Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description	It indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

USRDEFSTAT

Attribute	**Description**	
Name	USRDEFSTAT	
Datatype	String	
Description	Indicates User Defined Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYSTAT

Attribute	**Description**	
Name	PAYSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYPENRATE

Attribute	Description
Name	PREPAYPENRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYPENAMT

Attribute	Description
Name	PREPAYPENAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYREM

Attribute	Description
Name	PAYREM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Payment-BreakUp

Attribute	Description
Name	Payment-BreakUp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates FCC Contract Reference Number.

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVERDUE

Attribute	Description
Name	OVERDUE
Datatype	Number
Description	Indicates Over Due.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTPAID

Attribute	Description
Name	AMTPAID
Datatype	Number
Description	Indicates the Amount Paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXPAID

Attribute	Description
Name	TAXPAID
Datatype	Number
Description	Indicates the Tax Paid.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Overrides

Attribute	Description

Name	Overrides
Datatype	
Description	Overrides
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDSN

Attribute	Description
Name	OVDSN
Datatype	String
Description	Indicates Override Event Sequence NUmber.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates The Module
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	Indicates Error Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ONLAUTHID

Attribute	Description
Name	ONLAUTHID

Datatype	String
Description	Indicates Onlie Authorizer Id.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHBY

Attribute	Description
Name	AUTHBY
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHDTSTAMP

Attribute	Description
Name	AUTHDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTSTATUS

Attribute	Description
Name	TXTSTATUS
Datatype	String
Description	Indicates Transaction Status A Authorised; U Unauthorised; R Rejected.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVDSTATUS

Attribute	Description
Name	OVDSTATUS
Datatype	String
Description	Indicates Override Status.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDREMARKS

Attribute	Description
Name	OVDREMARKS
Datatype	String
Description	Indicates Override Remarks.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDTXT

Attribute	Description
Name	OVDTXT
Datatype	String
Description	Indicates Override Text.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deposits Service
[April] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2013], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.